



Floor Stand





QP3380FS - 33U



Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)











Top Cover Vented Design

Equipment Tray

19" 5 Gang Power Distribution

Earthing cable

Side Panel Latch

19" Panel Mounting

Model	Capasity (U)		Width (mm)	_	Packing Dimension (H*W*D)	Weight (kg)
QP3380FS	33	1612	600	800	1635 x 612 x 812	90





Beige

* Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD *NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,* Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvisb.com.my **Penang Branch** 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

Johor Branch No.49 & 49A, Jalan Pulai 23, Taman Pulai Utama, 81300 Skudai, Johor, Malaysia +607 - 520 5236

^{*} Customized sizes available upon request