

# Floor Stand


**X** SERIES

**XP1580FS - 15U**




## Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg



*Top Cover  
Vented Design*



*Equipment  
Tray*



*Ball Bearing  
Fans*



*Earthing  
cable*



*Side Panel  
Latch*



*19" Panel  
Mounting*

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)	PDU (nos)
XP1580FS	15	850	600	800	862 x 612 x 812	93	5

☒ Black
 ☐ Grey
 ☐ Beige

\* Customized sizes available upon request  
 \* Product shown is for illustration purpose only



**GV INDUSTRIES SDN. BHD**  
 NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,  
 Taman Indah Subang Uep, 47150 Subang Jaya,  
 Selangor Darul Ehsan.  
 +603 - 8081 2216    sales@gvisb.com.my

**Penang Branch**  
 737-6-9, Sri Nibong Complex,  
 Jalan Sultan Azlan Shah,  
 11900 Penang  
 +604 - 642 8753

**Johor Branch**  
 No.49 & 49A, Jalan Pulai 23,  
 Taman Pulai Utama, 81300  
 Skudai, Johor, Malaysia  
 +607 - 520 5236