

oor Stand





GV INDUSTRIES SDN. BHD








Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
 Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg



Top Cover


Vented Design













Earthing cable



Side Panel Latch



19" Panel Mounting

Model	Capasity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	A-100	PDU (nos)
XP1870FS	18	980	600	700	992 x 612 x 712	96.5	5





Beige

* Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang, Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvisb.com.my Penang Branch 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

Johor Branch

^{*} Customized sizes available upon request