

AS Series

World Leader in Sophisticated Packaging Systems



series overview -

The BestPack® AS series are standard operator-free, cartonsealing machines designed to meet the needs of uniform in-line carton closure applications.

The units are two belt driven (two side belts driven), driven by three electric 110V UL approved motors. The AS series carton sealers are designed with a four column support structure. These units use 60 PSI and 4-5 CFM of air.

All systems incorporate our exclusive pop out pressure sensitive "High Speed" tape heads with patented tab adjustment.

AS Automatic Uniform Sidedrive

• UL Approved Electrical Parts

of machine

Designed for Uniform Carton Applications
Capable of Interchanging 2" or 3" Tape Heads

• Electrical on/off box can be mounted on either side

major features -

- In-line Carton Closure
- Adjustable Bed Height from 19.5" to 30.75"
- Reduced Cycle Time
- Rugged Construction
- Operator Free Design
- Cost Effective
- Height/Width Adjustments on either side of
 Machine
- Box Top Compression Unit
- Tape Roll Lengths: 1000 yd., 1500 yd., 2000 yd.
- Heavy Duty Frame

standard features

- Exclusive Pop-out pressure sensitive "high speed" tape head with patented tab adjustment and noise reduction arm
- Exclusive Automatic Flap-Fold
- Adjustable Bed Height
- Upper Side Compression
- Operation Manual



AS Series

World Leader in Sophisticated Packaging Systems

optional features

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Infeed/Exit Conveyor



Locking Castors

machine & carton specifications

- Power Requirements: 110 Volts 60 Hz
- 45 60 PSI, 4 5 CFM
- Speed: Up to 35 cartons/minute
- Tape Head: Standard: 2", Available: 3"

series comparison table

Model	Machine Dimensions	Carton Range	Cartons/Min.	Weight (lbs.)
AS 12-2 2″ tape head	(70.75") x (26.5") x (68.0")	(6.0"-27.5) x (6.0"-14.6") x (4.5"-20.0")	Up to 35	500
AS 12-3 3″ tape head	(70.75") x (26.5") x (68.0")	(6.0"-27.5) x (7.5"-14.6") x (45"-20.0")	Up to 35	500
AS 22-2 2″ tape head	(78.0") x (33.8") x (73.0")	(6.0"-27.5) x (6.0"-21.0") x (4.5"-20.0")	Up to 35	585
AS 22-3 3″ tape head	(78.0") x (33.8") x (73.0")	(6.0"-27.5) x (7.5"-21.0") x (4.5"-20.0")	Up to 35	585

* All specifications capable of customization or subject to change without notice

Compatible Indexer: ARX model
 Interlock Safety Gates



ARX Indexer