



**EU NIAN PRECISION TECHNOLOGY SDN. BHD.** (629410-X)

友聯精準科技有限公司

No. 23, Jalan Ros Merah 2/7, Taman Johor Jaya, 81100 Johor Bahru, Johor, Malaysia.

Tel : +60-7-3538933, 3538533 Fax : +60-7-3539533 E-mail : admin@eunian.com



## MEINAN ARISTO LATHE AL-4 (2-Box Stacker)

- Capacity for Log Diameter of 50cm to 60cm:  
Approx. 60m<sup>3</sup>/12hr (Veneer Collected in the Stacker)
- Capacity for Log Diameter of < 50cm:  
Approx. 50m<sup>3</sup>/12hr (Veneer Collected in the Stacker)
- Capacity for Log Diameter < 22cm:  
Approx. 40m<sup>3</sup>/12hr (Veneer Collected in the Stacker)

| Machine Spec                   |                  |
|--------------------------------|------------------|
| Knife length                   | 1500 mm          |
| Max. Log Diameter              | 1600mm           |
| Peeling speed                  | 100 m/min        |
| Peeling veneer thickness       | 1.3-4.0mm        |
| Range of log length            | 900-1,460mm      |
| Spur knife span (5 mm pitch)   | 920-1,285mm      |
| Max. torque of spindle         | Approx. 140 KG-M |
| Diameter of spindle            | 95mm             |
| Min. spindle chuck diameter    | 102mm            |
| Covering chuck diameter (Min.) | 150mm            |
| Covering chuck diameter (Mid.) | 190mm            |
| Covering chuck diameter (Max.) | 270mm            |



**EU NIAN PRECISION TECHNOLOGY SDN. BHD.** (629410-X)

友聯精準科技有限公司

No. 23, Jalan Ros Merah 2/7, Taman Johor Jaya, 81100 Johor Bahru, Johor, Malaysia.

Tel : +60-7-3538933, 3538533 Fax : +60-7-3539533 E-mail : admin@eunian.com

| <b>Machine Electric Motor Spec</b>       |                |
|------------------------------------------|----------------|
| <b>Spindle drive</b>                     | 22KWx1         |
| <b>Gangi roll drive</b>                  | 15KWx2         |
| <b>Rapid move of knife carriage</b>      | 2.2KWx1        |
| <b>Log clamp (oil pump)</b>              | 2.2KWx1        |
| <b>Adjusting nose bar</b>                | 0.1KWx1        |
| <b>Cleaning blower</b>                   | 0.4KWx1        |
| <b>Adjusting of deflecting bar</b>       | 0.1KWx1        |
| <b>Dream Clipper DC-4 Spec</b>           |                |
| <b>Working veneer length</b>             | 920-1,285 mm   |
| <b>Mini. Veneer width</b>                | 100 mm         |
| <b>Range of working thickness</b>        | 1.3-4.0 mm     |
| <b>Feeding speed</b>                     | 100 m/min      |
| <b>Thickness detecting points</b>        | Max. 11 points |
| <b>Working foremast width (2 kinds)</b>  | 2,100-2,700 mm |
| <b>Max. Stacking Height</b>              | 1,000 mm       |
| <b>Dream Clipper Electric Motor Spec</b> |                |
| <b>Feeding</b>                           | 5.5KW x 1      |
| <b>Stacked veneer lifting</b>            | 1.5KW x 2      |
| <b>Stacker conveyer NO.1</b>             | 1.5KW x 1      |
| <b>Side way conveyer for Stacked</b>     | 0.4 KW x 2     |
| <b>Veneer width adjusting</b>            | 0.4KW x 1      |
| <b>Waste veneer conveyer</b>             | 1.5KW x 1      |