


## CNC4560 – 4M POE Fisheye Camera



### Features

- 4 Megapixel 2560x1440 @25fps
- H.264 High Profile, ONVIF compatible
- 1.6mm 180° Fisheye Lens
- 3D-DNR, Dual Stream
- Day&Night by Filter Change (TDN)
- LED Array, 0 Lux up to 5m
- 1 Audio In / 1 Audio Out
- 1 Alarm In / 1 Alarm Out
- uSD Card storage up to 64GB
- Alarm Trigger : Line Crossing, Intrusion Detection, Motion Detection, Tampering Alarm, Network Disconnect, IP Conflict, Storage fail etc

### SPECIFICATION



Unit: mm

Model	CNC4560
Image Sensor	1/3" progressive scan CMOS Sensor
Resolution	2560x1440@12.5fps or 1920x1080@25fps
Shuttle	1/3s ~ 1/100,000s
Lens	1.6mm 186° Fisheye Lens
LEDs	1nos 3W 850nm IR LED Array
Day & Night	Filter Change or TDN (True Day & Night)
Min. illumination	0 Lux up to 5m
Network	10/100-BaseT, RJ45
Security	User Authentication, Address Filtering
Working Environment	-10° ~ +40°C, <90° Humidity (Non-Condensing)
Power	POE (802.3af)/12VDC, Max. 5.55W (IR-On)
Dimension	120mm(φ) x 41.2mm(H), 0.6kg

\* Specification maybe changed without prior notice