





Since 1983 OPSEWOOD TROPICAL SDN RHD (OPSEWOOD) formerly known as OLD PÄRQUET:SPECIALIST ENTERPRISE (OPSE) has built a reputation for being the pioneer and market leader in Wooden Flooring. Our proven track record is evident in the countless satisfied customers and ever increasing number of formes.

offices and other public and private properties that have relied on our of workmanship, superior materials and commitment to excellence.

OPSEWOOD has offered its clients magnificent wood flooring produced in respect of and in harmony with the

environment. Our timber comes directly from expertly managed commercial forests throughout the world and skilled craftsmanship turn this valuable natural resources into a wide range of quality wooden floors.

Our product timber comes in different sizes and types of wood to meet your choice of designs and budget requirements. We guarantee that you are getting Quality limber that can last all fell-lime. As a pioneer and market leader in our wooden flooring, OPSEWOOD has successfully completed many prestigious bungalows, double story links, condominiums, commercial buildings, multipurpose halls and sport courts.

OUR VISION

To become the leader in the wooden flooring industry in the Southern East Asian Region.

OUR MISSION

To provide the high quality and excellent services to meet our clients satisfaction;
To enhance the aesthetic value and unique characteristic of natural timber wood;
To promote healthy living concept and environmental flooring material.



Outstanding

The philosophy of our company is to be ready to take challenges, commitment to achieve high performance in meeting customer's satisfaction.



Professional

A team of skilled professionals comprised of experienced sales people, technician and administrative staff to deliver excellent and comprehensive services.



Supervision

We practice high quality and consistent control over our services and products.



Environmentally Friendly

We deliver quality materials and excellent services. We are environmentally responsible, so we offer eco-friendly products at competitive prices.



OPSEWOOD..... collection brings beauty and value to any space.

Our selection of solid hardwood flooring offers you a variety of finishes, widths and options to match your style, from rustic to modern. Our flooring species add character, warmth and value to any room in your house or commercial space.

Species Solid Hardwood Flooring





















Merbau

Burmese Teak

Kempas

Mahogany

Burmese Walnut African Teak Indian Rosewood

Sierra Wood

White Oak







Species Solid Hardwood Decking (outdoor)







Why Hardwood Decking?

Hardwoods have unique natural properties that make them significantly longer lasting, more durable, stable and stronger than softwoods.

- Naturally resistant to rot, insect attack, mould, fungus & decay.
- · Low maintenance.
- Low mainter
 Safe to use.
- . Less likely to bow, crack or warp when properly installed.
- Our Hardwood decking boards are suitable for many different climates and weather conditions.
- The decking can be oiled when installed but can also be left untreated.

Belian

Balau

Chengal





Re Furbish

of Solid Hardwood Timber Flooring

Refurnishing your solid timber floor after years of use is easy, it can be done through sanding and varnishing your floor, making it brand new and naturally beautiful. OPSE-WOOD provides refurnishing and maintenance a post sales service.

Our company uses imported equipment that allowes us to sand the floor with minimum amount of dust. This machine meets the world standard in sanding technology that has dust collection begs and excellent vacuum system. Your house is almost dust free when you get the new flooring done even without the need to move out.

Wate-borne faulting systems are the best to protect your flow against scatcher over in the highest trails and a high resistance sharpen of any late. Waterborn in highest not only for durable and beaufail floor, but to protect your health and environment Our valendome finishing suppliers are the proposed or invironment choice in finishing system advanced technology resulting in low VSCIN is also to use waterborne finished combined with dust containment standing yotem.

OPSEWOOD maintenance team comprised of skilled, trained, experienced and responsible members provides a high level of professionalism by delivering excellent and comprehensive services.



Adhesive


Cement Screeding





Installation Method of difference types of sub floor / underlay

1 (a) GLUE DOWN INSTALLATION METHOD



Maximum depth of sanding

1 (c) NAIL-DOWN INSTALLATION WITH BATTEN METHOD



(2) PROFILE OF WOOD FLOORING

2 (a) Tounge & Groove (T&G)



2 (b) Smooth 4 Side (S4S)



2 (c) Tounge & Groove (T&G) with space and cleat





(3) SIZE OF WOOD FLOORING

3 (a) Smooth 4 side (S4S) no space

50-60 mm(W)	70-75 mm(W)	90-98 mm(W)
11111		
10mm thk. & above	11-12mm thk.	17-18mm thk.

3 (b) Tounge & Groove (T&G) no space

18mm thk. 18-20mm thk

(5) STAIR BOARD



(6) STAIR NOSING PROFILE



EQUIPMENT OF SOLID HARDWOOD TIMBER FLOORING

The right hardwood flooring equipment can make all the difference in terms of time and results. Professional flooring specialist have relied on the surface quality achieved by professional flooring sanding machines. All our floor sanding machines have the most sophisticated technology for quick, environmentally friendly and perfect finishing of wooden floor and thus offer the greatest value returned possible. From the past until now, our company has invested in many types of the most successful flooring machines, light weight yet high performance floor, stair, edge, and corner sanders. A complete range of flooring sanding machines to make sure we deliver the quality flooring to meet your needs.



TOP COAT / FINISHING OF SOLID HARDWOOD TIMBER FLOORING



Glossy Surface (Natural Finishing)



Satin / Semi Gloss Surface (Natural Finishing)



PGOS

Matt Surface (Natural Finishing)

DIFFERENT TYPES OF WOOD FLOOR VARNISHES

Although oil-based polyuethanes are easier to apply, they are now rarely used as they tend to add a lot of colour to the wood, can take ages to fully cure, potentially weeks, and have a short shelf life. Two or three coats usually do the trick. But bear in mind it's smellier than water-based products. It's prone to brush marks and takes a lot longer to dry than the alternative solvent or water based varnishes.

Water-based polyurethanes dry faster and smell less, but they can raise the wood's grain slightly on some soft woods. This isn't a problem as the process of defibbing between coats will help to keep the final finish smooth. Water-based polyurethanes don't go well over oil-based wood stains but work well over solven that and wholte spirit based stains. Most toros use water based varishes because they have virture hos mell.

Solvent based polymerhanes are very quick to dy but are also the smill due to their high VOC (Volatile Organical Hospital Hospita





Maintenance and Care

With high build finish, our Solid Hardwood floors offer a durable finish that repels most household chemicals and is extremely easy to maintain.

VENTILATION AND/OR AIR-CONDITIONING

Wood is hygroscopic. It will adapt to the temperature and the reliative humidity in the serounding area where it has been installed. The relative humidity should be between 60% to 80% (Malaysia) at all times. For areas with air-conditioning on 24 hours, the relative humidity will be lower (the air feels dry) which may cause natural contraction of the boards and can be seen as small gaps between the limber strips. This doesn't affect the fundion and daily use of the floor.

If you are away for a longer petiod (23 weeks), we recommend that your air-conditioning systems is pre-set to operate 1:2 hours daily thus maintaining the above-mentioned relative humidity level. For areas without air-conditioning we recommend to keep your windows open to ensure sufficient ventilation. Pay attention to leaving doors or windows opened during rain falls, as any puddle of water left on the floor may damage the timber strips.

CLEANING & MAINTENANCE

(FINISHED FLOOR) DAILY/WEEKLY:

Vacuum-clean or dry mop the floor to remove surface dust and grift. Occasionally, the floor should be cleaned using a mild based cleaner or a solution of soap flakes and a well-wrung cloth.Important: The "ponding" of water must be kept to a minimum. Remove any puddle of water on the surface immediately.

LONG TERM MAINTENANCE:

Unlike other types of floors, solid hardwood floors can be Re-sanded and Re-varnished to retain its original luster and to add a new layer of protection. Hardwood floors can last for many generations if proper care and maintenance are exercised.

Although our floors are tough, they are not indestructible and can be scratched and damaged through improper use. We offer the following suggestions to maximize the enjoyment of your floor. As with any floor covering material, a bit of preventative care and some common sense will go a long way in keeping your floor tooking its best



Due to printing limitations, colors shown cannot be guaranteed to match actual flooring material. © Floor designs & project pictures copyrighted by OPSEWOOD TROPICAL SDN BHD.

Scan Me for More Details