

RATCHET WRENCHES

**Performance:**

Power: 0.3 hp (0.25 kW)  
Torque: 35 ft lb (47 Nm)

**Features:**

Lever Start  
Teasing Throttle  
Comfort Grip



SRW03S-25

**Ratchet Wrenches**

Model Number	Drive Size		Torque		Free Speed	Weight		Length		Side to Center		Air Consumption		Exhaust
	in	mm	ft lb	Nm	rpm	lb	kg	in	mm	in	mm	cfm	l/s	
<b>0.3 hp (0.25 kW)</b>														
SRW03S-25	1/4"	6	35	47	235	1.4	0.6	7.7	197	1.1	28	1.4	0.66	Rear
SRW03S-38	3/8"	10	35	47	235	1.4	0.6	7.7	197	1.1	28	1.4	0.66	Rear
SRW03S-38Q	3/8"	10	35	47	235	1.4	0.6	7.7	197	1.1	28	1.4	0.66	Rear

**General:**

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:**

Parts List • Safety and Instruction Manual

**Accessories:**

Ratchet Accessories, see page 36



SRW07-38

**Performance:**

Power: 0.7 hp (0.52 kW)  
Torque: 65 ft lb (88 Nm)

**Ratchet Wrenches**

Model Number	Drive Size		Torque		Free Speed	Weight		Length		Side to Center		Air Consumption		Exhaust
	in	mm	ft lb	Nm	rpm	lb	kg	in	mm	in	mm	cfm	l/s	
<b>0.7 hp (0.52 kW)</b>														
SRW07-38	3/8"	10	65	88	260	3	1.3	11.8	300	1	25	2.7	1.27	Front
SRW07-50	1/2"	13	65	88	260	3	1.3	11.8	300	1	25	2.7	1.27	Front

**General:**

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:**

Parts List • Safety and Instruction Manual

**Accessories:**

Ratchet Accessories, see page 36



**SAFETY PRECAUTION:** Read and follow all safety and operating instructions.  
**WARNING:** Face & eye protection must be worn while operating power tools, per ANSI B186.1