

## Installation of BaitSafe™ Units



Provisional Patent Filed





## What is BaitSafe™ ?

BaitSafe™ is a revolutionary new product to eliminate rodents. BaitSafe™ allows **instant access** to '**their world**' where rodents live and breed. It provides a safe barrier which helps to reduce the risks associated with pest control.

## Where can it be installed ?

It can be installed in ceilings, walls, flat roofed areas and between floors just to name a few. It eliminates the dangers associated with climbing ladders to access hazardous areas.

## Selecting Installation Location

Install the unit away from food preparation and eating areas - dining/coffee tables etc. . This will allow for easy access to the station for checking and replacement of baits and avoid the possibility of descending debris.

**Walls** - Do not install at ground level. Installation is recommended at a minimum height of 250mm above floor level.

## Clean Up Procedure


Be very conscious of the dust and particles that come from this operation being collected, with drop sheets etc, so it does not contaminate the surrounding environment.

## Secure Locking system...

BaitSafe's™ patented locking system secures the bait and allows safety, not only you, but your children and pets.



Ceiling  
mount view




The 'Key'  
that gives  
you access

A standard paint  
pole screws in  
here to allow a  
reach of up to 5  
metres (17ft).  
Paint Pole  
not included



Wall  
mount  
View



The 2 tabs reach out  
to clamp unit in position

A standard paint (not  
supplied) pole screws in  
here to allow a reach of  
up to 5 metres (17ft)

The bait 'Spike'

Unit assembled with 'Key' inserted

## The Parts that come in the Box




## Before Installing

You are going to cut a 90 mm diameter hole

### Caution - Before Cutting Hole

Check that there are no ceiling supports or services above your selected installation area.

**Caution - If installing in the Walls** - Some baits include an attractant which may arouse curiosity in pets. Please check manufacturer's labelling.



Always check for dangerous services above



Stud Finder makes it easier to find studs



You will need a Philips head screwdriver




## ● Install Procedure

### Ceilings

### Walls

Check for the location of studs and services (shown here using a stud finder)



Take cutting template from the box. Pin the centre & rotate with a pencil - or - cut out 90 mm circle and draw around the perimeter.



Mark out the 90 mm hole with the template.



Cut the hole. Use an insulated handle, and exercise caution if you hit cutting resistance.

Caution - hidden services






## ● Install Procedure ... continued

Remove any obstructing material, such as insulation.

### Ceilings



### Walls




Take the base unit and push the wing tabs in, as shown here.




If you are fixing to fibre cement, e.g. outside under the eaves, then you use the rubber seal provided.



Install the unit and then push the wings back out fully. Using a Philips head screwdriver to tighten the screws to clamp the unit in position. Do not over-tighten the screws.



The BaitSafe™ unit is now ready to use. Cut wall spike down in length (usually about 73mm) to suit space available.






## ● Install Procedure ... continued

You can insert the face plate using the key. Insert and twist to lock in the face plate.

### Ceilings



### Walls



The BaitSafe™ unit is now installed.

Screw the BaitSafe™ key onto any standard paint pole.  
If the thread on your particular pole is loose, use tape on the thread to overcome.  
Be sure when you are using the pole that the unit is firmly fixed on the end.  
Check each time after use.




## Secure Locking system

BaitSafe's™ patented locking system secures the bait and allows safety, not only you, but your children and pets.

## Clean Up Procedure


Clean the dust and particles that come from this operation, so it does not contaminate the surrounding environment.





## ● Accessing the BaitSafe™


Tighten the 'Key' onto the head of the paint pole. If you have a loose thread on your paint pole tape the pole to the 'Key'. Check tightness before each use.



Hold the pole directly under the unit - NOT at an angle. If in the wall - at right angles to the wall.

Insert 'Key' prongs into the slots of the fascia plate, pushing up gently, against the surface.

**Turn anti-clockwise to unlock.** Lower the unit carefully from the ceiling.





**To replace the unit,** insert the 'Key' into the fascia plate and raise it up to the ceiling, at right angles to the surface.

Gently insert and **turn clockwise to lock.**

After locking, lower the pole, and your bait station is ready for use.

## ● Installing the Bait

When installing in the wall cut the stem length down to suit the available wall depth. For exterior (or fibre cement) use the rubber seal.



Spike Socket must be **tightly** inserted into the base unit at all times.

**Caution**  
Bait Spike must be **tightly** inserted into the Spike Socket to prevent removal by rodents.

When checking & replacing baits BE SURE the Spike is secured **tightly** onto the socket.

**Caution** - Any stray particles that may come from bait, while inserting, should be kept away from children or pets.

**Malaysia Distributor :-**  
**Compesti Sdn. Bhd.** (1116259-H)

No. 17, Jalan Utama 2/16, Taman Perindustrian Puchong Utama, 47100 Puchong, Selangor.  
Office Mobile: +6012-438 2729 Fax: +603-8060 2729 Email: enquiry@compesti.com

**www.compesti.com**