

Built ruggedly with aluminum die extrusion housing and available in 3 power rating of 10 / 20 / 40 and 60W 100V line with dual power tapping.  
Suitable for classrooms, hyper markets, mosques, ballroom, factories, passenger terminals, exhibition areas etc.



**Features**

- Slim design to match environment or hidden from view
- Engineered for speech and BGM clarity

**Packing information**

CL902	: 230(W) x 150(H) x 230(D) mm : 2.6 kg : 2 uts per carton
CL904	: 390(W) x 150(H) x 230(D) mm : 3.60 kg : 2 uts per carton
CL908	: 608(W) x 168(H) x 235(D) mm : 5.55 kg : 2 uts per carton
CL912	: 828(W) x 168(H) x 235(D) mm : 7.80 kg : 2 uts per carton

**Technical Specifications**

	CL902	CL904	CL908	CL912
Power rating	10W 100V	20W 100V	40W 100V	60W 100V
Speaker components	2 x 2"	4 x 2"	8 x 2"	12 x 2"
Transformer tapping(100V)	6 / 10W	10 / 20W	30 / 40W	50 / 60W
Primary impedance (Ohm)	1.6K / 1K	1K / 500	330 / 250	200 / 166
SPL descriptions	87 ± 3dB		88 ± 3dB	89 ± 3dB
Frequency response	230 - 16 KHz @ 1KHz +/-3dB			
Dimension (WxHxD) (mm)	190 x 79 x 89	350 x 79 x 89	567 x 79 x 89	782 x 79 x 89
Material	Aluminum			
Weight with bracket (kg)	0.9	1.4	2.35	3.2

**20 - 40W 100V Line Column Speaker | CH700**

Built ruggedly with aluminum die cast housing and available in 3 power rating of 20 / 30 and 40W 100V line with dual power tapping. Suitable for classrooms, hyper markets, mosques, etc.



**Technical Specifications**

	CH720	CH730	CH740
Power rating	20W 100V	30W 100V	40W 100V
Speaker component	2 x 4"	3 x 4"	4 x 4"
Tapping (100V line)	10 / 20W	15 / 30W	20 / 40W
Primary impedance (Ohm)	1 K / 500	660 / 330	500 / 230
Secondary impedance (Ohm)	8		
Freq response (+/- 3dB)	85 ~ 15 KHz	80 ~ 15 KHz	75 ~ 15 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	91 dB	93 dB	95 dB
Grille / enclosure	Aluminum / metal grille		
Overall size (WxHxD) (mm)	145 x 400 x 100	145 x 495 x 100	145 x 605 x 100
Weight (kg)	3.2	3.7	4.6
Colour	Dark grey / front black grille		

**Packing information**

CH720	: 430 (W) x 310 (H) x 220 (D) mm : 7.1 kg : 2 uts per carton
CH730	: 520 (W) x 320(H) x 215 (D) mm : 8.9 kg : 2 uts per carton
CH740	: 620 (W) x 310 (H) x 220 (D) mm : 10.5 kg : 2 uts per carton

