



PUNCHES, CHISELS & HAMMERS

Whether you're looking for finesse or power — or both — our hammers, punches and chisels are made to deliver powerful blows without punishing your hands and arms. They're available in both hard and soft grips and feature special energy-absorbing material for maximum comfort.

STRIKE A BLOW FOR SUPERIOR QUALITY.

We not only offer the largest range of striking tools, we offer the best construction. Snap-on® punches and chisels are made from heat-treated steel for maximum strength and performance, with heads that are machined to direct the striking force to the center of the tool head. This controls mushrooming, allows slow metal displacement and reduces chipping and splitting. Our standard, dead blow and ball peen hammers feature a free flowing shot that improves dead blow action and delivers concentrated blows while reducing rebound. Their composite handles are also designed to reduce vibration, prevent slippage and withstand the rigors of any shop environment.



Punches and Chisels

The anvil end on heads of Snap-on® punches and chisels are machined to a modified parabolic curve. This design directs the striking force to the center of the tool head to allow slow metal displacement. The parabolic curve controls mushrooming to reduce chipping and splitting. Heads should be redressed to their original shape with

hand files as necessary. The tough alloy steel is machined and differentially heat treated for optimum performance. The hardness of the striking head is reduced to help toughness and add qualities that result in a slower mushrooming of the striking surface.

Soft Grip Punches and Chisels

- Ergonomic soft grip handle provides a powerful grip, improves the thermal sensation in cold work environments and reduces strike vibration
- Semispherical striking area controls mushrooming to help reduce chipping and splitting
- Cutting edges on chisels are hand ground to consistently produce a quality edge
- Black oxide coated
- Manufactured from special alloy steel that is differentially heat treated to increase durability



PPCSG710

Set Contains:				
Stock No.	Description	Point/ Edge, inches	Length, inches	
PCSG812	Flat Chisel	3/8	6-1/8	•
PCSG816	Flat Chisel	1/2	6-1/8	•
PCSG820	Flat Chisel	5/8	6-1/8	•
PPSG103	Pin Punch	3/32	6-1/8	•
PPSG105	Pin Punch	5/32	6-1/2	•
PPSG106	Pin Punch	3/16	6-1/2	•
PPSG203	Starter Punch	3/32	6-1/8	•
PPSG205	Starter Punch	5/32	6-1/8	•
PPSG206	Starter Punch	3/16	6-1/8	•
PPSG4	Center Punch	3/16	6-1/8	•

			CHSL400R	CHSL400O	CHSL400G
Set Contains:					
Stock No.	Description	Tip Width, inches (mm)	Red	Orange	Green
CHSL25R	Striking Chisel, Red	1/4 (6.35)	•		
CHSL25O	Striking Chisel, Orange	1/4 (6.35)		•	
CHSL25G	Striking Chisel, Green	1/4 (6.35)			•
CHSL50R	Striking Chisel, Red	1/2 (12.7)	•		
CHSL50O	Striking Chisel, Orange	1/2 (12.7)		•	
CHSL50G	Striking Chisel, Green	1/2 (12.7)			•
CHSL75R	Striking Chisel, Red	3/4 (19.05)	•		
CHSL75O	Striking Chisel, Orange	3/4 (19.05)		•	
CHSL75G	Striking Chisel, Green	3/4 (19.05)			•
CHSL100R	Striking Chisel, Red	1 (25.4)	•		
CHSL100O	Striking Chisel, Orange	1 (25.4)		•	
CHSL100G	Striking Chisel, Green	1 (25.4)			•



PPC14LB

Oval Bearing Race Punches

High alloy steel makes these tools ideal for stubborn bearing races.

PPC6LB 6" Oval Bearing Race Punch

- 7/16" hex stock, 7/16 x 15/64" oval point, 6" long

PPC10LB 10" Oval Bearing Race Punch

- 1/2" hex stock, 1/2 x 17/64" oval point, 10" long

PPC14LB Oval Bearing Race Punch

- 9/16" hex stock, 9/16 x 19/64" oval point, 14" long

PPC20LB Oval Bearing Race Punch

- 9/16" hex stock, 5/8 x 5/16" oval point, 20" long

PPC704BK 4 pc Punch Set

- Includes PPC6LB PPC20LB (4 pc)



PGH8A

Gasket Punch Set

PGH8A 11 pc Gasket Punch Set (Blue-Point®)

- Cuts holes in gaskets and other soft materials
- Includes 5-3/8" long mandrel and (10) punches (1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 3/4, 7/8 and 1")
- Includes storage case



GA1

Bushing Cutter

GA1 Bushing Cutter (Blue-Point®)

- Made of 1/2" octagonal stock with a 7/16 x 1/8" bit
- Curved bit pushes material away from work
- 7-1/4" long



YA879A



YA900

Automatic Centering Punches

YA879A Heavy Duty Automatic Center Punch (Blue-Point®)

- Single hand operation
- Design eliminates need for striking with hammer
- Adjustable spring tension cap
- Hardened steel point is replaceable
- 1/2" diameter

YA900 4-3/4" Automatic Center Punch (Blue-Point®)

- Strikes blow when pressure is applied, no hammer needed
- Cap adjusts force of blow
- 7/16" diameter
- 4-3/4" long

PUNCHES AND CHISELS



	Stock No.	Hex Size, inches	Point/ Edge, inches	Length, inches	Set Contains:									
					PPC250BK	PPC210BK	PPC115BK	PPC110BK	PPSD120BK	PPC100AK	PPCD70BK	PPCS60BK	PPC50AK	PPCM60BK
Punch and Chisel Accessories 	PPC1A	N/A	N/A	2-5/8	•	•	•	•						
	PPC5A	N/A	N/A	6-15/16		•								
Center Punches 	PPC3A	5/16	1/8	5	•	•	•							
	PPC4A	7/16	3/16	6	•	•	•	•						
	PPC6B	5/8	5/16	7										
	PPC714B	9/16	5/32	14										
Pin Punches 	PPC103A	9/32	3/32	4-7/32	•	•	•	•	•		•			
	PPC104A	5/16	1/8	4-3/4	•	•	•		•		•			
	PPC105A	3/8	5/32	5	•	•	•	•	•		•			
	PPC106A	3/8	3/16	5-1/4	•	•	•	•	•		•			
	PPC107A	3/8	7/32	5-1/4	•						•			
	PPC108A	7/16	1/4	5-3/4	•	•	•				•			
	PPC110A	1/2	5/16	5-1/4	•	•			•		•			
	PPC112	9/16	3/8	5-1/4	•	•								
Metric Pin Punches 	PPCM103B	5/16	—	154.2										•
	PPCM104B	5/16	—	154.2										•
	PPCM105B	3/8	—	154.2										•
	PPCM106B	3/8	—	154.2										•
	PPCM107B	3/8	—	154.2										•
	PPCM108B	7/16	—	154.2										•
Starter Punches 	PPC203A	5/16	3/32	5-1/2	•	•	•	•	•			•		
	PPC204A	3/8	1/8	5-3/4	•	•	•		•			•		
	PPC205A	3/8	5/32	6	•	•	•	•	•			•		
	PPC206A	7/16	3/16	6-1/4	•	•	•	•	•			•		
	PPC208A	1/2	1/4	6-3/4	•	•	•		•			•		
	PPC210A	9/16	5/16	7-1/4	•	•			•			•		
Flat Chisels 	PPC808A	1/4	1/4	5										
	PPC812B	5/16	3/8	5-1/2	•	•	•	•		•			•	
	PPC816B	7/16	1/2	6	•	•	•	•		•			•	
	PPC820B	1/2	5/8	6-1/2	•	•	•	•		•			•	
	PPC824B	5/8	3/4	7-1/4	•	•				•			•	
	PPC828B	11/16	7/8	8	•	•				•			•	
	PPC832B	7/8	1	9										
	BPPC187B*	7/8	1	18										
Long Flat Chisels 	PPC820LB	1/2	5/8	16										
Half Round Nose Cape Chisels 	PPC12B	3/8	5/16	6	•					•				
Cape Chisels 	PPC13B	5/16	1/4	5-5/8						•				
	PPC14B	3/8	5/16	6	•					•				
Diamond Point Chisels 	PPC15B	7/16	7/32	6						•				
	PPC19B	3/8	1/8	5-3/4	•					•				
Kit Bag					KB2179	KB2178	KB2182	KB2181	KB2187	KB2175	KB2183	KB2185	KB2173	KB2189

*Blue-Point®



PUNCHES AND CHISELS

PPC250BK 24 pc Punch and Chisel Set

- 24 pc in KB2179 kit bag



PPC250BK

PPC100AK 10 pc Punch and Chisel Set

- 10 pc in KB2175 kit bag



PPC100AK

PPC210BK 22 pc Punch and Chisel Set

- 22 pc in KB2178 kit bag



PPC210BK

PPCD70BK 7 pc Punch and Chisel Set

- 7 pc in KB2183 kit bag



PPCD70BK

PPC715BK 16 pc Punch and Chisel Set

- 16 pc in KB2182 kit bag



PPC715BK

PPCS60BK 6 pc Starter Punch Set

- 6 pc in KB2185 kit bag



PPCS60BK

PPC710BK 11 pc Punch and Chisel Set

- 11 pc in 2181 kit bag



PPC710BK

PPC50AK 5 pc Flat Chisel Set

- 5 pc in KB2173 kit bag



PPC50AK

PPSD120BK 12 pc Pin and Starter Punch Set

- 12 pc in KB2187 kit bag



PPSD120BK

PPCM60BK 6 pc Metric Pin Punch Set

- 6 pc in KB2189 kit bag



PPCM60BK

PPRG80 8 pc Roll Pin Punch Guide Set

- Companion tool for the PPR708BK roll pin punch set
- Provides faster, safer pin installation
- Pin guide is a vinyl sleeve uniting pin and punch to achieve perfect alignment during installation
- Ideal for pin installation in tight quarters where two hands cannot reach

- Use with Snap-on® roll pin punches PPR2 through PPR8 (1/16–1/4")
- Can also be used with Snap-on® pin punches PPC103A through PPC108A (3/32–1/4") and long pin punches PPC104LA thru PPC108LA (1/8–1/4")



PPRG80

Steel Stamping Sets

- Heat treated square stamp bodies
- Stored in 2 piece wooden containers

Stock No.	Characters	Number Stamps	Figure Size, inches	Square Body, inches	Length, inches
GA237	0-9	9	3/16	5/16	2-7/16
GA238	A-Z	27	3/16	5/16	2-7/16
YA817	0-9	9	1/8	1/4	2-3/8
YA818	A-Z	27	1/8	1/4	2-3/8

*One stamp serves as both 6 and 9.

**Also includes stamp for period.



GA237

Transfer Punches (Blue-Point®)

Set Contains:

Stock No.	Description	
DPFT531-6	3/32" Transfer Punch	•
DPFT531-7	7/64" Transfer Punch	•
DPFT531-8	1/8" Transfer Punch	•
DPFT531-9	9/64" Transfer Punch	•
DPFT531-10	5/32" Transfer Punch	•
DPFT531-11	11/64" Transfer Punch	•
DPFT531-12	3/16" Transfer Punch	•
DPFT531-13	13/64" Transfer Punch	•
DPFT531-14	7/32" Transfer Punch	•
DPFT531-15	15/64" Transfer Punch	•
DPFT531-16	1/4" Transfer Punch	•
DPFT531-17	17/64" Transfer Punch	•
DPFT531-18	9/32" Transfer Punch	•
DPFT531-19	19/64" Transfer Punch	•
DPFT531-20	5/16" Transfer Punch	•
DPFT531-21	21/64" Transfer Punch	•



DPFT531









DPFT531-22	11/32" Transfer Punch	•
DPFT531-23	23/64" Transfer Punch	•
DPFT531-24	3/8" Transfer Punch	•
DPFT531-25	25/64" Transfer Punch	•
DPFT531-26	13/32" Transfer Punch	•
DPFT531-27	27/64" Transfer Punch	•
DPFT531-28	7/16" Transfer Punch	•
DPFT531-29	29/64" Transfer Punch	•
DPFT531-30	15/32" Transfer Punch	•
DPFT531-31	31/64" Transfer Punch	•
DPFT531-32	1/2" Transfer Punch	•
DPFT531-33	Transfer Punch	•
DPFT531-34	17/32" Transfer Punch	•
DPFT531-48	3/4" Transfer Punch	•
DPFT531-56	7/8" Transfer Punch	•
DPFT531-64	1" Transfer Punch	•
DPFT531-P	Replacement Pouch	•



- Use the proper punch or chisel for the job
- Do not use punches or chisels having chipped or mushroomed end; discard or dress to original shape with a hand file
- Use hammer with head about 3/8" larger in diameter than head of punch or chisel
- Read safety precautions on pages W1 to W4

PUNCHES AND CHISELS



	Stock No.	Hex Size, inches	Point/ Edge, inches	Length, inches	Set Contains:	PPR709BK	PPCL60BK	PPVP70BK	PPLT40AK	LP30A	PPB30AK	PPBL30AK	PPB20AK
 Roll Pin Punches	PPR2	—	1/16	3-5/32	•								
	PPR2-1/2	—	5/64	3-1/2	•								
	PPR3	—	3/32	3-29/32	•								
	PPR4	—	1/8	4-1/4	•								
	PPR5	—	5/32	4-5/8	•								
	PPR6	—	3/16	5	•								
	PPR7	—	7/32	5-3/8	•								
	PPR8	—	1/4	5-3/4	•								
	PPR10	—	5/16	6-1/8									
	PPR12	—	3/8	6-1/8									
	PPR14	—	7/16	6-1/8									
 Long Pin Punches	PPC104LA	5/16	1/8	5-5/16		•							
	PPC105LA	3/8	5/32	6-1/2		•							
	PPC106LA	3/8	3/16	7-1/16		•							
	PPC107LB	3/8	7/32	7-5/8		•							
	PPC108LA	7/16	1/4	8-3/16		•							
	PPC110LA	1/2	5/16	8-3/4		•							
 Midget Punches and Chisels	PPC402A	9/32	1/16	3				•					
	PPC403A	9/32	1/8	3-1/4				•					
	PPC404A	9/32	3/32	3-5/8				•					
	PPC405A	9/32	1/16	3-3/4				•					
	PPC406B	9/32	3/16	3-7/8				•					
	PPC407B	9/32	5/32	4				•					
	PPC408B	—	5/16	4-1/8				•					
	PPC905B	3/8	5/32	8					•				
 Drift Pin Punches	PPC908B	7/16	1/4	8-1/2					•				
	PPC910B	1/2	5/16	9					•				
	PPC912B	9/16	3/8	9-1/2					•				
	1210B	5/8	5/16	12						•			
	1512B	3/4	3/8	15						•			
	1816B	7/8	1/2	18						•			
 Bronze Pin Punches	PPB408A	—	1/4	4							•		
	PPB612A	—	3/8	6							•		
 Bronze Drift Punches	PPB816A	—	1/2	8							•		
	PPB826A	—	13/16	8								•	
	PPB1226A	—	13/16	12								•	
 Bronze Tapered Punches	PPB1001A	5/8	3/8	8									
	PPB1012A	—	3/8	10								•	•
	PPB1414A	—	7/16	14									•
 Bronze Round Punch	PPB1002A	—	10	3/4									
Kit Bag						KB2186	KB2184	KB2188	KB2174	KB2177	KB2171	KB2172	KB2170

PPR708BK 8 pc Roll Pin Punch Set

• 8 pc in KB2186 kit bag



PPR708BK

PPCL60BK 6 pc Long Pin Punch Set

• 6 pc in KB2184 kit bag



PPCL60BK

PPVP70BK 7 pc Midget Punch and Chisel Set

• 7 pc in KB2188 kit bag



PPVP70BK

PPLT40AK 4 pc Drift Pin Punch Set

• 4 pc in KB2174 kit bag



PPLT40AK

LP30A 3 pc Drift Pin Punch Set

• 3 pc in KB2177 kit bag



LP30A

PPB30AK 3 pc Bronze Punch Set

• 3 pc in KB2171 kit bag

PPBL30AK 3 pc Bronze Punch Set

• 3 pc in KB2171 kit bag



PPBL30AK

PPB20AK 2 pc Bronze Tapered Punch Set

• 2 pc in KB2170 kit bag

DEAD BLOW

Standard

- Free flowing shot design to improve dead blow action while reducing rebound
- Compact head has larger surface striking area and heavier caps to improve delivered force by as much as 40 percent Applications: Brake rotors, brake drum removal, ball joints (tie rod removal), tires, seal installation, loosen oil pans and covers, OE rims, axle insertion, piston installation and crank shaft end play Standard
- Soft grip handle with ribbed, textured elastomer grip prevents hand slippage
- Composite handle shank improves balance while defusing shock and dampening vibration
- Improved thermoplastic urethane material is nonsparking and resistant to most shop chemicals
- Dead Blow Hammers feature the Free Flowing Shot Design which improves dead blow action while reducing rebound
- Composite Handle Shank Material – Improves hammer balance while defusing shock and dampening vibration
- Compact Head – Larger surface striking area and heavier caps can improve delivered force by as much as 40%
- Free Flowing Shot Design – Improves dead blow action while reducing rebound
- Multi-position Hand Grip – Helps user “choke up” in tighter work areas

Applications: Brake Rotors, Brake Drum Removal, Ball Joints (Tie Rod Removal), Tires, Seal Installation, Loosen Oil Pans and Covers, OE Rims, Axle Insertion, Piston Installation and Crank Shaft End Play.

Compact Slimline

Incorporates our new microcellular soft grip handle, a softer, more comfortable energy absorbing material. Applications: Main bearing caps, dust caps, smaller objects, custom bikes and tighter applications that standard dead blow hammers will not fit

Slimline Dead Blow incorporates our new microcellular soft grip handle, a softer more comfortable energy absorbing material.

- Microcellular Grip and Composite Shank – Delivers a comfortable, secure grip and dampens the vibration to the users hand
- Smaller Face – For more concentrated blows
- Longer Head Profile – For extended reach
- Internal Steel Canister with Free Flowing Shot Design – Delivers maximum dead blow action
- Multi-position Hand Grip – Helps user “choke up” in tighter work areas
- Wide Flare at End of Handle – Helps prevent hammer from slipping out of hand

Applications: Main Bearing Caps, Dust Caps, Smaller Objects, Custom Bikes, Tighter Applications that Standard Dead Blow Hammers will not fit and Extended Reach Applications.



HBFE32

Set Contains:

HBFE103

Stock No.	Weight, oz	Head Length, inches	Face Dia., inches	Length, inches	
HBFE16	16	3-1/4	1-9/16	12	
HBFE24	24	3-3/4	1-3/4	12-3/4	•
HBFE32	32	4-1/4	2	13-1/2	•
HBFE48	48	4-3/4	2-1/4	15	•
HBFE56	56	5-7/16	2-3/4	15-3/4	



HBSE20

Stock No.	Weight, oz	Face Dia., inches	Length, inches
HBSE10	10	1-1/4	10-5/8
HBSE20	20	1-3/8	11-1/8
HBSE30	30	1-1/2	12-3/8



- Use the proper punch or chisel for the job
- Do not use punches or chisels having chipped or mushroomed end; discard or dress to original shape with a hand file
- Use hammer with head about 3/8" larger in diameter than head of punch or chisel
- Do not use urethane hammers near liquid oxygen
- Read safety precautions on pages W1 to W4

DEAD BLOW



HBBD24

Dead Blow Ball Peen

- Dead Blow Hammers feature the Free Flowing Shot Design which improves dead blow action while reducing rebound
- Total Composite Insert – Improves hammer balance while defusing shock and dampening vibration
- Free Flowing Steel Canister – Improves the deadblow action
- Multi-position Hand Grip – Helps user “choke up” in tighter work areas
- Microcellular Grip and Composite Shank – Delivers comfortable, secure grip and dampens the vibration to the users hand
- Polished steel peen and head for a smooth striking surface
- Composite handle shank improves the hammer balance while defusing shock
- Free-flowing steel head canister design improves dead blow action
- Extra wide flaring on grip end helps prevent hammer from slipping out of hand
- Multi-position hand grip features a ribbed thumb rest, allowing user to choke up in tight work areas

Stock No.	Weight	Head Length, inches	Face Dia., inches	Length, inches
HBBD8	8	4	1	11-5/8
HBBD16	16	4-3/8	1-1/4	12-1/4
HBBD24	24	4-3/4	1-3/8	12-3/4
HBBD32	32	5-3/4	1-3/4	13-5/8
HBBD40	40	5-3/4	1-3/4	15-1/8



HSD32

Dual Face Drilling

- Sustained impact and maximum striking force with almost no rebound
- Composite handle shank improves the hammer balance while defusing shock
- Free flowing steel head canister design improves dead blow action and reduces rebound
- Nonsparking, chemical resistant molded urethane covering
- Ribbed thumb rest allows user to choke up in tighter work areas



BC110B

Sledge (Blue-Point®)

Stock No.	Weight	Head Length, inches	Face Dia., inches	Length, inches
BC7B	5	7	2-3/4	20
BC110B	8	7	2-3/4	30
BC114B	11 lb 8 oz	8	3-1/4	36



HBBT32

HBBT Series Bronze

- Bronze tipped nonmarring hammer ideally suited for work on bushings, gears and transmissions. Applications: Bearings & race install, pinion & half shafts, distributor rebuilds, alternator and starter rebuilds, seal installation, body moldings and nonspark applications

Stock No.	Weight, oz	Head Length, inches	Head Dia., inches	Length, inches
HBBT16	16	3-3/4	1-3/8	12
HBBT24	24	4-1/4	1-3/8	12
HBBT32	32	4-1/2	1-1/2	12-3/4

SOFT FACE



HLE24

Piston

- One piece urethane construction
- Full length canister increases head strength
- Made of material that will not damage the piston
- Shot filled head drastically reduces rebound

Stock No.	Weight, oz	Head Length, inches	Face Dia., inches	Length, inches
HLE24	24	7-3/4	5-1/2	12-3/4



HBPT24

HBPT Series Plastic

- Plastic tipped hammers used where metal to metal scratching or marring needs to be eliminated
Applications: Transmission work, rear end work, metal body moldings and light tapping

Stock No.	Head Length, inches	Weight, oz	Length, inches	Soft Tip Stock No. (Gray)	Hard Tip Stock No. (Black)
HBPT16	3-3/4	16	12	HPTS16	HPTH16
HBPT24	4-3/4	24	12-3/4	HPTS24A	HPTH24A


BF623

Soft Blow

- Designed to reduce marring and denting
- Use in assembly applications and on surfaces including metal, glass, plastic and wood
- Special polymer head resists dynamic fatigue, creep and compression set, even at extreme temperatures

Stock No.	Face Dimensions, inches	Head Color	Length, inches
BF623	1-7/8 x 2-1/8	Blue	12-1/2


BF620C

BF620C Rubber Head 11" Mallet (Blue-Point®)

- Solid rubber head is 3-3/4" long, 2-1/4" diameter
- 11" hardwood handle

Combination

- Combination steel and soft face dead blow
- 1 pc urethane construction
- Replaceable tips

Stock No.	Head Length, inches	Weight, oz	Tip Diameter, inches	Length, inches	Soft Tip Stock No.	Hard Tip Stock No.
HSPD16	4-3/8	16	1-1/4	12-1/8	HPTS16	—
BH232A*	—	32	1-5/8	13	BH232-2	BH232-3
BH232-4	Optional nylon tip (also available)					
BH232-5	Optional brass tip (also available)					

*Blue-Point®


BH232A

HSPD16

HSP16KT

Interchangeable Head

- Shot loaded, dead blow hammer adds more striking force by eliminating rebound and dampening vibration shock
- 1-1/2" striking face diameter on each hammer head
- Six interchangeable heads meet a number of various applications, including nonmarring and nonsparking applications with selected head surfaces
- Comfortable, nonslip handle grip
- Set includes 10" fiberglass handle and storage case
- 1" head extender is optional

Stock No.	Description
HSP16KT	7 pc Dead Blow Interchangeable Fiberglass Handle Hammer Set (Blue-Point®)


HBR15

Brass (Fiberglass Handle)

- Nonsparking/nonmarring surface for many applications
- Brass head absorbs blow and reduces rebound
- Flat surface for even distribution of blow
- Comfortable, nonslip handle grip

Stock No.	Weight, lb	Length, inches
HBR15	1-1/2	12
HBR4	4	12
HBR6	6	12


HCL16

Claw Hammers

HCL16 16-Ounce Claw Hammer

- Drop forged carbon steel head
- Oversized striking surface
- Polyurethane leather improves grip and offers abrasion resistance and low temperature flexibility for unparalleled comfort
- Antishock core reduces vibration and hand fatigue
- One-piece construction delivers increased strength


BFNM1

Non-Marring Hammers

BFNM1 1 lb Non-Marring Mallet (Blue-Point®)

- Head of Mallet is non-marring on finished surfaces due to soft durometer material
- Durable, resin-rich "pull-truded" fiberglass handle
- Handle is UV and chemical resistant
- Less rebound than traditional rubber head mallets helps reducing operator fatigue
- Non-slip, cushion-gripped handle



- Do not use urethane hammers near liquid oxygen
- Do not strike another hammer or hardened object
- Do not use chipped, mushroomed or cracked hammer
- Strike squarely, avoid glancing blows
- Read safety precautions on pages W1 to W4

BALL PEEN



BP16B

Ball Peen (Hickory Handle)

Set
Contains:

BP1004S

Stock No.	Weight, oz	Handle Length, inches	Replacement Handle	
BP2B	2	9-1/2	BPH2C	
BP4B	4	10-1/2	BPH4C	
BP8B	8	12-1/2	BPH8C	•
BP12B	12	13-1/2	BPH12C	•
BP16B	16	14-1/2	BPH16C	•
BP20B	20	15	BPH20C	
BP24B	24	16	BPH20C	•
BP32B	32	16	BPH40C	
BP40B	40	16-1/4	BPH40C	
BP48B	48	16-1/4	BPH40C	

ASME®/ANSI® B107.400



BPN16B

Ball Peen (Fiberglass Handle)

Stock No.	Weight, oz	Handle Length, inches	Replacement Handle	Previous* Model Handle
BPN12B	12	12	BPNH12B	BPN12-1
BPN16B	16	13	BPNH12B	BPN16-1
BPN24B	24	14	BPNH24B	BPN24-1
BPN32B	32	16	BPNH24B	BPN24-1
BPN8B	8	11	BPNH8B	BPN8-1

ASME®/ANSI® B107.400

HEAVY DUTY Blue-Point®



HCB2SG

HCS2SG

Dual Face Dead Blow (Fiberglass Handle)

- 100% cast polyurethane face is designed to withstand the most severe striking applications
- Nonsparking/nonmarring brass face for multiple applications
- Nonferrous shot loaded cavity delivers more power and less rebound than any hammer of its kind
- Abrasion and Impact Resistant
- Chemical Resistant
- Comfortable, nonslip handle grip
- Applications: aerospace, automotive, metal fabrication, petrochemical, electronics, industrial assembly, construction, oil and mining

Stock No.	Weight, lb (kg)	Face Dia., inches (mm)	Handle Length, inches (mm)	Length, inches (mm)
HCB2SG	2 (.91)	2 (50.8)	10-5/8 (270)	13-3/4 (349)
HCS2SG	2 (.91)	2 (50.8)	10-5/8 (270)	13-3/4 (349)

Meets or exceeds all ANSI® specifications



BD10ESG

Sledge (Fiberglass Handle) (Blue-Point®)

Stock No.	Weight, lb (kg)	Face Dia., inches (mm)	Handle Length, inches (mm)	Overall Length, inches (mm)	Replacement Handle
BD6ESG	6 (2.7)	1-5/8 (41.1)	16 (406.4)	18 (457.2)	BD6ESG-1
BD10ESG	10 (4.5)	2 (50.8)	29 (736)	32 (812.8)	BD8ESG-1



BC4SG

HD4SG

BD4SG

Heavy-Duty (Fiberglass Handle)

- Dampens vibration and provides strength and safety
- Handle is resistant to dry rot, warp and splintering
- Fiberglass handle dampens vibration and provides extra strength and safety
- Handle is epoxy welded to hammer head and will withstand 8,000 lb of separation force
- Comfortable, nonslip handle grip
- Materials will resist most shop chemicals

Stock No.	Description	Weight, lb	Striking Face Dia., inches	Handle Length, inches	Overall Length, inches	Replacement Handle
BC4SG	Cross Peen	4	1-1/2	12	14	BD4SG-1
BD4SG	Engineer	4	1-1/2	12	14	BD4SG-1
HD4SG	Hand Drilling	4	1-1/2	8-3/4	10-3/4	HD4SG-1



BH122D

BH133B

BH141A

Heavy Duty (Hickory Handle)

Stock No.	Description	Weight, oz	Head Length, inches	Overall Length, inches	Replacement Handle
BH122D	Engineer	40	4-1/2	15	BPH40C
BH123D	Engineer	48	4-3/4	15	BPH40C
BH133B	Hand Drilling	48	4-1/2	10	BPH133
BH141A	Cross Peen	32	4-1/2	15	BPH20C
BH142A	Cross Peen	40	5	15	BPH40C
BH143A	Cross Peen	48	5-1/2	15	BPH40C