

BT-DA10K2/13K2/20K2

IR HD IP Cameras



Features:

Support Onvif2.4, P2P function and mobile
3D DNR, 8*ROI Area, Stable Snapshot view through mainstream NVR
Motion Detection

Specifications

Model	BT-DA10K2	BT-DA13K2	BT-DA20K2
Sensor	Progressive Scan CMOS		
Light-sensing surface area	1/4-inch	1/3-inch	1/2.7-inch
Resolution	1.0MP	1.3MP	2.0MP
Definition	1280(H)x720(V)	1280(H)x960(V)	1920(H)×1080(V)
Video Compression	H.264		
Min. illumination	Color: 0.05Lux@(F1.2), Black: 0.01Lux@(F1.2),0 LUX with IR		
Lens	4mm@F1.8(6mm, 8mm, 12mm optional)		
Protocol	TCP/IP, DHCP, HTTP, HTTPS NTP, DNS, RTP RTSP		
Audio Compression	G.711a		
Shutter	Auto		
Infrared Resection	IR-CUT		
IR Distance	20m		
Power Supply	DC12V±10%		
Working Environmentl	-10 °C- 60 °C, Less than 90%RH		
Gross/Net Weight	0.28KG/0.20KG		
Dimension(color box)	130mm*130mm*102mm		