



NON-SPARKING HEX KEYS

Copper Beryllium

Product Code	Size (MM)	Overall Length (Inches)	Width (Inches)
NSB320-2	2	2 ³ / ₈	1
NSB320-3	3	2 ³ / ₈	1
NSB320-4	4	2 ¹ / ₂	1 ³ / ₁₆
NSB320-5	5	3 ¹ / ₈	1 ¹ / ₄
NSB320-6	6	3 ³ / ₈	1 ⁷ / ₁₆
NSB320-7	7	3 ¹ / ₂	1 ¹¹ / ₁₆
NSB320-8	8	3 ³ / ₈	1 ³ / ₄
NSB320-9	9	3 ⁷ / ₈	1 ³ / ₄
NSB320-10	10	4 ³ / ₈	1 ³ / ₄

Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- Anti-magnetic and highly corrosion resistant.



NSB320-5



NON-SPARKING ERGO® SLOTTED SCREWDRIVERS

Copper Beryllium

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
NSB300-3-50	6 ³ / ₄	2	¹ / ₈
NSB300-3-75	7 ³ / ₄	3	¹ / ₈
NSB300-4-75	7 ³ / ₄	3	⁵ / ₃₂
NSB300-4.5-100	8 ³ / ₄	4	³ / ₁₆
NSB300-4.5-50	6 ³ / ₄	2	³ / ₁₆
NSB300-5-75	7 ³ / ₄	3	³ / ₁₆
NSB300-5-100	8 ³ / ₄	4	³ / ₁₆
NSB300-6-100	8 ³ / ₄	4	¹ / ₄
NSB300-6-125	9 ³ / ₄	5	¹ / ₄
NSB300-6-150	10 ³ / ₄	6	¹ / ₄
NSB300-7-150	10 ³ / ₄	6	¹ / ₄
NSB300-8-150	10 ³ / ₄	6	⁵ / ₁₆
NSB300-8-200	12 ¹ / ₂	7 ³ / ₄	⁵ / ₁₆
NSB300-9-250	14 ¹ / ₂	9 ³ / ₄	⁵ / ₁₆
NSB300-10-200	12 ¹ / ₂	7 ³ / ₄	³ / ₈
NSB300-10-300	12 ¹ / ₂	7 ³ / ₄	³ / ₈
NSB300-11-250	14 ¹ / ₂	9 ³ / ₄	¹ / ₂
NSB300-11-300	16 ¹ / ₂	11 ³ / ₄	¹ / ₂
NSB300-11-350	18 ¹ / ₂	13 ³ / ₄	¹ / ₂
NSB300-12-400	20 ¹ / ₂	15 ³ / ₄	¹ / ₂
NSB300-13-450	22 ¹ / ₂	17 ³ / ₄	¹ / ₂

Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.



NSB300-6-100

ergo



NSB301-4-100



NON-SPARKING ERGO® ELECTRICIAN'S SCREWDRIVERS

Copper Beryllium

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
NSB301-3-50	6 ¾	2	⅛
NSB301-4-100	8 ¾	4	⅜
NSB301-4-150	10 ¾	6	⅜
NSB301-5-100	8 ¾	4	⅜
NSB301-5-200	12 ½	7 ¾	⅜
NSB301-6-100	8 ¾	4	¼
NSB301-8-150	10 ¾	6	⅜
NSB301-10-200	12 ½	7 ¾	⅜
NSB301-10-300	16 ½	11 ¾	⅜

Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.

ergo



NSB302-3-150



NON-SPARKING ERGO® PHILLIPS® SCREWDRIVERS

Copper Beryllium

Product Code	Overall Length	Blade Length	Point Size
NSB302-0-50	6 ¾	2	0
NSB302-1-100	8 ¾	4	1
NSB302-2-125	9 ¾	5	2
NSB302-3-150	10 ¾	6	3
NSB302-4-300	16 ½	11 ¾	4

Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.

ergo



NSB304-2-125



NON-SPARKING ERGO® POZIDRIV® SCREWDRIVERS

Copper Beryllium

Product Code	Overall Length	Blade Length	Point Size
NSB304-0-50	6 ¾	2	PZ0
NSB304-1-100	8 ¾	4	PZ1
NSB304-2-125	9 ¾	5	PZ2
NSB304-3-150	10 ¾	6	PZ3
NSB304-4-300	16 ½	11 ¾	PZ4

Features

- Safe and suitable for use in hazardous environments to reduce the risk of producing ignitable sparks.
- Material: Copper Beryllium
- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Anti-magnetic and highly corrosion resistant.