

JACTO HD 400

16 Litre Manual Knapsack Sprayer

Internal, High-Efficiency Piston pump

Long-life, chemical resistant Viton® seals. Operates with minimum effort. Safety valve prevents overloading.

Pumping Lever With Hand Grip

Can be mounted for left or right hand operation. Requires less pumping effort.

Lance Holder Clips

To secure lance for transportation and storage.

Carrying Straps

Easy and quickly adjusted. With shoulder pads.

Flat Bottom Base

Sits on the ground without tipping for easy filling and storage.

Comes With 3 Different Nozzles

Nozzle cap is compatible with any standard nozzle attachment. Fitted with nozzle filter.

Carrying Handle

For easy transportation.

Wide Filler Opening

Wide 115 mm filler opening and deep basket strainer facilitate cleaning and quick filling. Tank lid has one-way breather valve to prevent leaking.

16 Litre Ergonomically Designed Tank

Contoured for maximum comfort. Impact, corrosion and UV resistant, high density polyethylene. Filling scale in gallons and litres.

Built-In Agitator

Internal agitator constantly mixes chemical solution.

High Pressure Hose

1800 mm long.

Heavy-Duty Trigger Valve

Easy to operate. Lever also locks for constant spraying. With in-line filter.

Light-Weight

Weighs just 3.4 kg empty.

Reinforce Spray Lance

500 mm long for optimum operating efficiency.



Field service kit supplied with every sprayer for ease of repair and maintenance.

The HD Series - Heavy Duty Knapsack Sprayers

Independently tested for 1500 hours of use with no breakdowns.

Jacto HD400




Optional Accessories



Calibrator Bottle

The easiest and fastest way to calibrate a knapsack sprayer. Avoids waste and damage to the environment.



Flexible Boom

Holds the required shape for better coverage of row crops.



Spray Hood

Prevents drift and unwanted contact of non-selective herbicides with the crop.



Spray Lance 160

Mounted with two nozzles to improve penetration specially on perennial crops.



VPC -1 & 2 bar Constant Pressure Valve

Provides even flow rate and spray angle. Reduces the pumping frequency with better use of the pressure accumulated in the chamber. Reduces drift and improves safety and quality of applications.



Optional Trigger valves

Choose from brass or plastic body or optional HD filter.



Double Nozzle Holder

For high volume spraying.



Double Nozzle Boom

Mounted with two nozzles. Improves coverage while increasing productivity.



Optional Spray Lances



Extensin 700

Increases the application reach on garden beds or high trees.



Brass Spray Lance Extension

Longer reach for hard to get spots.

Specifications

	HD 400
Net Weight	3.4 kg
Tank Capacity	16 litres
Dimensions	380 x 175 x 560 mm
Installed Nozzle	JD - 12 P
Flow Rate	615 ml/min
Pump Type	Piston
Working Pressure	1 - 4 bar