



Reliable DO tests made Simple

State of the art Luminescent Optical DO Sensor

- Easy to use compared to the traditional electrochemical methods. No need to wait for probe polarization. No electrolyte solution.
- The probe does not consume oxygen. No limit on water flowing speed. Quick response time: it takes only 2 to 3 minutes for the readings to be stable.
- Minimal maintenance. No need to calibrate before every use.
- The service life of the luminescent cap is over 8000 hours. No need to replace the cap often.
- The special coating on the luminescent cap makes it anti-interference and unaffected by light and chemicals.
- A calibration cap comes with the probe, which allows it to be calibrated and stored in saturated air.



	MODEL	DO850	DO8500
Dissolved Oxygen	Range	0-200%; 0-20.0mg/L	
	Resolution	0.1%, 0.01mg/L (ppm)	
	Accuracy	$\pm 2\%$ of reading or $\pm 2\%$ of saturation, whichever is greater; $\pm 2\%$ of reading or ± 0.2 mg/L (ppm), whichever is greater	
	Calibration Points	Zero Oxygen and saturated oxygen	
	Temp. Compensation	0 to 50°C (32 to 122°F) Automatic	
	Air Pressure Compensation	60 to 120 kPa Automatic	
	Salinity Compensation	Manual	Automatic or Manual
Temperature	Range	0 to 50.0 °C (32 to 122 °F)	
	Resolution	0.1 °C	
	Accuracy	±0.5 °C	
Instrument specs	Stable reading indication	Yes	
	Reading Auto-Lock	Yes	
	Display	White Backlit LCD	
	Data Storage	N/A	500 groups (with time and date)
	Digital Clock	N/A	Yes
	Data Output	N/A	USB
	IP Rating	IP57 Waterproof rating	
	Power Supply	AA Batteries×3 Battery life> 200 Hours	AA Batteries×3 Battery life> 200 Hours / USB



Intelligent Functions

- Auto temperature compensation; Auto Air Pressure Compensation
- Auto Salinity Compensation (only for D08500)
- Large backlit LCD screen, simultaneously displaying dissolved oxygen reading and temperature. Users can switch from "mg/L & %" to "ppm & %".
- Advanced digital processing technology, which supports stable reading and auto-lock display modes
- D08500 has a built-in digital clock and supports manual/auto data logging with USB data output.

Durable Structure Design

- IP57 Waterproof rating allows the meter to be used in harsh environments.
- Comes with a rugged carrying case, which includes a meter, an optical DO probe, and the accessories.

Foldable stand allows use as benchtop meters





APERA Instruments (Europe) GmbH Wilhelm-Muthman-Strasse 15 42329 Wuppertal, Germany Tel.: +49 (0)202 5198 8998 info@aperainst.de www.aperainst.de