



Model	■ =Electric	JCPT0708DCS	JCPT0607DCS
Size			
Max. Working Height		7.60m	5.60m
Max. Platform Height		5.60m	3.60m
Overall Length(With)		1.52m	1.44m
Overall Length(Without Ladder)		1.37m	1.29m
Overall Width		0.81m	0.76m
Overall Height(Rails Up)		2.12m	2.02m
Overall Height(Rails Down)		1.76m	1.66m
Platform Size(Length×Width)		1.37m×0.70m	1.29m×0.70m
Platform Extension Size		0.60m	0.60m
Ground Clearance(Stowed/Raised)		0.06m/0.015m	0.06m/0.015m
Wheelbase		1.13m	1.05m
Turning Radius(Inside/Outside)		0.45m/1.60m	0.40m/1.50m
Tyres		φ230×100mm	φ230×80mm

Performance			
S.W.L		230kg	240kg
S.W.L On Extension		113kg	100kg
Max. Occupants		2	2
Gradeability		25%	25%
Travel Speed(Stowed)		4.0km/h	4.0km/h
Travel Speed(Raised)		0.6km/h	0.5km/h
Max. Working Slope		1.5°/3°	1.5°/3°
Up/Down Speed		26/21sec	32/27sec

Weight			
Overall Weight		1240kg	880kg

Power			
Battery		2×12V/115Ah	2×12V/85Ah
Charger		24V/15A	24V/15A
Driving Motor		24V/0.5kW	24V/0.4kW
Lifting Motor		24V/2.2kW	24V/1.2kW

Other Configurations			
4×2 Driving	Forklift Pockets	Automatic Pothole Protection Device	


Self-propelled Scissor Lifts(Electric Mini Type)

Model: JCPT0708DCS - JCPT0607DCS

Mini scissor lifts series uses the battery as the power source. The maximum working height covers 5.9-7.6m and the maximum load is 240kg. The whole machine is compact and flexible, small in size, light in weight, and can enter and exit the elevator at will. It is specially designed for building interlayer aerial working.



Safety Bracket



Great Passability



Slide-out Tray



Folding Guardrails