

Model <span style="color: green;">■</span> =Electric	JCPT1212 AC/HA	JCPT1012AC AC/HA	JCPT1008 AC/HA
<b>Size</b>			
Max. Working Height	12.00m	10.00m	10.00m
Max. Platform Height	10.00m	8.00m	8.00m
Overall Length	2.48m	2.48m	2.48m
Overall Width	1.15m	1.15m	0.83m
Overall Height(Rails Up)	2.49m	2.36m	2.36m
Overall Height(Rails Down)	1.96m	1.83m	2.00m
Platform Size(Length×Width)	2.27×1.12m	2.27×1.12m	2.27×0.81m
Platform Extension Size	0.90m	0.90m	0.90m
Ground Clearance(Stowed/Raised)	0.10m/0.019m	0.10m/0.019m	0.10m/0.019m
Wheelbase	1.87m	1.87m	1.87m
Turning Radius(Inside/Outside)	0m/2.20m	0m/2.20m	0m/2.1m
Tyres	φ381×127mm	φ381×127mm	φ381×127mm

<b>Performance</b>			
S.W.L	320kg	450kg	230kg
S.W.L On Extension	113kg	113kg	113kg
Max. Occupants	2	2	2
Gradeability	25%	25%	25%
Max. Working Slope	1.5°/3°	1.5°/3°	1.5°/3°
Travel Speed(Stowed)	<b>AC:</b> 5km/h <b>HA:</b> 3.5km/h	<b>AC:</b> 5km/h <b>HA:</b> 3.5km/h	<b>AC:</b> 5km/h <b>HA:</b> 3.5km/h
Travel Speed(Raised)	0.8km/h	0.8km/h	0.8km/h
Up/Down Speed	<b>AC:</b> 54/45sec <b>HA:</b> 55/49sec	34/30sec	<b>AC:</b> 32/36sec <b>HA:</b> 27/36sec

<b>Weight</b>			
Overall Weight	<b>AC:</b> 3060kg <b>HA:</b> 3050kg	<b>AC:</b> 2710kg <b>HA:</b> 2670kg	<b>AC:</b> 2230kg <b>HA:</b> 2190kg
Overall Weight	<b>AC:</b> 3000kg <b>HA:</b> 2990kg	<b>AC:</b> 2650kg <b>HA:</b> 2610kg	<b>AC:</b> 2170kg <b>HA:</b> 2130kg

<b>Power</b>			
Battery	4×6V/220Ah	4×6V/170Ah	4×6V/170Ah
Charger	24V/30A	24V/30A	24V/30A
Driving Motor	<b>AC:</b> 2×24VAC/0.87kW	<b>AC:</b> 2×24VAC/0.87kW	<b>AC:</b> 2×24VAC/0.87kW
Lifting Motor	24VAC/3.5kW	24VAC/3.5kW	24VAC/3.5kW

<b>Other Configurations</b>			
Overload Sensor With Alarm AC Power To Platform Platform Work Lights Airline To Platform Ultrasonic Anti-collision Sensor			
IoT (internet Of Things) Module Lithium Battery High-power Charger Lithium Battery Foot-pedal Switch Anti-collision Bar			

Model <span style="color: green;">■</span> =Electric	JCPT0808 AC/HA	JCPT0807 AC/HA
<b>Size</b>		
Max. Working Height	8.00m	7.80m
Max. Platform Height	6.00m	5.80m
Overall Length	2.48m	1.86m
Overall Width	0.83m	0.76m
Overall Height(Rails Up)	2.23m	2.15m
Overall Height(Rails Down)	1.87m	1.83m
Platform Size(Length×Width)	2.27×0.81m	1.67×0.74m
Platform Extension Size	0.90m	0.90m
Ground Clearance(Stowed/Raised)	0.10m/0.019m	0.09m/0.016m
Wheelbase	1.87m	1.36m
Turning Radius(Inside/Outside)	0m/2.1m	0m/1.64m
Tyres	φ381×127mm	Φ323×100mm

<b>Performance</b>		
S.W.L	380kg	230kg
S.W.L On Extension	113kg	113kg
Max. Occupants	2	2
Gradeability	25%	25%
Max. Working Slope	1.5°/3°	1.5°/3°
Travel Speed(Stowed)	<b>AC:</b> 5km/h <b>HA:</b> 3.5km/h	<b>AC:</b> 4.5km/h <b>HA:</b> 4.0km/h
Travel Speed(Raised)	0.8km/h	0.6km/h
Up/Down Speed	25/42sec	18/26sec

<b>Weight</b>		
Overall Weight	<b>AC:</b> 2160kg <b>HA:</b> 2120kg	<b>AC:</b> 1630kg <b>HA:</b> 1610kg
Overall Weight	<b>AC:</b> 2100kg <b>HA:</b> 2060kg	<b>AC:</b> 1580kg <b>HA:</b> 1560kg

<b>Power</b>		
Battery	4×6V/170Ah	4×6V/170Ah
Charger	24V/30A	24V/30A
Driving Motor	<b>AC:</b> 2×24VAC/0.87kW	<b>AC:</b> 2×24VAC/0.5kW
Lifting Motor	24VAC/3.5kW	24VAC/3kW

<b>Other Configurations</b>		
Overload Sensor With Alarm AC Power To Platform Platform Work Lights Airline To Platform Ultrasonic Anti-collision Sensor		
IoT (internet Of Things) Module Lithium Battery High-power Charger Lithium Battery Foot-pedal Switch Anti-collision Bar		