



SIRIM QAS INTERNATIONAL SDN. BHD.

(No. Syarikat 199601037981(410334-X))

1, Persiaran Dato' Menteri, Seksyen 2, Peti Surat 7035, 40700 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel : 603-5544 6400 Emel : cserviceqas@sirim.my www.sirim-qas.com.my

File No : P5-013557
Licence No : PC004432

Date : 15/06/2023

MAGNUM CABLE SDN. BHD.
8, JALAN TP 4
TAMAN PERINDUSTRIAN BUKIT RAMBAI FASA 6
75250 MELAKA TENGAH
MELAKA, MALAYSIA

Attn : KC TUI

Tel No : 06-3513789

Fax No : 06-3513780

Dear Sir/Madam,

Product Certification Licence

Product : POWER CABLES WITH EXTRUDED SOLID INSULATION
Standard : IEC 60502-1 : 2009

With regards to your request for new/renewal/changes of licence(s) under the SIRIM Product Certification Licence scheme, enclosed please find the copy of the licence(s) and the certification report(s) for your safe keeping.

For enquiry, please contact

Officer Name : MOHD NUR NAZMI BIN AB. HALIM
Contact No : 603-55445694
Email : nurnazmi@sirim.my

Thank you.

This is a computer generated document. No signature is required.

LESEN PENSIJILAN BARANGAN

Product Certification Licence



**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to**

**MAGNUM CABLE SDN. BHD.
8, JALAN TP 4
TAMAN PERINDUSTRIAN BUKIT RAMBAI FASA 6
75250 MELAKA TENGAH
MELAKA, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on**

POWER CABLES WITH EXTRUDED SOLID INSULATION

Please refer to detail in the SCHEDULE

**sebagai mematuhi keperluan
as complying with**

IEC 60502-1 : 2009



Nur Fadhilah binti Muhammad
Ketua Pegawai Eksekutif
Chief Executive Officer
SIRIM QAS International Sdn. Bhd.



SCHEDULE

MAGNUM CABLE SDN. BHD.



Trade Mark : Magnum Cable
Model : XLPE INSULATED, PVC SHEATHED, ARMOURED, STRANDED ANNEALED
COPPER CONDUCTOR
Rating : 600/1000V
Size : 1 CORE, 2 CORE, 3 CORE, 4 CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120,
150, 185, 240, 300, 400, 500, 630)mm²

Trade Mark : Magnum Cable
Model : XLPE INSULATED, PVC SHEATHED, NON-ARMOURED, STRANDED ANNEALED
COPPER CONDUCTOR
Rating : 600/1000V
Size : 1 CORE, 2 CORE, 3 CORE, 4 CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120,
150, 185, 240, 300, 400, 500, 630)mm²

End of page
