

SKINNER PRESSED STEEL CLAMP

BODY C-1008 HR PICKLED STEEL PLATE
 GASKET BUNA N MATERIAL ASTM D 2000
 DUROMETER 50 +/-5
 -40 DEGREES F-250 DEGREES F TEMPERATURE RANGE
 HARDWARE SAE GRADE 5, ZINC PLATED C-1541 STEEL
 E COATING JDM F11T3 18 MILL THICKNESS

NOTE: Viton Gasket available for the Pressed Steel Wide Clamps upon request for high temperature applications.

MODEL "PS" WIDE



MODEL "PS" NARROW



The Pressed Steel Clamp is available in two widths:
Narrow: 4" wide for pit holes, complete with Cone Plug Gasket fastened in place.
Wide: 8" wide for running corrosion spots, complete with a crescent-shaped, pressure-equalizing gasket of Skinner Special Composition for use on oil or gas lines.

Size (inches)	NARROW STYLE		WIDE STYLE	
	Part Number	Approx. Weight (lbs.)	Part Number	Approx. Weight (lbs.)
3	089624	3.5	089625	7.0
4 OD	089623	3.75		
4	089621	4	089620	8.5
5	089617	5	089616	10.5
6 OD	089615	5		
6	089613	5.5	089612	11.25
8	089607	7	089606	14
10	089603	8	089602	17
12	089600	9	089599	19
14	089598	10	089597	20.5
16	089596	11.5	089595	23
18	089594	12.5	089593	26
20	089592	14	089591	28.5
24	089589	17.5	089588	33.5
30	089583	24	089582	42
36	089581	32	089580	50

Size	Narrow		Wide	
	Torque	Working Pressure	Torque	Working Pressure
3"	60 ft/lbs	1000 psi	60 ft/lbs	500 psi
4"	60 ft/lbs	1000 psi	60 ft/lbs	500 psi
5"	60 ft/lbs	1000 psi	60 ft/lbs	500 psi
6"	60 ft/lbs	1000 psi	60 ft/lbs	500 psi
8"	60 ft/lbs	1000 psi	60 ft/lbs	400 psi
10"	60 ft/lbs	1000 psi	60 ft/lbs	400 psi
12"	60 ft/lbs	1000 psi	60 ft/lbs	300 psi
14"	60 ft/lbs	1000 psi	60 ft/lbs	300 psi
16"	60 ft/lbs	800 psi	60 ft/lbs	300 psi
18"	60 ft/lbs	800 psi	60 ft/lbs	200 psi
20"	60 ft/lbs	800 psi	60 ft/lbs	200 psi
24"	60 ft/lbs	800 psi	60 ft/lbs	200 psi