

## LESEN PENSIJILAN BARANGAN

*Product Certification Licence*



SIRIM

**SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada  
SIRIM QAS International Sdn. Bhd. hereby grants to**

**UTAMA CABLES SDN. BHD.  
JA 955, PLOT 5C-D  
KAWASAN PERINDUSTRIAN MERLIMAU  
77300 MERLIMAU  
MELAKA, MALAYSIA**

**Lesen untuk menggunakan Tanda Pensijilan di atas barangan  
a licence to use the Certification Mark on**

**POWER CABLES WITH EXTRUDED SOLID INSULATION**

**Please refer to detail in the SCHEDULE**

**sebagai mematuhi keperluan  
as complying with**

**IEC 60502-1 : 2004**



**Nur Fadhilah binti Muhammad**  
Ketua Pegawai Eksekutif  
*Chief Executive Officer*  
SIRIM QAS International Sdn. Bhd.



# SCHEDULE

**UTAMA CABLES SDN. BHD.**



Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, NON-ARMoured, SHAPED STRANDED PLAIN ANNEALED COPPER CONDUCTOR 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, NON-ARMoured, STRANDED CIRCULAR COMPACTED PLAIN ALUMINIUM CONDUCTOR SINGLE CORE (16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630, 800, 1000)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, ARMoured, SHAPED STRANDED PLAIN ALUMINIUM CONDUCTOR 2-CORE, 3-CORE, 4-CORE (16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, ARMoured MULTICORE, AUXILIARY STRANDED COPPER CONDUCTOR 7, 12, 19, 27, 37, 48-CORE (1.5, 2.5, 4)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED ARMoured, STRANDED CIRCULAR COMPACTED PLAIN ANNEALED COPPER CONDUCTOR SINGLE CORE (16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, ARMoured, SHAPED STRANDED PLAIN ANNEALED COPPER CONDUCTOR 2-CORE, 3-CORE, 4-CORE (1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500)MM <sup>2</sup>
Rating	: 600/1000V
Trade Mark	: UTAMA
Model	: XLPE INSULATED PVC SHEATHED, NON-ARMoured, STRANDED CIRCULAR COMPACTED PLAIN ANNEALED COPPER CONDUCTOR SINGLE CORE (16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500, 630, 800, 1000)MM <sup>2</sup>
Rating	: 600/1000V

**End of page**