

**Jobber Length, Cobalt, 135° Point (Blue-Point®)**

Stock No.	Size, inches	Stock No.	Size, inches
DBBPC1/16	1/16	DBBPC15/64	15/64
DBBPC5/64	5/64	DBBPC1/4	1/4
DBBPC3/32	3/32	DBBPC17/64	17/64
DBBPC7/64	7/64	DBBPC9/32	9/32
DBBPC1/8	1/8	DBBPC19/64	19/64
DBBPC9/64	9/64	DBBPC5/16	5/16
DBBPC5/32	5/32	DBBPC21/64	21/64
DBBPC11/64	11/64	DBBPC11/32	11/32
DBBPC3/16	3/16	DBBPC23/64	23/64
DBBPC13/64	13/64	DBBPC3/8	3/8
DBBPC7/32	7/32		

**DBBPC21 21 pc Cobalt Drill Bit Set (Blue-Point®)**

- Ideal for drilling low- and medium-carbon steel, plus steel alloy
- 135° split point penetrates on contact and prevents walking of the bit
- Jobber length for access in tight locations
- Cobalt construction for higher temperature applications
- Use CL6 Cutting Oil to maximize drill bit life
- Includes DBBPC1/16–DBBPC3/8 (1/16–3/8") in metal drill bit index


**DBBPC21**
**Jobber Length, High-Speed Steel, 135° Point (Blue-Point®)**

Stock No.	Size, inches	Stock No.	Size, inches
DBBP1/16	1/16	DBBP15/64	15/64
DBBP5/64	5/64	DBBP1/4	1/4
DBBP3/32	3/32	DBBP17/64	17/64
DBBP7/64	7/64	DBBP9/32	9/32
DBBP1/8	1/8	DBBP19/64	19/64
DBBP9/64	9/64	DBBP5/16	5/16
DBBP5/32	5/32	DBBP21/64	21/64
DBBP11/64	11/64	DBBP11/32	11/32
DBBP3/16	3/16	DBBP23/64	23/64
DBBP13/64	13/64	DBBP3/8	3/8
DBBP7/32	7/32		

**DBBP21 21 pc HSS Drill Bit Set (Blue-Point®)**

- Includes (21) drill bits (1/16–3/8")
- Includes metal drill index


**DBBP21**
**Jobber Length, HSS Titanium Coated, 135° Point (Blue-Point®)**


Stock No.	Size, inches	Stock No.	Size, inches
DBBPT1/16	1/16	DBBPT11/64	11/64
DBBPT5/64	5/64	DBBPT3/16	3/16
DBBPT3/32	3/32	DBBPT13/64	13/64
DBBPT7/64	7/64	DBBPT7/32	7/32
DBBPT1/8	1/8	DBBPT15/64	15/64
DBBPT9/64	9/64	DBBPT1/4	1/4
DBBPT5/32	5/32		

**DBBPT13 13 pc HSS Titanium-Coated Drill Bit Set (Blue-Point®)**

- Ideal for drilling aluminum, copper, plastic and cast iron
- Titanium-coated high-speed steel for heavy-duty applications
- Designed for increased speed and feed rates
- 135° point
- Titanium coating resists rust
- Use CL6 Cutting Oil to maximize drill bit life
- Includes DBBPT1/16–DBBPT1/4 (1/16–1/4") in metal drill bit index


**DBBPT13**


‡These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1–P2 for details.  
• Read Safety Precautions on pages W1–W4



DBD110A



DBD1/8AMP10



DBLS105B



DBCL105B

## Double-Ended, 135° Split Point

Set Contains:

DBD110A<sup>†</sup>

Stock No.	Description	Size	
DBD7/64A <sup>†</sup>	7/64" Double Ended Drill Bit	7/64"	•
DBD1/8A <sup>†</sup>	1/8" Double Ended 135° Split Point Drill Bit	1/8"	•
DBD9/64A <sup>†</sup>	9/64" Double Ended Drill Bit	9/64"	•
DBD5/32A <sup>†</sup>	5/32" Double Ended Drill Bit	5/32"	•
DBD3/16A <sup>†</sup>	3/16" Double Ended 135° Split Point Drill Bit	3/16"	•
DBD7/32A <sup>†</sup>	7/32" Double Ended Drill Bit	7/32"	•
DBD1/4A <sup>†</sup>	1/4" Double Ended 135° Split Point Drill Bit	1/4"	•
DBD11A <sup>†</sup>	#11 Double Ended Drill Bit	#11	•
DBD20A <sup>†</sup>	#20 Double Ended Drill Bit	#20	•
DBD30A <sup>†</sup>	#30 Double Ended Drill Bit	#30	•

### DBD110A<sup>†</sup> 10 pc Double-Ended 135° Split Point Drill Bit Set

- Includes (10 pc) (7/64–1/4", #11, #20 and #30)
- Includes a plastic pouch

### DBD1/8AMP10<sup>†</sup> 1/8" Double-Ended 135° Split Point Drill Bit

- Used for pop rivet applications and drilling thin sheet metal
- 135° split point for fast penetration
- Made from long-lasting high-speed steel
- (10 pc) of DBD1/8A drill bits

## Left-Hand Fractional Drill Bits, High Speed Steel

Stock No.	Size, inches
DBLS1/8B <sup>†</sup>	1/8
DBLS3/16B <sup>†</sup>	3/16
DBLS1/4B <sup>†</sup>	1/4

Stock No.	Size, inches
DBLS5/16B <sup>†</sup>	5/16
DBLS11/32B <sup>†</sup>	11/32

### DBLS105B<sup>†</sup> 5 pc Left-Hand High-Speed Drill Bit Set

- Use left-hand drill bits to make a hole in the broken screw before the extractor is inserted
- Left-hand drill bits tend to loosen screws for easier removal
- Set includes (5) drill bits (1/8–11/32) in a plastic pouch

## Left-Hand Fractional Drill Bits, Cobalt

Set Contains:

DBCL105B<sup>†</sup>

Stock No.	Size, inches	
DBCL5/64B <sup>†</sup>	5/64	•
DBCL7/64B <sup>†</sup>	7/64	•
DBCL5/32B <sup>†</sup>	5/32	•
DBCL3/16A <sup>†</sup>	3/16	
DBCL1/4B <sup>†</sup>	1/4	•
DBCL9/32A <sup>†</sup>	9/32	
DBCL1/2A <sup>†</sup>	1/2	
DBCL19/64B <sup>†</sup>	19/64	•

Set Contains:

DBCL105B<sup>†</sup>

Stock No.	Size, inches	
DBCL5/16A <sup>†</sup>	5/16	
DBCL11/32A <sup>†</sup>	11/32	
DBCL3/8A <sup>†</sup>	3/8	
DBCL13/32A <sup>†</sup>	13/32	
DBCL7/16A <sup>†</sup>	7/16	
DBCL15/32A <sup>†</sup>	15/32	
DBCL1/2A <sup>†</sup>	1/2	

### DBCL105B<sup>†</sup> 5 pc Left-Hand Cobalt Drill Bit Set

- Use left-hand drill bits to make a hole in the broken screw before the extractor is inserted
- Left-hand drill bits tend to loosen screws for easier removal
- Set includes DBCL5/64B, DBCL7/64B, DBCL5/32B, DBCL1/4B and DBCL19/64B drill bits in a plastic pouch

Set Contains:  
 DBH11B  
 DBH7B

Stock No.	Size, inches		
DBH1/16B	1/16	•	•
DBH3/32B	3/32	•	•
DBH1/8B	1/8	•	•
DBH5/32B	5/32	•	•
DBH3/16B	3/16	•	•
DBH7/32B	7/32	•	•
DBH1/4BB	1/4	•	•
DBH9/32B	9/32	•	
DBH5/16B	5/16	•	
DBH11/32B	11/32	•	
DBH3/8B	3/8	•	


**DBH7B**

**DBH11B**
**Hex Shank Drill Bits**

- Black-oxide finish prevents rust and reduces operating temperature
- 118° point provides fast starts and optimal performance in thin-gauge material
- Hex drive design provides the ability to quickly adapt to all hex drive chucks
- Tapered fit of drill to hex drive shank eliminates bit wobble or runout to provide easier starting and a more precise hole
- Screw machine length allows the bits to be used in tight spaces
- Made in the US

**DBH7B 7 pc Hex Shank Drill Bit Set**

- Includes (7 pc) DBH1/16B–DBH1/4BB (1/16–1/4") in DBH7B-1 kit bag

**DBH11B 11 pc Hex Shank Drill Bit Set**

- Includes DBH1/16B–DBH3/8B (1/16–3/8") in DBH11B-1 kit bag

**Left-Hand Short Fractional Drill Bits, Cobalt**

 Set Contains:  
 DBTRCSL11

Stock No.	Size, inches	
DBTRCSL1/16 <sup>‡</sup>	1/16	•
DBTRCSL3/32 <sup>‡</sup>	3/32	•
DBTRCSL1/8 <sup>‡</sup>	1/8	•
DBTRCSL5/32 <sup>‡</sup>	5/32	•
DBTRCSL3/16 <sup>‡</sup>	3/16	•
DBTRCSL7/32 <sup>‡</sup>	7/32	•
DBTRCSL1/4 <sup>‡</sup>	1/4	•
DBTRCSL9/32 <sup>‡</sup>	9/32	•
DBTRCSL5/16 <sup>‡</sup>	5/16	•
DBTRCSL11/32 <sup>‡</sup>	11/32	•
DBTRCSL3/8 <sup>‡</sup>	3/8	•

**DBTRCSL11<sup>‡</sup> 11 pc Left-Hand Cobalt Short Drill Bit Set with Flats**

- Screw machine length for getting into smaller areas
- Flats on larger sized drill bits provide a better grip when used with keyless chucks (3/16–3/8")
- Left-hand flute for removing broken bolts
- Cobalt steel for drilling harder materials
- Bit lengths from 1.7–3.1"
- 11 most popular drill sizes in one set
- Includes (11) bits and a kit bag


**DBTRCSL11**
**90° Angle Drill Set**

 Set Contains:  
 YA409

Size	2-1/8" Long Bit Stock No.	1-1/4" Medium Bit Stock No.	3/4" Short Bit Stock No.
#10	YA409-10L	YA409-10M	YA409-10S
#11	—	—	YA409-11S
#13	—	—	YA409-13S
#20	—	—	YA409-20S
#21	—	—	YA409-21S
#30	YA409-30L	YA409-30M	YA409-30S
1/8"	YA409-18L	YA409-18M	YA409-18S
3/16"	YA409-316L	YA409-316M	YA409-316S
3/32"	YA409-332L	YA409-332M	YA409-332S
#40	YA409-40L	YA409-40M	YA409-40S
5/32"	YA409-532L	YA409-532M	YA409-532S
1/4"	YA409-14L	YA409-14M	YA409-14S

**YA409 90° Angle Drill Kit (Blue-Point®)**

- Allows drilling up to 1/4" holes in confined areas by positioning the bit at a 90° angle to the drill
- Threaded drill bits provide consistent concentricity and eliminate slippage
- Includes
  - YA409 Drive unit; chucking spud
  - YA409-316M 3/16" bit (1-1/4" long)
  - YA409-18L 1/8" bit (2-1/8" long)
  - YA409-332L 3/32" bit (2-1/8" long)
  - YA409-18M 1/8" bit (1-1/4" long)
  - YA409-532M 5/32" bit (1-1/4" long)
  - YA409-18S 1/8" bit (3/4" long)
  - YA409-15 Storage Case


**YA409**
**YA409-6 Threaded Collet (Blue-Point®)**

- Allows the use of 1/4" dia. shank grinding burrs and abrasive wheels



‡These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1–P2 for details.  
 • Read Safety Precautions on pages W1–W4

## SPECIALIZED DRILL BITS

### 1/2" Reduced-Shank Drill Bit, 118° Point

- Ideal for cutting in low- and medium-tensile strength materials
- Flatted shank provides a more secure grip for the drill chuck



CSE485B

Stock No.	Size, inches	Stock No.	Size, inches
CSE345B <sup>‡</sup>	17/32	CSE475 <sup>‡</sup>	45/64
CSE365B <sup>‡</sup>	9/16	CSE485B <sup>‡</sup>	3/4
CSE375 <sup>‡</sup>	37/64	CSE505B <sup>‡</sup>	25/32
CSE385B <sup>‡</sup>	19/32	CSE525B <sup>‡</sup>	13/16
CSE405B <sup>‡</sup>	5/8	CSE565B <sup>‡</sup>	7/8
CSE425B <sup>‡</sup>	21/32	CSE575 <sup>‡</sup>	59/64
CSE445B <sup>‡</sup>	11/16	CSE605B <sup>‡</sup>	15/16
CSE465B <sup>‡</sup>	23/32	CSE645B <sup>‡</sup>	1

<sup>‡</sup>Use with TDP6 Pipe Tap Set.

### Aircraft Length, 135° Split Point

- Extra-long bits for drilling thick materials



DBK7A

Set Contains: DBK7A<sup>‡</sup>

Stock No.	Size, inches	Flute Length, inches	Length, inches	
DBT1/8A <sup>‡</sup>	1/8	1-5/8	12	•
DBT3/16A <sup>‡</sup>	3/16	2-1/4	12	•
DBT1/4A <sup>‡</sup>	1/4	2-3/4	12	•
DBT5/16A <sup>‡</sup>	5/16	3-1/4	12	•
DBT3/8A <sup>‡</sup>	3/8	3-3/4	12	•
DBT7/16A <sup>‡</sup>	7/16	4	12	•
DBT1/2A <sup>‡</sup>	1/2	4-1/2	12	•

### Titanium-Nitride Step Drills

- Titanium-nitride coating creates a surface hardness that makes these tools last 4 to 5 times longer than ordinary drill bits
- Surface coating also reduces friction, resulting in a tool that runs cooler while running dry



YA1TA

Stock No.	Size Range	Increments	Shank Size, inches (mm)	Hole Sizes Per Bit	Length, inches
YA1TA	1/8-1/2"	1/32"	1/4 (6.5)	13	3-1/4
YA2TA	3/16-1/2"	1/16"	1/4 (6.5)	6	3-1/4
YA4TA	3/16-7/8"	1/16"	3/8 (10)	12	3
YA1MTA	4-12 mm	1 mm	1/4 (6.5)	9	3-1/4
YA3MTA	6-18 mm	2 mm	3/8 (10)	7	2-5/8
YA4MTA	4-22 mm	2 mm	3/8 (10)	10	3
YA5MTA	5-35 mm	2-3 mm	1/2 (13)	13	3-3/32



YA263A

### Step Drills

Set Contains: YAS203A

Stock No.	Size Range, inches	Increments, inches	Shank Size, inches	Hole Sizes Per Bit	Length, inches	
YA261A	1/8-1/2	1/32	1/4	13	3-1/4	•
YA262A	3/16-1/2	1/16	1/4	6	3-3/8	•
YA263A	1/4-3/4	1/16	3/8	9	2-5/8	
YA265A	3/16-3/8	1/16	1/4	5	1-5/8	•
YA267A	3/16-7/8	1/16	3/8	12	3	
YA266A	9/16-1	1/16	1/2	8	2-1/2	

## HOLE SAWS



### Hole Saws

- High-speed cutting edge is welded to an alloy steel back to absorb shocks
- Cut clean, accurate holes in steel and cast iron pipe, steel plates, aluminum, copper, brass, stainless steel, wood or plastic
- Side slits make it easy to knock out the spent disks

Stock No.	Diameter, inches	Recommended Arbors
LHS18D	9/16	LHS1C, LHS6C
LHS20D	5/8	LHS1C, LHS6C
LHS22D	11/16	LHS1C, LHS6C
LHS24D	3/4	LHS1C, LHS6C
LHS26D	13/16	LHS1C, LHS6C
LHS28D	7/8	LHS1C, LHS6C
LHS30D	15/16	LHS1C, LHS6C
LHS32D	1	LHS1C, LHS6C
LHS34D	1-1/16	LHS1C, LHS6C
LHS36D	1-1/8	LHS1C, LHS6C
LHS38D	1-3/16	LHS1C, LHS6C
LHS40D	1-1/4	LHS3D
LHS42D	1-5/16	LHS3D
LHS44D	1-3/8	LHS3D
LHS46D	1-7/16	LHS3D
LHS48D	1-1/2	LHS3D

Stock No.	Diameter, inches	Recommended Arbors
LHS50D	1-9/16	LHS3D
LHS52D	1-5/8	LHS3D
LHS54D	1-11/16	LHS3D
LHS56D	1-3/4	LHS3D
LHS58D	1-13/16	LHS3D
LHS60D	1-7/8	LHS3D
LHS64D	2	LHS3D
LHS66D	2-1/16	LHS3D
LHS68D	2-1/8	LHS3D
LHS72D	2-1/4	LHS3D
LHS76D	2-3/8	LHS3D
LHS80D	2-1/2	LHS3D
LHS88D	2-3/4	LHS3D
LHS96D	3	LHS3D
LHS128D	4	LHS3D
LHS184D	6	LHS3D

### LHS608B<sup>‡</sup> 9 pc Hole Saw and Arbor Kit

- Side slits make it easy to knock out the spent disks
- Includes LHS44D, LHS48D, LHS56D, LHS64D, LHS80D, LHS96D hole saws, LHS6C and LHS3D arbors, LHS8C arbor adaptor and recommended speed chart in a storage case

### LHS606D<sup>‡</sup> 7 pc Hole Saw and Arbor Kit

- Side slits make it easy to knock out the spent disks
- Includes LHS24D, LHS28D, LHS32D, LHS36D, LHS40D hole saws, LHS6C arbor, LHS8C arbor adaptor and recommended speed chart in a storage case

## Hole Saw Arbors and Pilot Drills

Stock No.	Thread Size	Fits Saws, inches	Fits Drill Chucks, inches	Replacement Pilot Drill
LHS5C	1/2"-20	9/16-1-3/16	1/4	LHS4D
LHS6C	1/2"-20	9/16-1-3/16	3/8	LHS4D
LHS1C	1/2"-20	9/16-1-3/16	1/2	LHS4D
LHS3D	5/8"-18	1-1/4-6	3/8	LHS4D
LHS8C	Arbor Adaptor to Convert 1/2"-20 Thread to 5/8"-18			



## DRILLING ACCESSORIES



YA246A

### YA246A<sup>+</sup> 13 pc Micro Utility Drill Set (Blue-Point<sup>®</sup>)

- Knurled surface at the chuck end of the pin vise provides a sure gripping surface
- Long 1-7/8" drill length
- Includes pin vise and (12) precision HSS twist drills from .0635-.0225", numbers 52-74



B1115A

### B1115A Metal Drill Bit Index

- Clearly marked trays hold 115 drill bits and lift to upright position for quick selection
- 14-1/8 L x 4-1/8 W x 2-1/2" D



DEBUR300

### DEBUR300 Deburring Tool

- Easily deburrs drilled and machined holes
- Push-button locking collet enables quick, easy blade changes
- Includes (3) round-head deburring blades
- Blades store in the handle of tool
- 6" long



RM125



RM150



RM250

### RM125 1/8-3/8" Hex Drive Tapered Reamer

- Compact 3-5/8" length profile provides access to tight locations
- Tough high-speed steel construction with precision cut edges for long life—can be resharpened
- Unique hex-profile for multiple means of use: RMT1 T-Bar (included), socket or palm ratchet
- Each size has an overlap for the largest diameter to the tip of the next reamer size to maintain seamless transitions
- Made in USA

### RM150 1/4-9/16" Hex Drive Tapered Reamer

- Same features as the RM125
- Unique hex-profile for multiple means of use: RMT2 T-Bar (included), socket or palm ratchet

### RM250 1/2-3/4" Hex Drive Tapered Reamer

## SANDER ACCESSORIES

### 14.4 V MicroLithium Polishing/Prep Tools

Stock No.	Description	Stock No.	Description
ACR2ALUM36	2" ROLOC <sup>®</sup> Abrasive Disc	ACR3HOLDER	3" ROLOC <sup>®</sup> Disc Holder
ACR2ALUM80	2" ROLOC <sup>®</sup> Abrasive Disc	ACR3MEDIUM	3" Medium Surface Prep Disc
ACR2CLEAN	2" Crud Disc	CTPP761-900	Disc Pad
ACR2CORSE	2" Coarse Surface Prep Disc	CTPP761-903	3" Knit Buffing Pad
ACR2HOLDER	2" ROLOC <sup>®</sup> Disc Holder	CTPP761-904	3" Sanding Disc, 36 Grit
ACR2MEDIUM	2" Medium Surface Prep Disc	CTPP761-905	3" Sanding Disc, 80 Grit
ACR3ALUM36	3" ROLOC <sup>®</sup> Abrasive Disc	CTPP761-906	2" ROLOC <sup>®</sup> Blocking Pad
ACR3ALUM80	3" ROLOC <sup>®</sup> Abrasive Disc	CTPP761-907	2" ROLOC <sup>®</sup> Medium Surface Disc
ACR3CLEAN	3" Crud Disc	CTPP761-950	Disc Pad Wrench
ACR3CORSE	3" Coarse Surface Prep Disc	CTPP761-951	ROLOC <sup>®</sup> Adaptor



ACR2ALUM36



ACR2CLEAN



†These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.  
• Read Safety Precautions on pages W1-W4

# SANDER ACCESSORIES

POWER TOOLS



AT401ACCKIT



AT402ACCKIT



AT403ACCKIT

## Micro Tool Accessory Kits

### AT401ACCKIT Micro Surface Prep Accessory Kit (Blue-Point®)

- 1/4 turn abrasive disc in two different grits helps get the job of removing rust or gasket material done quickly, even in confined areas
- Kit contains all of the consumables needed to restore a Micro Surface Prep Tool Kit back to new
- Includes (1) 2" ROLOC® pad 1/4" x 20T, (1) 3" ROLOC® pad 1/4" x 20T, (5) 2" 40 grit pads and (5) 3" 80 grit pads

### AT402ACCKIT Micro Dual Action Sander Accessory Kit (Blue-Point®)

- Fresh backing pad with all the sanding disc needed to work the surface down until it is ready for paint
- Kit contains all of the consumables needed to restore a Micro Dual Action Sander Tool Kit back to new
- Includes (1) 3" hook-and-loop pad 5/16" x 24T, (25) 3" 180 grit pads, (25) 3" 220 grit pads, (10) 3" 320 grit pads and (10) 3" 800 grit pads

### AT403ACCKIT Micro Polisher Accessory Kit (Blue-Point®)

- All the pads needed to go from buffing to final polish
- Kit contains all of the consumables needed to restore a Micro Polisher Tool Kit back to new
- Includes (1) 3" hook-and-loop pad 5/16" x 24T, (1) 3" wool pad and (1) foam waffle pad



PS4312-1H

PS4612V-1AH

PS468-34V



AT406CVAC

PSV4312KIT



YA7341

### YA7341<sup>±</sup> Bonnet Cleaning Tool

- Run the spur wheels over a buffing pad or bonnet to dislodge and remove dry, hardened polish

### GO459-39 Vacuum Adaptor

- Vacuum adaptor for PS4609 and PS4809

## Tune-up Kits

### PS46-TKA Tune Up Kit

- For PS4612/PS4512 series orbital sanders

## Replacement Sander Pads

Stock No.	Size, inches	Type	Style	Use on
PS4312-1H	3	PSA	Vacuum/Non-Vacuum	PSF4312
PS4512-1AH	5	PSA	Non-Vacuum	PS4512
PS4512V-1AH	5	PSA	Vacuum	PS4512
PSO4525-2H	5	Velcro® Brand fasteners	Non-Vacuum	PS4512
PS4512V-2H	5	Velcro® Brand fasteners	Vacuum	PS4512
PS4612V-1AH	6	PSA	Vacuum	PS4612 and PSF4612
PSO4625-2H	6	Velcro® Brand fasteners	Non-Vacuum	PS4612 and PSF4612
AT116-4	6	Velcro® Brand fasteners	Vacuum	PS4612 and PSF4612
PS468-34	6	PSA	Non-Vacuum	PS4609
PS468-34V	6	PSA	Vacuum	PS4609V
PSG468-34HL	6	Velcro® Brand fasteners	Non-Vacuum	PS4609
PS468-34VHL	6	Velcro® Brand fasteners	Vacuum	PS4609V
PS468-35	8	PSA	Non-Vacuum	PS4809
PS468-35V	8	PSA	Vacuum	PS4809V
AT116-3	2	Roloc®	Non-Vacuum	AT401MCA
AT116-4	3	Roloc®	Non-Vacuum	AT401MCA
AT402VEL75MM	3	Hook-and-loop	Non-Vacuum	AT402MCA and AT403MCA
AT406C-27	4	Hook-and-loop	Non-Vacuum	AT406C
PSO4325-2H	3	Velcro® Brand fasteners	Vacuum/Non-Vacuum	PSF4312

Vacuum Adaptor Kits (contains vacuum adaptor and shroud)		
Stock No.	Type	Use on
AT406CVAC	Vacuum Kit (AT406C) (Blue-Point®)	AT406C
PSV4312KIT	Vacuum Kit for 3" Sanders	PSF4312



Description	Stock No.	Brush Diameter, inches	Shank Size, Arbor Size	Wire Diameter, inches	Maximum Safe Free Speed, RPM
<b>Crimped Wire Brush (Blue-Point®)</b> Crimped for removing carbon from cylinder heads and valve parts	AC2D‡	1	1/4	.020	20,000
	AC3D‡	3/4	1/4	.020	20,000
<b>Solid End Wire Brush (Blue-Point®)</b> Solid end for cleaning aluminum cylinder heads and transmission parts	AC16D‡	3/4	1/4	.006	20,000
<b>Spiral Twist Wire Brush (Blue-Point®)</b> Spiral twist for removing heavy deposits	AC6B‡	3/4	1/4	.014	20,000
	AC7E‡	1	1/4	.020	20,000
<b>Cup-Type Wire Brush (Blue-Point®)</b> Cup-Type for cleaning wheel rims and scuffing tires	AC240B‡	1-3/4	1/4	.012	6,000
<b>Hollow End Crimped Cup Wire Brush (Blue-Point®)</b> Hollow End crimped cup for light-duty cleaning	AC241B‡	2-1/2	1/4	.012	6,000
<b>Cup Flared Wire Brush (Blue-Point®)</b> Cup flared for deburring, cleaning hard-to-reach areas and wheel rims, and scuffing tires	AC208A‡	1-1/2	1/4	.008	20,000
	AC212A‡	1-1/2	1/4	.012	20,000
	AC214A‡	2-1/2	1/4	.014	18,000
	AC224A‡	3	1/4	.014	15,000
<b>Encapsulated Wire End Wire Brush (Blue-Point®)</b> Encapsulated Wire End Wire Brushes for a consistent stiff brushing action	AC204C‡	1/2	1/4	.014	8,000
	AC205C‡	3/4	1/4	.014	8,000
	AC206C‡	1	1/4	.014	8,000
<b>Single Row Knot-Type Wire Brush (Blue-Point®)</b> Knot-type, single-row wire cup for heavy-duty surface application	AC339A‡	3	5/8-11	.020	12,500
	AC341B‡	3	5/8-11	.012	7,000
	AC342B‡	4	5/8-11	.020	7,000



## General Purpose

Description	Stock No.	Brush Diameter, inches	Shank Size, Arbor Size	Wire Diameter, inches	Maximum Safe Free Speed, RPM
<b>Knotted Wire Wheel Brush (Blue-Point®)</b> Heavy-duty cleaning	AC420A‡	4	5/8-11	.020	20,000
<b>Crimped Wire Wheel (Blue-Point®)</b> General-purpose cleaner	AC616‡	3	1/4	.0118	20,000
<b>Wire Brush (Blue-Point®)</b> Medium-duty general cleaner	AC17D‡	1	1/4	.006	20,000
	AC243‡	3	5/8-11	.014	14,000
<b>End Brush (Blue-Point®)</b> Ideal for cleaning right angles	AC10302‡	1/2	1/4	.014	25,000
	AC10306‡	3/4	1/4	.014	22,000

### A24C Arbor, 1/4" Shank, 1/2" Arbor Adaptor (Blue-Point®)

- Adapts electric drill to light-duty grinding and wire brushing: use with wheels and brushes up to 4" in diameter
- 1/4" shank, 1/2" diameter arbor, 1-3/4" length
- 20,000 RPM maximum speed



**AC3160FWMP‡ Flap Wheel (Blue-Point®)**  
• 3" dia., 60 grit, (10 pack)



**ACMANDREL Mandrel**  
• 1/4" stem for use on 2" and 3" flap discs



**AC4D‡ Brush**



**AC239‡ 1-1/2" Crimped Cup**



- Do not operate without the guard.
- Do not use grinding discs or accessories above their rated RPM.
- Do not use sanding discs or accessories above their maximum rated RPM.
- Do not use wire brushes above their maximum rated RPM.
- Do not use power tool accessories above their maximum rated RPM
- ‡These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.
- Read Safety Precautions on pages W1-W4

## CUTTING AND GRINDING ACCESSORIES



ETA125A

### ETA125A<sup>+</sup> Grinding Wheel Set

- Use with ET1350/ET1360
- 12,000 RPM maximum speed
- 5 pk



AT154RWHLMPA

### AT154RWHLMPA<sup>+</sup> 4" Cutting Wheel (Blue-Point®)

- Aluminum-oxide cutting wheel for all metal types
- 4" dia. with a 3/8" arbor hole
- 21,000 RPM maximum speed



AT215GWSETA

### AT215GWSETA 6 pc 2" Grinding Wheel Set (Blue-Point®)

- Replacement grinding wheels for the AT215 angle grinder
- 20,000 RPM maximum speed
- 6 pk



ETA250A

### ETA250A<sup>+</sup> Grinding Wheel Set (Blue-Point®)

- 1/4 x 4-1/2 x 7/8"
- Coarse 24 grit
- 12,000 RPM maximum speed



AT415-20B

### AT415-20B<sup>+</sup> Grinding Disc

- For the AT415B grinder
- 4" dia. x 3/16" thick with a 5/8" arbor hole
- 12,000 RPM maximum speed
- 5 pk

## CARBIDE BURRS



VWB800D



VWB400A




VWBL400



VWB200C

Grinding burrs are ideal for use with Snap-on® die grinders. 1/4" and 1/8" shank burrs are available, all with solid carbide heads. The 1/8" shank units all have a maximum head diameter of 1/8".



### Carbide Burrs, 1/4" Shank

Set Contains:  
 VWB800D  
 VWB400A  
 VWBL400  
 VWB200C

	Stock No.	Style (chart)	Shank Length, inches	Flute Length, inches	Head Dia., inches	Recommended RPM Cast Iron	Recommended RPM Stainless				
Carbide Burrs, 1/4" Shank	VWB1C	A	—	5/8	1/4	22,000	23,000	•	•		
	VWB9B	A	—	1	1/2	16,000	24,000				
	VWB2B	B	—	3/4	3/8	18,000	27,000	•	•		
	VWB10B	B	—	1	1/2	16,000	24,000				
	VWB3B	C	—	1/4	5/16	20,000	30,000	•			
	VWB4B	D	—	7/8	1/2	16,000	24,000	•			
	VWB11B	E	—	3/4	3/8	18,000	27,000				
	VWB5B	E	—	1	1/2	16,000	24,000	•	•		
	VWB6B	F	—	3/4	3/8	18,000	27,000	•			
	VWB7B	G	—	1-1/8	1/2	16,000	24,000	•	•		
	VWB12B	G	—	1-1/16	3/8	18,000	27,000				
VWB8B	H	—	7/8	1/2	16,000	24,000	•				
Long-Reach Carbide Burrs, 1/4" Shank	VWBL401	—	4	—	3/8	14,000	17,000				•
	VWBL402	—	4	—	3/8	14,000	17,000				•
	VWBL403	—	4	—	3/8	14,000	17,000				•
	VWBL404	—	4	—	3/8	14,000	17,000				•
Wide Fluted Carbide Burrs, 1/4" Shank	VWB206C	A	—	1	1/2	15,000	25,000				•
	VWB204C	A	—	3/4	1/4	15,000	25,000				•
	VWB203C	B	—	1	1/2	15,000	25,000				•
	VWB202C	E	—	1	1/2	15,000	25,000				•
	VWB201C	G	—	1-1/8	1/2	15,000	25,000				•
	VWB205C	G	—	1-1/16	3/8	15,000	25,000				•



VWB700B



Set Contains:

VWB700B

## Carbide Burrs, 1/8" Shank

Stock No.	Style (chart)	Flute Length, inches	Recommended RPM Cast Iron	Recommended RPM Stainless	
VWB301B	A	9/16	20,000	75,000	•
VWB302B	B	9/16	20,000	75,000	•
VWB303B	C	1/8	20,000	75,000	•
VWB304B	D	7/32	20,000	75,000	•
VWB305B	E	1/2	20,000	75,000	•
VWB306B	F	3/8	20,000	75,000	•
VWB307B	G	1/2	20,000	75,000	•
VWB308B	H	7/16	20,000	75,000	•

## AIR HAMMER ACCESSORIES



PHG1055BK  
PHG1056BK  
PHG1005BK

## Air Hammer Bit Sets

Set Contains:

Stock No.	Description	Applications	Length, inches	Tip, inches			
PHG63B	Air Hammer Ball Joint/Tie Rod Separator	Separating Ball Joints and Tie Rods	7-3/8	13/16 Opening			
PHG69B	Air Hammer Ball Joint/Tie Rod Separator	Separating Ball Joints and Tie Rods	7-3/8	1 Opening			
PHG93B	Ball Joint/Tie Rod Separator	Separating Ball Joints and Tie Rods	8-3/4	1-1/4 Opening			
PHG94B	Ball Joint/Tie Rod Separator	Separating Ball Joints and Tie Rods	7-3/8	5/8 Opening			
PHG64B	Air Hammer Bent End Chisel	Shears Ball Joint Rivets	10-1/2	5/8			
PHG76B	Bushing Cutter	Bushing Cutting	6-1/4	1/2			
PHG21B	Offset Bushing Splitter	Bushing Cutting (Extra Reach)	8-3/8	5/8			
PHG85B	Air Hammer Curved Flat Chisel	Rivet Cutting Work	5-3/4	5/8			
PHG57B	Air Hammer Double-Bladed Panel Cutter	Panel Cutting and Sheet Metal Cutting	6	3/4	•	•	
PHG73B	Air Hammer Drift Punch	Punching Out Pins and other Driving Applications	6-1/2	1/2		•	•
PHG77B	Straight Punch	Punching Out Pins and other Driving Applications (Extra Reach)	18	1/2			
PHG55B	Air Hammer Flat Chisel	Normal Chisel Cutting Applications	6-1/2	3/4	•	•	•
PHG58C	Air Hammer Flat Chisel	Normal Chisel Cutting Applications that need Extra Reach	10	3/4			•
PHG84B	Flat Chisel	Standard Chisel Cutting Applications (Extra Reach)	18	3/4			
PHG99B	Air Hammer Flat Chisel	Standard Chisel Cutting Applications (Extra Reach)	6-1/2	1-1/2			
PHG111B	Hinge Pin Driver	Removing and Installing Tube-Hinge Pins on Car and Truck Doors	7-3/8	0.237			
PHG112B	Hinge Pin Driver	Removing and Installing Tube-Hinge Pins on Car and Truck Doors	7-3/8	0.302			
PHG95B	Hole Punch	Punches 3/16" dia. Starting Hole in Sheet Metal to prepare use with CJ107 and CJ114 Body Dent Pullers	5-5/8	—			
PHG65B	Outside Muffler Cutter	For cutting the muffler flange	8-5/8	7/8			
PHG66B	Inside Muffler Cutter	Cutting the Exhaust Pipe Inside the Flange	8-3/4	3/16			
PHG87B	Muffler Cutter	Removing the Tail Pipe	8-3/4	7/8			
PH201	Needle Scaler	Projecting Rods Chip Away Rust and Scale. Use Only at Low-Pressure	7-13/16	—			
PHG74B	Riveter	3/16" Stem	5-13/16	1/2			
PHG75B	Pneumatic Bearing and Bushing Driver	Pneumatic Bearing and Bushing Driver	5-1/2	1/2			

- Do not operate without the guard. Do not use grinding discs or accessories above their rated RPM.
- Use air hammer accessories only for their intended purpose. Do not use chipped or damaged accessories.
- Do not use grinder accessories beyond their maximum rated RPM.
- Do not use wire brushes above their maximum rated RPM.
- † These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.
- Read Safety Precautions on pages W1-W4

**WARNING**



# AIR HAMMER ACCESSORIES

POWER TOOLS



Set Contains:  
 PHG1005BK  
 PHG1055BK  
 PHG1066BK

Stock No.	Description	Applications	Length, inches	Tip, inches			
PHG78B	Riveter	1/4" Stem	5-3/4	1/2			
PHG88B	Air Hammer Riveter	Forming Heads on 3/16" Compression Rivets	5-13/16	1/2			
PHG89B	Riveter	Forming Heads on 1/4" Compression Rivets	3-7/8	7/8			
PHG71B	Round Hammer	Hammering Applications that need Extra Reach	4-1/4	1			•
PHG68B	Round Hammer	Hammering Applications	7	1		•	•
PHG56B	Air Hammer Scraper	Scraping Applications	6-3/16	1-5/16			
PHG51B	Air Hammer Sheet Metal Ripper	Sheet Metal Ripping and Cutting	5-3/8	5/8	•		
PHG61B	Air Hammer Slitting Chisel	Cutting Tail Pipes and other Surfaces	6-7/8	1	•		
PH1038	3/8" Square Drive Air Hammer Socket Adaptor (Blue-Point®)	Attaches to Air Hammer to Provide Vibration While Turning Stubborn Fasteners, 3/4" Hex, 3/8" Square Drive	5	—			
PH1050	1/2" Square Drive Air Hammer Socket Adaptor (Blue-Point®)	Attaches to Air Hammer to Provide Vibration While Turning Stubborn Fasteners, 3/4" Hex, 1/2" Square Drive	5	—			
PHG70B	Air Hammer Spot Weld Breaker	Weld Removal	6-1/4	3/4	•		
PHG59B	Air Hammer Tapered Punch	Removal of Pins	6-1/2	3/16		•	•
PHG72B	Air Hammer U-Joint Needle Type Trunion Driver	Needle Type Trunions	3-7/8	7/8			
PHG83B	Valve Guide Remover	Removing and Installing Valve Guides	7.48	7.7 mm Pilot			
PHG86B	Valve Guide Remover	Removing and Installing Valve Guides	7.48	9.3 mm Pilot			
PHG91B	Valve Guide Remover	Removing and Installing Valve Guides	7.4	6.5 mm Pilot			
PHG96B	Valve Guide Remover	Removing and Installing Valve Guides	7.4	6.9 mm Pilot			
PHG97B	Valve Guide Remover	Removing and Installing Valve Guides	7.4	5.5 mm Pilot			
PHG151B	Panel Cutter	Edges and Trims Sheet Metal. Cutting End is Offset 25° Non-Turn Shank	6-7/8	5/8			
PHG161B	Slitting Chisel	Cuts Exhaust System Pipes, 1/8" Tip Thickness. Non-Turn Shank	8-3/4	1			
PHG155B	Air Hammer Cold Chisel	Cuts Bolts, Nuts, Tees and Angles; Splits and Bevels, Non-Turn Shank	7	21/32			
PHGCR1 <sup>†</sup>	Front Axle C-Clip Remover	Tire and Wheel: Removes C-Clips stuck in place by rust, cup shift, dirt and grime, for use on Ford®, GM® and Dodge® vehicles as well as any vehicle that uses a U-Joint with C-Clip retainer	—	—			
PH200D	Universal Quick-Change Chuck Retainer	Use for Fast, Easy Insertion/Removal of Air Hammer Bits	—	—			

## Air Hammer Bit Sets

PHG1540K<sup>‡</sup>

Stock No.	Description	
PHG1540-6 <sup>‡</sup>	6" Hammer Shaft	•
PHG1540-9 <sup>‡</sup>	9" Hammer Shaft	•
PHG1540-18 <sup>‡</sup>	18" Hammer Shaft	•
PHG1540-ALM <sup>‡</sup>	Aluminum Hammer Head	•
PHG1540-NYL <sup>‡</sup>	Nylon Hammer Head	•
PHG1540-STL <sup>‡</sup>	Steel Hammer Head	•
PHG1540-BAG <sup>‡</sup>	Hammer Set Canvas Pouch	•

Includes kit bag

### PHG1540K<sup>‡</sup> 6 pc Interchangeable Tip Air Hammer Bit Set

- Three (3) shafts in different lengths make accessing hard-to-reach places safer and easier
- Quick-change head design with (3) tips (steel, aluminum, nylon)
- Ability to choose the appropriate hammer head material to reduce damage to vulnerable areas
- Worn-out tips are easily replaceable



PHG1540K

## Roll Pin Punches

PHG1004RPBK  
Set Contains:

Stock No.	Description	Applications	Length, inches	Tip, inches	
PHG79B	Roll Pin Punch	For Removing and Installing Roll Pins	7-1/2	3/8	•
PHG80B	Roll Pin Punch	For Removing and Installing Roll Pins	7-1/2	1/4	•
PHG81B	Roll Pin Punch	For removing and installing roll pins	7-1/2	5/16	•
PHG821B	Roll Pin Punch	For Removing and Installing Roll Pins	7-1/2	1/2	•

Includes kit bag



PHG1004RPBK

## Extra-Long Drift Punches (Blue-Point®)

PHGL37KT  
Set Contains:

Stock No.	Description	Application	Length, inches	Size, inches (mm)	
PHGL78 <sup>‡</sup>	Extra-Long Drift Punch (Blue-Point®)	Loosens Hard-to-Reach Rusty Bolts and Fasteners	5	5/16 (8)	•
PHGL710 <sup>‡</sup>	Extra-Long Drift Punch (Blue-Point®)	Loosens Hard-to-Reach Rusty Bolts and Fasteners	5	3/8 (10)	•
PHGL712 <sup>‡</sup>	Extra-Long Drift Punch (Blue-Point®)	Loosens Hard-to-Reach Rusty Bolts and Fasteners	5	1/2 (12)	•

PHGL37-KB Kit includes storage pouch.



PHGL37KT

- Use air hammer accessories only for their intended purpose.
- Do not use chipped or damaged accessories.
- Do not use grinder accessories beyond their maximum rated RPM.
- Do not use wire brushes above their maximum rated RPM.
- Do not use power tool accessories above their maximum rated RPM
- ‡These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.
- Read Safety Precautions on pages W1-W4





YA4190A



YA4190CAPA



YA4190FAR



YA4190DIS

**YA4190A Mini Grease Gun**

- Fits all flush-type fittings
- Ideal for all FAR Series air ratchets
- Spring return plunger
- 3 oz capacity

**YA4190CAPA Grease Gun Head**

- Fits YA4190A mini grease gun

**YA4190FAR Grease Gun Assembly**

- Use with FAR series air ratchets

**YA4190DIS Grease Dispenser (Blue-Point®)**

- Grease dispenser attachment for YA4190A mini grease gun
- Contains 3 oz of Mobil® temp SHC-32 grease for Snap-on® FAR Series air ratchets



AT123-7-100



AT123-16-100



AT123-18-100



MG31MKIT

MG725MKIT

**AT123-7-100 7 pc Hammer and Anvil Tune-up Kit**

- Use on AT123A only
- Symptoms indicating repair is needed include air motor spins but anvil does not turn, air motor spins and anvil turns but no impacting occurs, or tools stalls while impacting

**AT123-16-100 19 pc Tune-up Kit**

- Use on AT123A and AT123AL
- Symptoms indicating repair is needed include trigger does not work properly or air leaks while tool is idle or running

**AT123-18-100 15 pc Tune-up Kit**

- Use on AT123A and AT123AL
- Symptoms indicating repair is needed include trigger does not work properly, air leaks while tool is idle or running, air motor has reduced RPM or air motor is excessively noisy

**MG31MKIT Muffler Kit  
MG725MKIT Muffler Kit**

- Reduces noise level to below 85 dBA
- Installs in minutes
- Maximum torque with muffler is 250 ft-lb (339 N•m)
- OSHA® compliant for 8 hours of continuous use



QC3ALC

QC3825

QC3844

QC5044

**Impact Wrench Accessories**

Stock No.	Description	Overall Length, inches (cm)	Weight, oz (grams)
QC3ALC	3 pc Quick-Change Adaptor Set	—	—
QC3825	3/8" Square to 1/4" Hex Adaptor	1-1/2 (3.8)	2.1 (60)
QC3844	3/8" Square to 7/16" Hex Adaptor	1-3/4 (4.5)	3.7 (104)
QC5044	1/2" Square to 7/16" Hex Adaptor	1-7/8 (4.75)	4.3 (124)

## Air Saw Blades

Stock No.	Application/Material Thickness	Teeth Per Inch (TPI)	Length, inches	Blade Thickness, inches (mm)	Quantity
ASB4-42	Over 0.20"	18	3-5/8	.025 (.63)	10 Each
ASB4-43	0.08-0.20"	24	3-5/8	.025 (.63)	10 Each
ASB4-44	0.00-0.08"	32	3-5/8	.025 (.63)	10 Each



ASB4-42

## Air Saw Blades

Stock No.	Description	Length, inches	Teeth Per Inch (TPI)	Blade Thickness, inches (mm)	Package Quantity
AT190-39C	Bi-Metal Blade Scroll (Blue-Point®)	3-3/4	18	.035 (.89)	5
AT190-40C	5 pk 3-3/4" Bi-Metal Scroll Air Saw Blades (Blue-Point®)	3-3/4	24	.035 (.89)	5
AT190-41C	Bi-Metal Blade Scroll (Blue-Point®)	3-3/4	32	.035 (.89)	5
AT190-42B	Bi-Metal Blade Multipurpose (Blue-Point®)	4	18	.035 (.89)	5
AT190-43B	5 pk 4" Bi-Metal Multipurpose Air Saw Blades (Blue-Point®)	4	24	.035 (.89)	5
AT190-44B	Bi-Metal Blade Multipurpose (Blue-Point®)	4	32	.035 (.89)	5



AT190-42B

## Metal Cutting Blades

Stock No.	Application/Material Thickness	Teeth Per Inch (TPI)	Blade Thickness, inches (mm)	Blade Length, inches (mm)	Quantity
CTRS614MC	Metal 1/8-3/8" Thick	14	.035 (.89)	6 (152)	5 Each
CTRS618MC	Metal 1/8-1/4" Thick	18	.035 (.89)	6 (152)	5 Each
CTRS624MC	Metal Less Than 1/8" Thick	24	.035 (.89)	6 (152)	5 Each
CTRS914MC	Metal 1/8-3/8" Thick	14	.035 (.89)	9 (229)	5 Each
CTRS918MC	Metal 1/8-1/4" Thick	18	.035 (.89)	9 (229)	5 Each
RSB424PM	Precision Metal Cutting	24	.035 (.89)	4 (102)	5 Each
RSB418PM	Precision Metal Cutting	18	.035 (.89)	4 (102)	5 Each
RSB6812JY	High-Strength Metal	8/12	.050 (1.27)	6 (152)	5 Each
RSB9812JY	High-Strength Metal	8/12	.050 (1.27)	9 (229)	5 Each



CTRS614MC



RSB418PM

## General Purpose Blades

Stock No.	Application/Material Thickness	Blade Length, inches (mm)	Material Thickness	Teeth Per Inch (TPI)	Blade Thickness, inches (mm)	Quantity
CTRS126GP	Metal/Plastic/Wood	12 (305)	3/8-2"	6	.050 (1.27)	5 Each
CTRS658GP	Metal/Plastic/Wood	6 (152)	3/8-2"	5-8 Variable	.050 (1.27)	5 Each
CTRS96GP	Metal/Plastic/Wood	9 (229)	3/8-2"	6	.050 (1.27)	5 Each
RSB911WP	General Purpose Wood/Plastic	9 (229)	5/32-1-5/32"	11	.04 (1)	5 Each
RSB97WB	Fast Cutting Wood 3/8" and Thicker	9 (229)	—	7	.040 (1.01)	5 Each



CTRS126GP

## Wood Cutting Blades

Stock No.	Application/Material Thickness	Teeth Per Inch (TPI)	Blade Thickness, inches (mm)	Blade Length, inches (mm)	Quantity
CTRS67WB	Fast Cutting Wood 3/8" and Thicker	7	.040 (1.01)	6 (152)	5 Each
RSB97WP	Fast Cutting Wood 3/8" and Thicker	7	.040 (1.01)	9 (229)	5 Each



CTRS67WB



- Use only impact sockets and accessories with air ratchets.
- Use air hammer accessories only for their intended purpose.
- Do not use chipped or damaged accessories.
- Read Safety Precautions on pages W1-W4

# BLOW GUNS



## Non-Vented Blow Guns

### AT4113 19" Straight Tube Air Blow Gun

- Built-in valve system improves trigger control
- Impact-resistant material for long-lasting service
- Galvanized blow tube for corrosion resistance
- Lifetime warranty (accessories not included)
- Used for blowing off, cleaning and drying surfaces
- Used in any sector of industry where compressed air is used

### AT4112B 300 mm Bent Tube Blow Gun

- Built-in valve system improves trigger control
- Impact-resistant material for long-lasting service
- Galvanized blow tube for corrosion resistance
- Lifetime warranty (accessories not included)

### AT4101 4" Blow Gun

- Built-in valve system improves trigger control
- Impact-resistant material for long-lasting service
- Galvanized blow tube for corrosion resistance
- Lifetime warranty (accessories not included)

### AT4135 Blow Gun with Air Adjustment

- Built-in valve system improves trigger control
- Impact-resistant material for long-lasting service
- Galvanized blow tube for corrosion resistance
- Lifetime warranty (accessories not included)
- Sound level 78 dB (8 bar)
- Regulate flow with adjustable volume control
- Complies with OSHA® safety standards
- Used for blowing off, cleaning and drying surfaces
- Used in any sector of industry where compressed air is used

### AT4124 Rubber Tip

- Prevents scratching of surface
- Used with AT4101, AT4113 and AT4135 air blow guns

### AT4164 Rubber Blow Gun Tip

- Rubber tip prevents scratching of delicate surfaces
- Push-to-connect collar holds tip securely onto the blow gun pipe
- Tip is easily removed from the blow gun pipe by simply pulling back on the collar
- 25 mm tip diameter is ideal for flushing hoses up to 7/8"
- Tip works with AT4101, AT4113 and AT4112 blow gun models
- Lifetime warranty

## Non-Vented Blow Guns (Blue-Point®)

### YA105020 20" Bent Nozzle Blow Gun (Blue-Point®)

- 20" bent nozzle
- Trigger provides variable airflow control
- Lightweight body with ergonomically designed grip provides comfort and control
- Venturi tip directs air sideways if the tip end is obstructed
- Reinforced 1/4"-18 NPT inlet

### YA105013 13" Bent Nozzle Blow Gun (Blue-Point®)

- Same as YA105020 except 13" bent nozzle

### YA1050T2 2" Venturi Air Booster (Blue-Point®)

- Venturi nozzle draws in ambient air for extra high-flow (increasing by 100%)
- Suitable for deflecting lightweight wood chips
- Diverts air when dead-ended, reducing the outlet pressure to less than 2 bar (29 PSI)

### YA1050B 4" Pistol Grip Blow Gun (Blue-Point®)

- Pistol-grip-style with full-sized front trigger
- Infinite variable flow
- 10-1/4" long

### YA4010 1/2" Quick Change Rubber Tip (Blue-Point®)

- Conical rubber tip for YA1050B Blow Gun

### YA1050T3 3 pc Rubber Tip Kit (Blue-Point®)

- Rubber tip kit for YA105020 Blow Gun

### YA1050T4 4" Chip/Fluid Shield (Blue-Point®)

- Chip/fluid shield for YA105020 Blow Gun



AT144800

## Non-Vented Blow Guns Accessories

### AT144800 5 pc Blow Gun Nozzle Kit

- Not for use above 30 PSI air supply pressure.

### Colors Available



\* O G  
 ADD SUFFIX TO STOCK NUMBER FOR SPECIAL COLORS.



AT4190



YA1055B



JT13B



JT17A



JT19A

## Vented Blow Guns

### AT4190<sup>+</sup> HI-FLO Venturi Tip Blow Gun

- Large diameter venturi nozzle draws in ambient air and increases output volume by 100%
- Nozzle delivers up to 21 CFM
- Ideal for heavy-duty chip and debris removal
- Excellent tool to quickly dry vehicles or motorcycles
- OSHA<sup>®</sup> compliant
- 1/4"-18 FNPT inlet
- Lifetime warranty

### YA1055B<sup>‡</sup> Blow Gun (Blue-Point<sup>®</sup>)

- Variable-flow trigger offers precise airflow control
- Six-outlet star tip delivers an even distribution of air
- 4" full-flow tube
- OSHA<sup>®</sup> compliant
- Air inlet: 1/4"-18 NPT(f)

### JT13B Blow Gun (Blue-Point<sup>®</sup>)

- Tapered, rubber tip for a leak-proof connection between the gun and the fluid line
- Vinyl-coated control lever
- Hanging hook for storage
- 4-1/2" long

### JT17A Blow Gun (Blue-Point<sup>®</sup>)

- Same as JT13B except with 3" extension in place of the rubber tip

### JT19A Venturi Tip Blow Gun (Blue-Point<sup>®</sup>)

- Directs air sideways if tip end becomes obstructed
- Venturi tip increases airflow
- Includes stabilizer valve for variable pressure
- 1" hanging hook and paddle type air control lever
- Air inlet: 1/4"-18 NPT(f)
- OSHA<sup>®</sup> compliant

#### Colors Available



Red Green  
\* R G

ADD SUFFIX TO STOCK NUMBER FOR SPECIAL COLORS.

## AIR WATER WASHERS



JETWASHER



JETWASHFAN



JETWASHNOZL

## Water Nozzles and Hoses

### JETWASHER Air Water Jet Washer

- Combines compressed air and water to create a powerful jet washer
- Provides safe and effective cleaning
- Separate air and water controls
- Multifunction—rinse, clean or dry with air and water
- Wide nozzle design prevents splash-back
- Lightweight and compact

- Durable nylon components will not scratch surfaces
- Includes a 3/4" threaded garden hose connection and quick-connect adaptor
- Optional stepped nozzle can be used to flush coolant systems and heater cores

### JETWASHFAN Jet Washer Fan Nozzle

### JETWASHNOZL Jet Washer Flushing Nozzle (Optional)

• Do not use vented blow guns above 135 PSI air supply pressure.

• Do not use non-vented blow guns above 30 PSI.

• Do not direct blow gun at yourself or others.

• Wear protective gloves.

‡ These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.

• Read Safety Precautions on pages W1-W4

**WARNING**



# AIR HOSES AND SWIVELS



IM2005A

## Air Hoses, Rubber

- Ideal for industrial applications
- Male threads at both ends

Stock No.	Hose I.D., inches	Hose Length, feet	Thread Size	Maximum Pressure, PSI
IM2001A <sup>‡</sup>	1/4	5 whip	1/4"-18 NPT	300
IM2002A <sup>‡</sup>	3/8	5 whip	1/4"-18 NPT	300
IM2004A <sup>‡</sup>	3/8	2 whip	1/4"-18 NPT	300
IM2005A <sup>‡</sup>	3/8	25	1/4"-18 NPT	325
IM2008A <sup>‡</sup>	3/8	50	1/4"-18 NPT	325
IM2009A <sup>‡</sup>	1/2	50	1/2"-14 NPT	325



AIRHOSE35

## Air Hoses, Reinforced Polyurethane

Stock No.	Hose I.D., inches	Hose Length, feet	Thread Size	Temperature Range	Working Pressure, PSI
AIRHOSE35 <sup>‡</sup>	3/8	35	1/4" NPT	-40-165 °F (-40-73.9 °C)	200 @ 70 °F (21 °C)
AIRHOSE50 <sup>‡</sup>	3/8	50	1/4" NPT	-40-165 °F (-40-73.9 °C)	200 @ 70 °F (21 °C)
AIRHOSE100 <sup>‡</sup>	3/8	100	1/4" NPT	-40-165 °F (-40-73.9 °C)	200 @ 70 °F (21 °C)
AIRHOSE1250	1/2	50	1"-11-1/2" NPT	-40-165 °F (-40-73.9 °C)	200 @ 70 °F (21 °C)

- Extremely lightweight for easy maneuverability
- Reinforced construction eliminates layer separation resulting from expansion and contraction during pulsating operations
- Resists abrasions better than PVC and rubber hoses
- Easy to wrap and store even in subzero weather
- UV stabilized for longer outdoor life
- Strain relief features a tight bending radius to virtually eliminate hose kinking
- Reusable fittings and strain reliefs for longer life

**AIRHOSEKIT Replacement End for 3/8" Air Hose**

**AIRHOSESPLCR Splicer Kit for 3/8" Air Hose**



YA502M

## Air Swivel Connectors

Stock No.	Thread Size	Maximum Pressure, PSI	Airflow
ASC14	1/4" NPT	150	Up to 35 SCFM (991 LPM)
ASC14U	1/4" NPT	150	Up to 35 SCFM (991 LPM)
YA502M	1/4" NPT	150	Up to 4.6 CFM (33 SCFM)
YA503M	3/8"-18 NPT	150	Up to 6.3 CFM (45 SCFM) [178 LPM]

- Swivels turn 360° at two points for complete tool maneuverability
- Air hoses hang straight to the floor





## Air Line Quick Couplers

Body Size, inches	Style	Thread Size	Quick Coupler Male	Quick Coupler Female	Adapter Male	Adapter Female
1/4	Lincoln®	1/4"-18 NPT	—	AHC26D‡	AHC26MD‡	AHC26FD‡
1/4	Tru-Flate®	1/4"-18 NPT	—	AHC24D	AHC24MD‡	AHC24FD‡
3/8	True-Flate®	1/4"-18 NPT	—	AHC25D‡	AHC25MD‡	AHC25FD‡
1/4	ARO®	1/4"-18 NPT	AHC23PMD‡	AHC23D‡	AHC23MD‡	AHC23FD‡
1/4	Industrial Interchange	1/4"-18 NPT	AHC21PMD‡*	AHC21D‡	AHC21MD‡	AHC21FD‡
3/8	Industrial Interchange	1/4"-18 NPT	—	AHC22E‡*	AHC22MD‡	AHC22FD‡
3/8	Industrial Interchange	3/8"- 18 NPT	—	AHC28D‡*	AHC28MD‡	AHC28FD‡
1/2	Industrial Interchange	3/8"- 18 NPT	—	—	AHC31‡	—
1/2	Industrial Interchange	1/2"-14 NPT	—	AHC27D‡**	AHC27MD‡	AHC27FD‡
1/4	Rigid Mounting	1/4"-18 NPT	—	AHC21PD‡*	—	—
1/4	Hi-Flow	1/4"-18 NPT	—	AHCC98C‡	AHCCP97C‡	—
1/4	Hi-Flow HVLP	1/4"-18 NPT	AHCC91C‡	AHCC90C‡	—	AHCCP90C

\*Conforms to Mil Spec. MIL-C-4109E.

\*\*Rigid Mounting: brass "push-to-connect" type; use in place of AHC21 and AHC22 on rigid piping systems only.

All adaptors are plated steel to improve durability

## Air Valves and Manifolds

### AHC300 Multiline Air Manifold (Blue-Point®)

- Capacity of three air lines running at the same time
- Allows three workstations to use the same air supply
- Evenly distributes air through three different lines

### IM10D Air Valve (Blue-Point®)

- Volume of airflow can be regulated with 1/4 turn of the control knob
- Male/female thread sizes



- Do not use wire brushes above their maximum rated RPM.
- ‡These products can expose you to chemicals which are known to the state of California to cause cancer and reproductive harm. See pages P1-P2 for details.
- Read Safety Precautions on pages W1-W4



ATHUBSCRUBKIT



ATHUBSCRUBSMPADS



ATHUBSCRUB



CL6



IM1PTMP6



IM10ZMP12



IM1PT



CTTOTE



BPTOTE

## Abrasive Discs (Blue-Point®)

### ATHUBSCRUBKIT<sup>‡</sup> Hub Scrub Kit (Blue-Point®)

- Quickly and effectively removes rust and debris from hub surfaces
- 1/2" drive allows for use with an impact gun—simply attach like any standard impact socket
- High-quality tool sculpted from aircraft-grade aluminum
- The majority of hub cleaning tool products on the market require use with an air or cordless drill
- Enhances shop productivity by not having to change from an impact to a drill and back to an impact
- Improves wheel assembly with better torquing against a clean surface and improving balance by removing rust, dirt and other foreign materials from the lug threads, hub surface
- Includes ATHUBSCRUB, ATHUBSCRUBLG, ATHUBSCRBPADS (1 pk/3 pc), ATHUBSCRUBSMPADS (1 pk/3 pc), ATHUBSCRUBLGPADS (1 pk/3 pc) in a storage tray

### ATHUBSCRUBLG<sup>‡</sup> Large Truck Hub Scrubber (Blue-Point®)

#### ATHUBSCRUBLGPADS<sup>‡</sup> Replacement Truck Pads, 4 pk (Blue-Point®)

- Fits 22 mm stud size on large trucks

#### ATHUBSCRUBSMPADS<sup>‡</sup> Replacement Compact Vehicle Pads, 4 pk (Blue-Point®)

- Fits 15 mm stud size on smaller vehicles

#### ATHUBSCRUB Hub Scrubber with Pad (Blue-Point®)

- Invaluable tool for all wheel service applications
- Quickly removes rust and corrosion from studs, rotors, hubs and wheels
- Used with any 1/2" drive impact wrench
- Long-lasting, replaceable abrasive pads

#### ATHUBSCRBPADS Abrasive Pad, 4 pk (Blue-Point®)

- Four pack of replaceable abrasive pads

## Lubrication Accessories

### CL6 Cutting Oil

- Superior anti-weld and lubricating properties reduce heat buildup in drill bits, grinding burrs and other metal cutting tools
- 1 pt bottle

### IM1PTMP6 16 oz Air Motor Oil (6 pk)

- Cleans all piston and rotary air motors, and helps prevent rust formation
- (6 pk) of IM1PT 16 oz bottles

### IM10ZMP12 1 oz Air Motor Oil (12 pk)

- (12 pk) of 1 oz bottles

### IM1PT 16 oz Air Motor Oil

- Improves performance and extends the life of power tools with regular use of Snap-on® motor oil
- Specially formulated to lubricate, clean and protect expensive components
- Used daily on all piston and rotary air motors
- 16 oz bottle

## Tote Bags

### CTTOTE Power Tool Tote Bag

- Wide opening for easy access to tools—extra padding for protection
- Durable 600 Denier exterior for strength
- Interior pockets and compartments for tool organization
- Padded handles for comfortable transport
- Reinforced bottom for strength
- Six external pockets for extra storage
- Approximate inside dimensions, open: 18" L x 8" W x 11-1/2" D (457 x 203 x 292 mm)

### BPTOTE Tote Bag (Blue-Point®)

- Heavy-duty 600 x 300 D-polyester
- Water-resistant, rugged and versatile
- Wide top opening for easy access
- Multiple interior and external pockets for organization
- Overall dimensions: 16-1/2" L x 10-1/2" W x 12-1/4" H