# NAMANI®



### Content

Α	b	O	u'	t	U	S

### Product Portfolio

V100 Ultra	0.4
U5	04
X100 Ultra Pro	06
N200	08
N300	10
N70	12 14
T70	16
N60	18
N50	20
N30	22
X10	24
N20	26
N10	28
N15	30
N7	32
N5	34
N1	36
NMini	38
N9	40
N6L	42
T4	44
T28Pro	46
T28	48
G6	50
G2	52
G3	54
N2D	56

NAM**ANI**®

### **About us**

Namani Smart Solution Sdn Bhd was established with a core principle of delivering affordable, innovative, and high-quality smart locks accompanied by robust after-sales service. Our aim is to make keyless entry accessible to everyone in Malaysia by introducing smart locks to the masses.

Our in-house brand, Namani, offers a broad range of smart lock options across multiple price points, catering to diverse customer needs. Our goal is to provide advanced and cost-effective smart access solutions to Malaysia, coupled with exceptional customer service.

At Namani Smart Solution, we prioritize customer satisfaction and recognize the significance of providing excellent service. Our team members are well-trained, knowledgeable, and experienced in delivering top-notch customer service.

We not only sell smart locks but also educate our customers on how to operate them seamlessly in their daily routines. From pin code unlocking to wifi remote unlocking and even the latest 3D face recognition technology, we remain at the forefront of access technology.

# **V100** Ultra

#### 3D FACIAL RECOGNITION SERIES

4.5 HD Screen. Seamless Touch Screen







intercom



connection




C-class lock cylinder



Facial recognition



Multiple alarm



Material	Aluminum alloy
Color	Black / Copper
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Face Recognition Fingerprint PIN code Card Master PIN code USmart Go App Mechanical key
Capacity	
Face Recognition	100
Fingerprint	100
PIN code	5
Card	20
Master PIN code	5
Electrical Power	
Working power supply	4200MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode Manual mode

Dimensions	
Front	690mm(H) x 80mm(W) x 65mm(T)
Back	690mm(H) x 80mm(W) x 65mm(T)
Installation Require	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environe	enent
Temperature	-20°C-+60°C
Humidity	20%RH-80%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
-	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside
	situations via APP
	Two-way talk via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicator
	Doorbell indicator

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



# **U5**

#### PALM VEIN RECOGNITION SERIES

4.5 HD Screen. 3D Facial Recognition











Remote visual intercom



WI-FI connection



C-class lock cylinder



Facial recognition



Plam vein recognition





Material	Aluminum alloy
Color	Black
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Palm Vein Recognition Face Recognition Fingerprint
	PIN code Card Master PIN code Xhome App Mechanical key
Capacity	
Palm Vein / Face Recogniti	on 20
Fingerprint	20
PIN code	20
Card	20
Master PIN code	1
Electrical Power	
Norking power supply 50	000MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
/oice guide	Human voice guide
Operation Modes	Auto mode
	Manual mode

Front	420mm(H) x 75mm(W) x 65mm(T)
Back	420mm(H) x 75mm(W) x 65mm(T)
Installation Requir	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-20°C-+60°C
————————— Humidity	20%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside situations via APP
	Two-way talk via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicator
	Doorbell indicator

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



# X100 Ultra Pro

PALM VEIN RECOGNITION SERIES

4.5 HD Screen. 3D Facial Recognition









Photo capture



WI-FI connection



Built-in door bell



Facial recognition



Remote visual intercom





Material	Aluminum alloy
Color	Black
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Palm Vein Recognition Face Recognition Fingerprint PIN code
	Card Master PIN code Xhome App Mechanical key
Capacity	
Palm Vein / Face Recog	nition 20
Fingerprint	20
PIN code	20
Card	20
Master PIN code	1
Electrical Power	
Working power supply	5000MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
/oice guide	Human voice guide
Operation Modes	Auto mode Manual mode

Dimensions	
Front	410mm(H) x 70mm(W) x 60mm(T)
Back	400mm(H) x 70mm(W) x 65mm(T)
Installation Requir	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-20°C-+60°C
Humidity	20%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside
	situations via APP
	Two-way talk via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicator
	Doorbell indicator

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



#### 3D FACIAL RECOGNITION SERIES

4.5 HD Screen. Seamless Touch Screen

















recognition





Material	Aluminum alloy
Color	Black
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Face Recognition Fingerprint PIN code Card Master PIN code Xhome App Mechanical key
 Capacity	
Face Recognition	20
	20
PIN code	20
Card	20
Master PIN code	1
Electrical Power	
Working power supply	5000MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode Manual mode

Dimensions	
Front	380mm(H) x 80mm(W) x 60mm(T)
Back	400mm(H) x 70mm(W) x 57mm(T)
Installation Require	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	enent
Temperature	-20°C-+60°C
Humidity	20%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside situations via APP
	Two-way talk via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicator
	Doorbell indicator

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



#### 3D FACIAL RECOGNITION SERIES

4.5 HD Screen. Seamless Touch Screen



Black















recognition

Multiple alarm





Material	Aluminum alloy
Color	Chrome / Matte
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Face Recognition Fingerprint PIN code Card Master PIN code Xhome App Mechanical key
Capacity	- Weenameat key
· ·	20
Face Recognition	
Fingerprint	20
PIN code	20
Card	20
Master PIN code	1
Electrical Power	
Working power supply	5000MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode
	Manual mode

Front	420mm(H) x 70mm(W) x 55mm(T
Back	420mm(H) x 70mm(W) x 55mm(T
Installation Requir	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-20°C-+60°C
Humidity	20%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside situations via APP
	Two-way talk via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicato
	Doorbell indicator





3D FACIAL RECOGNITION SERIES

Handsfree. App Unlock









Lithium rechargeable battery



WI-FI connection




Built-in door bell



Facial recognition



Indoor anti lock knob





Material	Aluminum alloy
Color	Black / Grey / Copper
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Face Recognition Fingerprint PIN code Card Master PIN code USmart Go App Mechanical key
Face Recognition	20
Fingerprint	20
PIN code	20
Card	20
Master PIN code	1
Electrical Power	
Working power supply	4200MA 7.4 V Lithium battery
Battery life	5 months
Emergency charging	5V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode Manual mode

Dimensions	
Front	420mm(H) x 75mm(W) x 50mm(T)
Back	420mm(H) x 75mm(W) x 50mm(T)
Installation Require	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	enent
Temperature	-20°C-+60°C
Humidity	20%RH-80%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Check access records
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicator
	Doorbell indicator



<sup>\*5</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license

**T70** 

**GLASS DOOR SERIES** 

3D Facial Recognition. App Unlock







Copper



WI-FI connection



Various ways to unlock



Access record query



Facial recognition



PIN code distributing



Material	Aluminum alloy	Dimensions	
Color	Gold	Front Back	190mm(H) x 78mm(W) x 15mm(T) 190mm(H) x 78mm(W) x 50mm(T)
Fingerprint sensor	Semiconductor	Installation Require	ements
Connectivity	WiFi	Door Thickness	38-120mm
Access Solution	Face Recognition Remote	Door opening direction	Left-in/Left-out Right-in/Right-out
	Fingerprint	Door type	Tempered Glass
	PIN code	Operating Envirome	enent
	Card Master PIN code	Temperature	-20°C-+60°C
	Tuya App	Humidity	20%RH-93%RH
	Mechanical key	Key Features	
Consoltre		Lock	System Lock
Capacity		Safety	Hidden PIN code
Face Recognition	20		
Fingerprint	gerprint 20		Anti-prying alarm
PIN code	ode 20		Outside forced lock alarm
Card	20	Doorbell & Video	Visitor's arrival notification
Electrical Power			Check access records
		Emergency escape	Indoor fast
Working power supply	4000MA 7.4 V Lithium battery		opening mortise
Battery life	3 months	Indicator	Low battery indicator
Emergency charging	5V powerbank		Doorbell indicator
Voice guide	Human voice guide		
Operation Modes	Auto mode		
	Manual mode		



3D FACIAL RECOGNITION SERIES 144° Viewing Angle. Built-In Camera









Lithium rechargeable battery



WI-FI connection



Photo capture



Facial recognition



PIN code distributing





Material	Al
	Aluminum alloy
Color	Phantom Black
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Face Recognition
	Fingerprint
	PIN code

Card

Master PIN code Tuya App Mechanical key

Manual mode

Capacity	
Face Recognition	20
Fingerprint	20
PIN code	20
Card	20
One-time PIN code	5

Electrical Power	
Working power supply	5000MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

Dimensions	
Front	430mm(H) x 70mm(W) x 50mm(
Back	400mm(H) x 70mm(W) x 76mm(
Installation Require	ements
Door Thickness	38-120mr
Door opening	Left-in/Left-ou
direction	Right-in/Right-ou
Door type	Wooden/Copper/Securit
Operating Environ	enent
Temperature	-20°C-+60°C
Humidity	20%RH-93%RI
Key Features	
Lock	Indoor deadloo
Safety	Hidden PIN cod
	Dual verfication
Alarm	Anti-prying aları
	Outside forced lock alar
Doorbell & Video	Visitor's arrival notificatio
	Surveillance of outsid
	situations via AP
	Surveillance of outside situation
	via indoor scree
	Check access record
	Photo Captur
	Share temporary PIN cod
Emergency escape	Indoor fas
	opening mortis
Indicator	Low battery indicate
	Doorbell indicate

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



3D FACIAL RECOGNITION SERIES

4.5 HD Screen. Handsfree. APP Unlock









Digital door viewer



WI-FI connection



Indoor anti lock knob



Dual verification



PIN code distributing





423mm

Material	Aluminum alloy	Dimensions	
Color	Copper / Black	Front Back	423mm(H) x 61mm(W) x 56mm(T 420mm(H) x 75mm(W) x 75mm(T
Handle	Push-pull handle	Installation Require	
Fingerprint sensor	Semiconductor	Door Thickness	38-120mm
Connectivity	WiFi	Door opening	Left-in/Left-out
Access Solution	Face Recognition	direction	Right-in/Right-out
	Fingerprint	Door type	Wooden/Copper/Security
	PIN code	Operating Envirome	enent
	Card Master PIN code	Temperature	-20°C-+60°C
	Usmart Go App	Humidity	20%RH-93%RH
	Mechanical key	Key Features	
	<u>-</u>	Lock	Indoor deadlock
Capacity		Safety	Hidden PIN code
Face Recognition	20		Dual verfication
Fingerprint	20	Alarm	Anti-prying alarm
PIN code	20		Outside forced lock alarm
		Doorbell & Video	Visitor's arrival notification
Card ————————————————————————————————————	20		Surveillance of outside
One-time PIN code	5		situations via APP
Electrical Power			Surveillance of outside situations via indoor screen
Working power supply	4200MA 7.4 V Lithium battery		Check access records
Battery life	3 months		Photo Capture
Emergency charging	5V powerbank		
Voice guide	Human voice guide	Emergency escape	Indoor fast
-			opening mortise
Operation Modes	Auto mode	Indicator	Low battery indicator
	Manual mode		Doorbell indicator

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license



VIDEO CAMERA SERIES

Dual Verification. Indoor Anti Lock Knob











Photo capture



WI-FI connection









User management





-	
Material	Zinc alloy
Color	Black
Handle	Push-pull handle
Fingerprint sensor	Semiconductor
Connectivity	WiFi
Access Solution	Fingerprint PIN code Card
	Master PIN code
	Tuya App
	Mechanical key
Capacity	
Fingerprint	20
PIN code	20
Card	20
One-time PIN code	10
Electrical Power	
Working power supply	4200MA 7.4 V Lithium battery
Battery life	5 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode
	Manual mode

Dimensions	
Front	400mm(H) x 75mm(W) x 50mm(T)
Back	410mm(H) x 70mm(W) x 63mm(T)
Installation Require	ements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	enent
Temperature	-20°C-+60°C
Humidity	20%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
	Dual verfication
Alarm	Anti-prying alarm
	Outside forced lock alarm
Doorbell & Video	Visitor's arrival notification
	Surveillance of outside situations via APP
	Surveillance of outside situations via indoor screen
	Check access records
	Photo Capture
	Share temporary PIN code
Emergency escape	Indoor fast
·-	opening mortise
Indicator	Low battery indicator
	Doorbell indicator



**X10** 

**ULTRA SLIM SERIES** 

Slimmest. Refined









Semicondutor fingerprint



Voice prompts



Built-in door bell



Virtual password



Lithium rechargeable battery





Material	Titanium alloy	Dimensio
Color	Black	Front
Handle	Push-pull handle	Back Installat
Fingerprint sensor		Door Thi
	Semiconductor	
Connectivity	WiFi	Door op directio
Access Solution	Fingerprint	Door typ
	PIN code	Operatin
	Card	
	Master PIN code	Tempera
	Xhome App	Humidity
	Mechanical key	Key Feat
Capacity		Lock
		Safety
Fingerprint	20	
PIN code	20	Alarm
Card	20	 Doorbell
Master PIN code	1	200.200
Electrical Power		
Working power supply	4200MA 7.4 V Lithium battery	Emergen
Battery life	3 months	Lineigen
Emergency charging	2V powerbank	Indicato
Voice guide	Human voice guide	
Operation Modes	Auto mode	
	Manual mode	

Front	390mm(H) x 78mm(W) x 30mm(T	
Back	390mm(H) x 78mm(W) x 40mm(T)	
Installation Requir	rements	
Door Thickness	38-120mm	
Door opening	Left-in/Left-out	
direction	Right-in/Right-out	
Door type	Wooden/Copper/Security	
Operating Envirom	enent	
Temperature	-20°C-+60°C	
Humidity	20%RH-93%RH	
Key Features		
Lock	Indoor deadlock	
Safety	Hidden PIN code	
	Dual verfication	
Alarm	Anti-prying alarm	
	Outside forced lock alarm	
Doorbell	Visitor's arrival notification	
	Check access records	
	Share temporary PIN code	
Emergency escape	Indoor fast	
	opening mortise	
Indicator	Low battery indicator	
	Doorbell indicator	



<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license

LEVER HANDLE SERIES

Door Bell. Airbnb Series







Semicondutor fingerprint



Indoor anti lock knob



Access record query



Virtual password



PIN code distributing





Material	Zinc alloy
Color	Black / Copper
Handle	Lever handle
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint
	PIN code
	Card
	Master PIN code
	TTlock App
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	8 pcs AA alkaline batteries
Battery life	10 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Manual mode

Front	378mm(H) x 78mm(W) x 75mm(T
Back	378mm(H) x 78mm(W) x 75mm(T
Installation Require	ements
Door Thickness	40-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirome	enent
Temperature	-10°C-+55°C
——————————————————————————————————————	15%RH-93%RH
Key Features	
Lock	Indoor deadlock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarn
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	Indoor fast
	opening mortis
Indicator	Low battery indicato
	System status indicato
	Lock status indicato



LEVER HANDLE SERIES

Double Lock. Airbnb Series







Semicondutor fingerprint



Indoor anti lock knob



Access record query



Virtual password



PIN code distributing



Material	Zinc alloy	Dimensions	
Color	Black / Copper	Front	370mm(H) x 75mm(W) x 70mm(T)
Handle	Lever handle	Back	370mm(H) x 75mm(W) x 70mm(T)
	Ecver manate	Installation Require	
Fingerprint sensor	Semiconductor	Door Thickness	38-120mm
Connectivity	Wifi / Bluetooth	Door opening	Left-in/Left-out
Access Solution	Fingerprint	direction	Right-in/Right-out
	PIN code	Door type	Wooden/Copper/Security
	Card	Operating Envirome	enent
	Master PIN code	Temperature	-10°C-+55°C
	TTlock App	Humidity	15%RH-93%RH
	Mechanical key	Key Features	
		Lock	Indoor deadlock
Capacity		Safety	Hidden PIN code
Fingerprint	200	Alarm	Anti-prying alarm
PIN code	150		Outside forced lock alarm
Card	200	Networking	Generate PIN code
E-key	Unlimited		Check access records
Electrical Power			Share temporary PIN code
Working power supply	8 pcs AA alkaline batteries	Emergency escape	Indoor fast
	— pos / w a a a a a a a a a a a a a a a a a a		opening mortise
Battery life	10 months	Indicator	Low battery indicator
Emergency charging	2V powerbank		
Voice guide	Human voice guide		
Operation Modes	Manual mode		



















PIN code distributing





Black / Copper Lever handle Semiconductor Wifi / Bluetooth
Semiconductor
Wifi / Bluetooth
,
Fingerprint PIN code Card
Master PIN code
TTlock App Mechanical key
200
150
200
Unlimited
A alkaline batteries
10 months
2V powerbank
2V powerbank Human voice guide

Front	360mm(H) x 75mm(W) x 80mm(T) 360mm(H) x 75mm(W) x 80mm(T)	
Back		
Installation Requir	ements	
Door Thickness	38-120mm	
Door opening	Left-in/Left-out	
direction	Right-in/Right-out	
Door type	Wooden/Copper/Security	
Operating Envirom	enent	
Temperature	-10°C-+55°C	
Humidity	15%RH-93%RH	
Key Features		
Lock	Indoor deadlock	
Safety	Hidden PIN code	
Alarm	Anti-prying alarm	
	Outside forced lock alarm	
Networking	Generate PIN code	
	Check access records	
	Share temporary PIN code	
Emergency escape	Indoor fast	
	opening mortise	
Indicator	Low battery indicato	



















Material	Aluminum alloy
Color	Black / Grey
Handle	Lever handle
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint PIN code
	Card Master PIN code
	TTlock App
	Mechanical key
 Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	10 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Manual mode

Dimensions		
Front	300mm(H) x 68mm(W) x 72mm(T)	
Back	300mm(H) x 68mm(W) x 72mm(T)	
Installation Requi	rements	
Door Thickness	38-120mm	
Door opening	Left-in/Left-out	
direction	Right-in/Right-out	
Door type	Wooden/Copper/Security	
Operating Environ	ienent	
Temperature	-10°C-+55°C	
Humidity	15%RH-93%RH	
Key Features		
Lock	System lock	
Safety	Hidden PIN code	
Alarm	Anti-prying alarm	
	Outside forced lock alarm	
Networking	Generate PIN code	
	Check access records	
	Share temporary PIN code	
Emergency escape	e Indoor fast	
	opening mortise	
Indicator	Low battery indicator	
	System status indicator	
	Lock status indicator	
	Outside forced lock indicator	

















PIN code distributing





Material	Aluminum alloy
Color	Black / Brushed Black / Copper
Handle	Lever handle
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint PIN code Card
	Master PIN code
	TTlock App
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	10 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Manual mode

Dimensions	
Front	255mm(H) x 65mm(W) x 69mm(T)
Back	255mm(H) x 65mm(W) x 69mm(T)
Installation Requir	rements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	ienent
Temperature	-10°C-+55°C
Humidity	15%RH-93%RH
Key Features	
Lock	System lock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarm
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	e Indoor fast
	opening mortise
Indicator	Low battery indicator
	System status indicator
	Lock status indicator
	Outside forced lock indicator













Access record query



Virtual password




PIN code distributing





Material	Aluminum alloy
Color	Black
Handle	Lever handle
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint PIN code Card
	Master PIN code TTlock App
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	10 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Manual mode

Dimensions	
Front	300mm(H) x 73mm(W) x 73mm(T
Back	300mm(H) x 73mm(W) x 73mm(T
Installation Requir	rements
Door Thickness	38-120mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-10°C-+55°C
Humidity	0%RH-95%RH
Key Features	
Lock	System lock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarn
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicato
	System status indicato
	Lock status indicato
	Outside forced lock indicate





### **NMINI**

RIM SERIES
Affordable. Airbnb Series















User management







Material	Aluminum alloy
Color	Black
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint
	PIN code
	Card
	Master PIN code
	TTlock App
	Remote Controller
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	8 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

nm(H) x 68mm(W) x 55.5mm(T s  35-55mm  Left-in/Left-out Right-in/Right-out Wooden/Copper/Security  -10°C-+65°C  20%RH-95%RH
35-55mm  Left-in/Left-out Right-in/Right-out  Wooden/Copper/Security  -10°C-+65°C
Left-in/Left-out Right-in/Right-out Wooden/Copper/Security -10°C-+65°C
Right-in/Right-out Wooden/Copper/Security -10°C-+65°C
Wooden/Copper/Security -10°C-+65°C
-10°C-+65°C
20%RH-95%RH
System lock
Indoor deadlock
Hidden PIN code
Anti-prying alarm
Outside forced lock alarn
Generate PIN code
Check access records
Share temporary PIN code
Indoor fast
opening mortise
Low battery indicato
System status indicato
Lock status indicato



## **N9**

GRIIL GATE SERIES
Outdoor. Waterproof









Bluetooth



Various ways to unlock



Access record query



Waterproof



PIN code distributing



Material	Aluminum alloy	Dimensions
Color	Black	Front
Fingerprint sensor	Semiconductor	Back
Connectivity	Bluetooth	Installation Re
Connectivity		Door Thicknes
Access Solution	Fingerprint	Door openin
	PIN code	direction
	Card	Door type
	Master PIN code	Operating Env
	TTlock App	Temperature
	Mechanical key	Humidity
		Key Features
Capacity		Lock
Fingerprint	200	Safety
PIN code	150	Alarm
Card	200	Networking
E-key	Unlimited	
Electrical Power		
Working power supply	4 pcs AA alkaline batteries	Emergency es
Battery life	8 months	Indicator
Emergency charging	2V powerbank	
Voice guide	Human voice guide	
Operation Modes	Auto mode	

Front	170mm(H) x 59mm(W) x 35mm(T)
Back	100mm(H) x 176mm(W) x 43mm(T)
Installation Requi	rements
Door Thickness	35-65mm
Door opening direction	Left-in/Left-out Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	nenent
Temperature	-20°C-+50°C
Humidity	20%RH-95%RH
Key Features	
Lock	System lock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarm
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	e Indoor fast
	opening mortise
Indicator	Low battery indicator
	System status indicator
	Lock status indicator
	Outside forced lock indicator



<sup>\*8</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license

### **N6**

**GRILL GATE SERIES** 

Automatic Locking. Dual Fingerprint



















Material	Zinc alloy
Color	Black
Fingerprint sensor	Semiconductor
Connectivity	Wifi / Bluetooth
Access Solution	Fingerprint
	PIN code
	Card
	Master PIN code
	TTlock App
	Remote Controller
	Mechanical key
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	8 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

Dimensions	
Front	162mm(H) x 56mm(W) x 27mm(T)
Back	203mm(H) x 60mm(W) x 47mm(T)
Installation Requir	rements
Door Thickness	35-55mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	nenent
Temperature	-10°C-+65°C
Humidity	20%RH-95%RH
Key Features	
Lock	System lock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarm
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	e Indoor fast
	opening mortise
Indicator	Low battery indicator
	System status indicator
	Lock status indicator
	Outside forced lock indicator



<sup>\*8</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license











Various ways to unlock



Access record query



Bluetooth



PIN code distributing









Aluminum alloy
Black
Semiconductor
Bluetooth
Fingerprint
PIN code
Card
Master PIN code
TTlock App
Mechanical key
200
150
200
Unlimited
4 pcs AA alkaline batteries
10 months
2V powerbank
Human voice guide
Auto mode

Front	224mm(H) x 70mm(W) x 75mm(T)
Back	224mm(H) x 70mm(W) x 75mm(T)
Installation Requir	ements
Door Thickness	35-65mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-20°C-+50°C
————————— Humidity	20%RH-95%RH
Key Features	
Lock	System lock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarm
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency escape	Indoor fast
	opening mortise
Indicator	Low battery indicato



## T28 Pro

#### **ROOM SERIES**

Affordable. Easy to install









automatic



record query



Bluetooth





Fingerprint sensor  Connectivity  Wifi / Bluetooth  Connectivity  Door Thickness  Door opening direction  PIN code  Card  Master PIN code  TTlock App  Mechanical key  Capacity  Capacity  Card  PIN code  Card  Mechanical key  Capacity  Card  PIN code  Card  PIN code  Toolog Thickness  Door opening direction  Door type  Woo  Operating Enviromenent  Temperature  Humidity  Key Features  Lock  PIN code  PIN code  150  Our  Card  200  Networking				
Fingerprint sensor  Connectivity  Wifi / Bluetooth  Access Solution  Fingerprint PIN code Card Master PIN code TTlock App Mechanical key  Capacity  Fingerprint PIN code Toda  Alarm  Card PIN code Card Card PIN code Card PIN code Card Card Card Card PIN code Card Card Card Card Card Card Card Card	Material	Aluminum alloy	Dimensions	
Fingerprint sensor  Connectivity  Wifi / Bluetooth  Access Solution  Fingerprint PIN code Card Master PIN code TTlock App Mechanical key  Capacity  Fingerprint PIN code TTlock App Mechanical key  Capacity  Fingerprint  Card PIN code Card PIN code Card PIN code Card Card Card PIN code Card PIN code Card PIN code Card Card Card Card Card Card Card Card	Color	Black		65mm(H) x 14
Installation Requirements   Door Thickness	Fingerprint sensor	Semiconductor		65mm(H) x 14
Access Solution  Fingerprint PIN code Card Master PIN code TTlock App Mechanical key  Capacity  Fingerprint PIN code Toor type Woo Operating Enviromenent Temperature Humidity Key Features Lock  Alarm Our Networking  Electrical Power  Working power supply A pcs AAA alkaline batteries Battery life Battery life But a guide Human voice guide  Door opening direction Door type Woo Operating Enviromenent Temperature Humidity Key Features  Lock  Networking  Emergency escape Indicator			Installation Requir	ements
PIN code Card Master PIN code TTlock App Mechanical key  Capacity  Fingerprint  Card Card PIN code TTlock App Mechanical key  Capacity  Fingerprint  Card Card Card Card Coverating Enviromenent  Temperature Humidity Key Features Lock  Alarm Our Networking  Electrical Power  Working power supply  A pcs AAA alkaline batteries Battery life  8 months Emergency charging  2V powerbank Voice guide  direction  Door type Wood Operating Enviromenent  Temperature  Humidity  Key Features  Lock  Fingerprint  200 Networking  Emergency escape  Indicator	Connectivity	Wifi / Bluetooth	Door Thickness	
PIN code Card Master PIN code TTlock App Mechanical key  Capacity  Fingerprint  Card  Card	Access Solution	Fingerprint	Door opening	
Card Master PIN code  TTlock App Mechanical key  Capacity  Capacity  Capacity  Capacity  Capacity  Fingerprint  200  PIN code  Card  200  E-key  Unlimited  Electrical Power  Working power supply  4 pcs AAA alkaline batteries  Battery life  8 months  Emergency charging  2V powerbank  Voice guide  Door type  Operating Enviromenent  Temperature  Humidity  Key Features  Lock  Alarm  Ou  Networking  Emergency escape  Indicator		PIN code	direction	R
Master PIN code TTlock App Mechanical key  Capacity  Fingerprint  200 PIN code Card E-key Unlimited  Electrical Power  Working power supply  A pcs AAA alkaline batteries  Battery life  8 months Emergency charging  2V powerbank  Voice guide  Master PIN code Temperature Humidity Key Features  Lock  Alarm Our Networking  Emergency escape  Indicator			Door type	Woode
Mechanical key  Capacity  Fingerprint  200  PIN code  150  Card  200  E-key  Unlimited  Electrical Power  Working power supply  4 pcs AAA alkaline batteries  Battery life  8 months  Emergency charging  2V powerbank  Voice guide  Humidity  Key Features  Lock  Alarm  Our  Networking  Emergency escape  Indicator			Operating Envirom	enent
Mechanical key  Capacity  Capacity  Fingerprint  200  PIN code  150  Card  200  E-key  Unlimited  Electrical Power  Working power supply  4 pcs AAA alkaline batteries  Battery life  8 months  Emergency charging  2V powerbank  Voice guide  Humidity  Key Features  Lock  Alarm  Our  Networking  Emergency escape  Indicator		TTlock App	Temperature	
Capacity  Eingerprint  Card  Card  E-key  Unlimited  Electrical Power  Working power supply  4 pcs AAA alkaline batteries  Battery life  8 months  Emergency charging  2V powerbank  Voice guide  Lock  Alarm  Our  Networking  Emergency escape  Indicator		• •	Humidity	
Fingerprint 200 PIN code 150 Card 200 E-key Unlimited  Electrical Power Shar Working power supply 4 pcs AAA alkaline batteries Battery life 8 months Emergency charging 2V powerbank Voice guide Human voice guide		Mechanical key	Key Features	
PIN code 150 Card 200 E-key Unlimited  Electrical Power Shar Working power supply 4 pcs AAA alkaline batteries Battery life 8 months Emergency charging 2V powerbank Voice guide Human voice guide	Capacity		Lock	
PIN code 150  Card 200 E-key Unlimited  Electrical Power Shar  Working power supply 4 pcs AAA alkaline batteries  Battery life 8 months  Emergency escape  Indicator  Woice guide Human voice guide	Fingerprint	200		
Card 200 E-key Unlimited  Electrical Power Shar  Working power supply 4 pcs AAA alkaline batteries Battery life 8 months Emergency charging 2V powerbank  Voice guide Human voice guide	PIN code	150	Alarm	0
E-key Unlimited  Electrical Power Shar  Working power supply 4 pcs AAA alkaline batteries  Battery life 8 months  Emergency escape  Indicator  Indicator  Voice guide Human voice guide	Card	200	N	Outsic
Electrical Power  Working power supply 4 pcs AAA alkaline batteries  Battery life 8 months  Emergency escape  Indicator  Woice guide Human voice guide			Networking	
Working power supply 4 pcs AAA alkaline batteries  Battery life 8 months  Emergency escape  Indicator  Emergency charging 2V powerbank  Voice guide Human voice guide				Cł
Battery life 8 months  Emergency charging 2V powerbank  Voice guide Human voice guide	Electrical Power			Share t
Emergency charging 2V powerbank  Voice guide Human voice guide	Working power supply	4 pcs AAA alkaline batteries	Emergency escape	
Voice guide Human voice guide	Battery life	8 months	Indicator	L
	Emergency charging	2V powerbank		
Operation Modes Auto mode	Voice guide	Human voice guide		
	Operation Modes	Auto mode		

Front	65mm(H) x 145mm(W) x 65mm(T)
Back	65mm(H) x 145mm(W) x 65mm(T)
Installation Requir	rements
Door Thickness	35-65mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Environ	
Temperature	-20°C-+50°C
Humidity	20%RH-95%RH
Key Features	
-	
Lock	System lock
Lock	
	Anti-prying alarm
	Anti-prying alarm Outside forced lock alarm
Alarm	Anti-prying alarm Outside forced lock alarm Generate PIN code
Alarm	Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records
Alarm	Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code
Alarm Networking	Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code





# **T28**

#### **ROOM SERIES**

Affordable. Easy to install







Lithium rechargeable battery



Fully automatic



Access record query



Bluetooth



Voice prompts



Material	Zinc alloy	Dimensions	
Color	Black	Front	65mm(H) x 145mm(W) x 65mm(T)
Fingerprint sensor	Semiconductor	Back Installation Requi	65mm(H) x 145mm(W) x 65mm(T)
Connectivity	Bluetooth	Door Thickness	35-55mm
Access Solution	Fingerprint	Door opening	Left-in/Left-out
	Smart Life App	direction	Right-in/Right-out
	Mechanical key	Door type	Wooden/Copper/Security
		Operating Environ	nenent
Capacity		Temperature	-20°C-+50°C
Fingerprint	200		20%RH-95%RH
Electrical Power		Key Features	
Working power supply	Lithium battery	Lock	System lock
——————————————————————————————————————		Alarm	Anti-prying alarm
Battery life	3 months		Outside forced lock alarm
Emergency charging	2V powerbank	Networking	Check access records
	<u> </u>	Emergency escape	e Indoor fast
Voice guide	Human voice guide		opening mortise
Operation Modes	Auto mode	Indicator	Low battery indicator











C-class lock cylinder



Various ways to unlock




Access record query



Bluetooth



PIN code distributing





Material	Aluminum alloy
Color	Sliver / Blaci
Fingerprint sensor	Semiconducto
Connectivity	WI-FI / Bluetooth
Access Solution	Fingerprint
	PIN code
	Carc
	Master PIN code
	TTlock App
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AA alkaline batteries
Battery life	8 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

Dimensions	
Front	333.5mm(H) x 43.5mm(W) x 88.4mm(T)
Back	333.5mm(H) x 43.5mm(W) x 88.4mm(T)
Installation Req	uirements
Door Thickness	35-65mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envir	omenent
Temperature	-20°C-+50°C
Humidity	20%RH-95%RH
Key Features	
Lock	System lock
	Indoor deadlock
Safety	Hidden PIN code
Alarm	Anti-prying alarm
	Outside forced lock alarm
Networking	Generate PIN code
	Check access records
	Share temporary PIN code
Emergency esca	ape Indoor fast
	opening mortise
Indicator	Low battery indicato
	System status indicato
	Lock status indicato
	Outside forced lock indicato



<sup>\*8</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license

G2











C-class lock cylinder



Various ways to unlock



Access record query



Bluetooth



PIN code distributing



Card	200
PIN code	150
Fingerprint	200
Capacity	
	TTlock App Mechanical key
	Master PIN code
	Card
	PIN code
Access Solution	Fingerprint
Connectivity	WI-FI / Bluetooth
Fingerprint sensor	Semiconductor
Color	Black

350mm(H) x 37mm(W) x 53mm(T)
350mm(H) x 37mm(W) x 45mm(T)
ements
35-65mm
Left-in/Left-out
Right-in/Right-out
Wooden/Copper/Security
enent
-20°C-+50°C
20%RH-95%RH
System lock
Indoor deadloc
Hidden PIN code
Anti-prying alarm
Outside forced lock alarm
Generate PIN code
Check access records
Share temporary PIN code
Indoor fast
opening mortise
Low battery indicato
System status indicato
•















Bluetooth



PIN code distributing





Material	Aluminum alloy
Color	Black
Fingerprint sensor	Semiconductor
Connectivity	WI-FI / Bluetooth
Access Solution	Fingerprint
	PIN code
	Card
	Master PIN code
	TTlock App
	Remote Controller
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	1200 MA 7.4 V Lithium battery
Battery life	3 months
Emergency charging	5V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

Front	316mm(H) x 35mm(W) x 48mm(T)
Back	316mm(H) x 22mm(W) x 48mm(T
Installation Requir	ements
Door Thickness	35-65mm
Door opening	Left-in/Left-out
direction	Right-in/Right-out
Door type	Wooden/Copper/Security
Operating Envirom	enent
Temperature	-20°C-+50°C
Humidity	20%RH-95%RH
Key Features	
Lock	System lock
Lock	Hidden PIN code
Lock	Hidden PIN code Anti-prying alarm
Lock	Hidden PIN code Anti-prying alarm Outside forced lock alarm
Lock Safety Alarm	Hidden PIN code Anti-prying alarm Outside forced lock alarm Generate PIN code
Lock Safety Alarm	Hidden PIN code  Anti-prying alarm  Outside forced lock alarm  Generate PIN code  Check access records
Lock Safety Alarm	Hidden PIN code  Anti-prying alarm  Outside forced lock alarm  Generate PIN code  Check access records  Share temporary PIN code
Safety Alarm Networking	Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code
Safety Alarm Networking	Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code Indoor fast
Safety Alarm Networking Emergency escape	System lock  Hidden PIN code  Anti-prying alarm  Outside forced lock alarm  Generate PIN code  Check access records  Share temporary PIN code  Indoor fast  opening mortise  Low battery indicato  System status indicato
Safety Alarm Networking Emergency escape	Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code Indoor fast opening mortise Low battery indicato

<sup>\*3</sup> months: The actual battery life will vary depending on the using scenes. Product specification are subject to modify without prior notice. The Namani are registered trademark and are used under license







Dual Fingerprint



Remote unlock




Access record query



Bluetooth




PIN code distributing





Material	Aluminum alloy
Color	Black
Fingerprint sensor	Semiconductor
Connectivity	WI-FI / Bluetooth
Access Solution	Fingerprint
	PIN code
	Card
	Master PIN code
	TTlock App
	Remote Controller
	Mechanical key
Capacity	
Fingerprint	200
PIN code	150
Card	200
E-key	Unlimited
Electrical Power	
Working power supply	4 pcs AAA alkaline batteries
Battery life	8 months
Emergency charging	2V powerbank
Voice guide	Human voice guide
Operation Modes	Auto mode

307mm(H) x 39mm(W) x 72mm(T)
155mm(H) x 68mm(W) x 72mm(T)
ments
35-65mm
Left-in/Left-out
Right-in/Right-out
Wooden/Copper/Security
nent
-20°C-+50°C
20%RH-95%RH
System lock
System lock
Hidden PIN code
Hidden PIN code Anti-prying alarm
Hidden PIN code Anti-prying alarm Outside forced lock alarm
Hidden PIN code Anti-prying alarm Outside forced lock alarm Generate PIN code
Hidden PIN code  Anti-prying alarm  Outside forced lock alarm  Generate PIN code  Check access records
Hidden PIN code  Anti-prying alarm  Outside forced lock alarm  Generate PIN code  Check access records  Share temporary PIN code
Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code
Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code Indoor fast opening mortise
System lock  Hidden PIN code  Anti-prying alarm Outside forced lock alarm Generate PIN code Check access records Share temporary PIN code Indoor fast opening mortise Low battery indicato System status indicato





# NAMANI®

Namani reserves the right to make changes in specifications or to discontinue any product at any time without prior notice. Namani will not be liable for any consequences arising from publication.

Namani is a registered trademark and is used under license

Company name: Namani Smart Solution Sdn. Bhd.

Address: No.330, Jalan Simbang, Taman Perling, 81200 Johor Bahru, Johor

**Website:** www.namani.com.my **Email:** namanismartlock@gmail.com