C SHARE

# Skid-Steer Loaders / S630 Skid-Steer Loader Specifications & Options

| E Standard | Optional   | MA Not Applicable  | Units | US |
|------------|------------|--------------------|-------|----|
|            | - optional | and Not Applicable | UNITS | US |

|                      | Bobcat S630  |
|----------------------|--------------|
| Emissions Tier (EPA) | Tier 4       |
| Engine Cooling       | Liquid       |
| Engine Fuel          | Diesel       |
| Horsepower           | 74 hp        |
| Turbocharged Engine  | $\checkmark$ |

#### Performance

| Rated Operating Capacity (ISO) | 2,180 lb |
|--------------------------------|----------|
| Tipping Load                   | 4360 lb  |
| Operating Weight               | 7610 lb  |
| Travel Speed                   | 7.1 mph  |
| Travel Speed (2-speed option)  | 12.3 mph |

## Capacities

| Fuel Tank | 23.9 gal |
|-----------|----------|
|-----------|----------|

#### Hydraulic System

| System Relief @ Quick Couplers | 3,500 psi    |
|--------------------------------|--------------|
| Auxiliary Std Flow             | 23 gal/min   |
| Auxiliary High Flow            | 30.5 gal/min |

### Dimension

| Length                      | 136.8 in |
|-----------------------------|----------|
| Length without Attachment   | 108.4 in |
| Length with Standard Bucket | 136.8 in |
| Width                       | 72.1 in  |
| Width (with bucket)         | 74 in    |
| Height                      | 81.3 in  |
| Height with Operator Cab    | 81.3 in  |
| Height to Bucket Hinge Pin  | 121 in   |
| Reach @ Maximum Height      | 21.4 in  |
| Turning Radius              | 83.4 in  |
| Wheelbase                   | 45.3 in  |

#### **Features**

| Joystick Control             |  |
|------------------------------|--|
| Air Conditioning             |  |
| Adjustable Seat              |  |
| Backup Alarm                 |  |
| BICS System (Interlock)      |  |
| Cab Enclosure                |  |
| Sound Option                 |  |
| Cab Heater                   |  |
| Operating Lights             | · · · · · · · · · · · · · · · · · · ·                    |
| Parking Brake                | <ul> <li>• • • • • • • • • • • • • • • • • • •</li></ul> |
| Radio                        |  |
| Rear Window                  | · · · · · · · · · · · · · · · · · · ·                    |
| Top Window                   | <ul> <li>•</li> </ul>                                    |
| Lift-Arm Support             | · · · · · · · · · · · · · · · · · · ·                    |
| Seat Belt                    | -  |
| Suspension Seat              | · · · · · · · · · · · · · · · · · · ·                    |
| Two Speed Travel             |  |
| Deluxe Instrumentation       |  |
| Engine Shutdown              | · · · · · · · · · · · · · · · · · · ·                    |
| Hydraulic Bucket Positioning |  |
| High Flow Option             |  |
| Auxiliary Hydraulics         | · · · · · · · · · · · · · · · · · · ·                    |
| Spark Arrestor Muffler       | • • • • • • • • • • • • • • • • • • •                    |
| Bob-Tach Attachment System   | · · · · · · · · · · · · · · · · · · ·                    |
| Power Bob-Tach               |  |
| ACS (Switchable Controls)    | $\checkmark$   |
| Ride Control                 |  |
| Rear Hydraulics              |  |
| Horn                         | • • • • • • • • • • • • • • • • • • •                    |
|                              |  |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.