



Skid-Steer Loaders / S570 Skid-Steer Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Units **US**

Bobcat S570

| | |
|----------------------|-------------------------------------|
| Emissions Tier (EPA) | Tier 4 |
| Engine Cooling | Liquid |
| Engine Fuel | Diesel |
| Horsepower | 61 hp |
| Turbocharged Engine | <input checked="" type="checkbox"/> |

Performance

| | |
|--------------------------------|----------|
| Rated Operating Capacity (ISO) | 1,950 lb |
| Tipping Load | 3900 lb |
| Operating Weight | 6480 lb |
| Travel Speed | 7.4 mph |
| Travel Speed (2-speed option) | 11 mph |

Capacities

| | |
|-----------|----------|
| Fuel Tank | 24.8 gal |
|-----------|----------|

Hydraulic System

| | |
|--------------------------------|--------------|
| System Relief @ Quick Couplers | 3,500 psi |
| Auxiliary Std Flow | 17.1 gal/min |
| Auxiliary High Flow | 26.7 gal/min |

Dimension

| | |
|------------------------------------|----------|
| Length | 133 in |
| Length without Attachment | 104.6 in |
| Length with Standard Bucket | 133 in |
| Width | 64.7 in |
| Width (with bucket) | 68 in |
| Height | 77.8 in |
| Height with Operator Cab | 77.8 in |
| Height to Bucket Hinge Pin | 119 in |
| Reach @ Maximum Height | 32.6 in |
| Turning Radius | 79.7 in |
| Wheelbase | 42.6 in |

Features

| | |
|------------------------------|-------------------------------------|
| Joystick Control | <input checked="" type="checkbox"/> |
| Air Conditioning | <input checked="" type="checkbox"/> |
| Adjustable Seat | <input type="checkbox"/> |
| Backup Alarm | <input type="checkbox"/> |
| BICS System (Interlock) | <input type="checkbox"/> |
| Cab Enclosure | <input checked="" type="checkbox"/> |
| Sound Option | <input checked="" type="checkbox"/> |
| Cab Heater | <input checked="" type="checkbox"/> |
| Operating Lights | <input type="checkbox"/> |
| Parking Brake | <input type="checkbox"/> |
| Radio | <input checked="" type="checkbox"/> |
| Rear Window | <input type="checkbox"/> |
| Top Window | <input type="checkbox"/> |
| Lift-Arm Support | <input type="checkbox"/> |
| Seat Belt | <input type="checkbox"/> |
| Suspension Seat | <input type="checkbox"/> |
| Two Speed Travel | <input checked="" type="checkbox"/> |
| Deluxe Instrumentation | <input checked="" type="checkbox"/> |
| Engine Shutdown | <input type="checkbox"/> |
| Hydraulic Bucket Positioning | <input checked="" type="checkbox"/> |
| High Flow Option | <input checked="" type="checkbox"/> |
| Auxiliary Hydraulics | <input type="checkbox"/> |
| Spark Arrestor Muffler | <input type="checkbox"/> |
| Bob-Tach Attachment System | <input type="checkbox"/> |
| Power Bob-Tach | <input checked="" type="checkbox"/> |
| ACS (Switchable Controls) | <input checked="" type="checkbox"/> |
| Ride Control | <input checked="" type="checkbox"/> |
| Rear Hydraulics | <input checked="" type="checkbox"/> |
| Horn | <input type="checkbox"/> |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.