



Excavators / E85 Compact Excavator

Specifications & Options

Standard

Optional

N/A Not Applicable

UnitsUS

Bobcat E85	
Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,100 rpm
Horsepower	65.9 hp
Turbocharged Engine	<input checked="" type="checkbox"/>
Optional Horsepower	n/a

Performance

Operating Weight	18,977 lb
Weight Class	8.6 t
Travel Speed - High	2.9 mph
Travel Speed - Low	1.7 mph
Arm Digging Force	8,253 lbf
Bucket Digging Force	16,269 lbf
Rated Lift Capacity	9754 lb
Lift Radius	118 in
Boom Swing - Left	64°
Boom Swing - Right	61°
Maximum Dig Depth	15.5 ft
Max Dump Height	16.5 ft
Maximum Reach at Ground Level	23.6 ft

Capacities

Fuel Tank	30.6 gal
-----------	----------

Hydraulic System

Auxiliary Std Flow	25.1 gal/min
Auxiliary Pressure	3,045 psi

Dimension

Length	246 in
Overall Length in Travel Position	246 in
Width	87 in
Height	99.8 in
Height with Operator Cab	99.8 in

Features

Air Conditioning	<input type="checkbox"/>
Cab Enclosure	<input type="checkbox"/>
Cab Heater	<input type="checkbox"/>
Heater Air Conditioning	<input type="checkbox"/>
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Minimal
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>
Quick Tach System	<input checked="" type="checkbox"/>
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.