

 SHARE

## Excavators / E32 Compact Excavator

# Specifications & Options

■ Standard
  Optional
N/A Not Applicable

Units **US**

Configuration	Bobcat E32 25 HP		
	E32R Std Arm	E32R (EA)	E32R (LA)
Emissions Tier (EPA)	Tier 4	Tier 4	Tier 4
Engine Fuel	Diesel		
Maximum Governed RPM	2,200 rpm	2,200 rpm	2,200 rpm
Horsepower	24.8 hp	24.8 hp	24.8 hp
Turbocharged Engine	N/A	N/A	N/A
Optional Horsepower	n/a		

## Performance

Operating Weight	7,183 lb	8,434 lb	8,203 lb
Weight Class	3.3 t	3.8 t	3.7 t
Travel Speed - High	2.9 mph	2.9 mph	2.9 mph
Travel Speed - Low	1.6 mph	1.6 mph	1.6 mph
Arm Digging Force	4,589 lbf	4,478 lbf	3,986 lbf
Bucket Digging Force	6,969 lbf	6,968 lbf	6,968 lbf
Rated Lift Capacity	2969 lb	2564 lb	2702 lb
Lift Radius	118 in		
Boom Swing - Left	75°		
Boom Swing - Right	55°		
Maximum Dig Depth	10.2 ft	12.9 ft	11.2 ft
Max Dump Height	11 ft	12.5 ft	11.5 ft
Maximum Reach at Ground Level	16.3 ft	18.9 ft	17.4 ft

## Capacities

Fuel Tank	13.7 gal		
-----------	----------	--	--

## Hydraulic System

Auxiliary Std Flow	16.9 gal/min		
Auxiliary Pressure	2,987 psi	2,987 psi	2,987 psi

## Dimension

Length	183.5 in	187.7 in	187.5 in
Overall Length in Travel Position	183.5 in	187.7 in	187.5 in
Width	61 in	61 in	61 in
Height	96.2 in	96.2 in	96.2 in
Height with Operator Cab	96.2 in	96.2 in	96.2 in

## Features

Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Enclosure	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Heater Air Conditioning	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Radio	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tail Swing Type	Conventional	Conventional	Conventional
Engine Shutdown	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Quick Tach System	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rubber Track	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Angle Blade	N/A	N/A	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.