

Cassette Deluxe – R410A



(Applicable to 10,000-13,800 Btu/hr)



(Applicable to 19,030-50,000 Btu/hr)

Wireless Remote Controller



Wired Remote Controller (Optional)



Features



Personalized Air Control
 (Applicable to 19,030 50,000 Btu/hr)
 Four flaps personalized air control for individual air comfort.



Super Slim
 (Applicable to 19,030~50,000 Btu/hr)
 Super slim design that fits narrow ceiling spaces.



Healthy Ionizer
 Breathe fresher and healthier air for your family with the ion purifier.



4-Speed Drive
 4-Speed Drive provides extra cooling during the hotter days.



Vertical Flow
 Vertical Flow provides strong optimal airflow from heights up to 4.2 meters.



Air Surround
 (Applicable to 19,030~50,000 Btu/hr)
 Feel the air all around with the round air feature.



Other Features



Comfortable Sleep




Auto Mode



24 HourTimer



High Performance Compressor



Water Pump



Fresh Air



3 Minutes Protection



Auto Restart



Self - Diagnosis

Specifications

Indoor Unit		Wireless	YCK3F10AAS-W	YCK3F15AAS-W	YCK3F20AAS-W	YCK3F25AAS-W
Outdoor Unit		Wired	YCK3F10AAS-SLM	YCK3F15AAS-SLM	YCK3F20AAS-SLM	YCK3F25AAS-SLM
			YSM3F10AAS	YSM3F15AAS	YSM3F20AAS	YSM3F25AAS
Cooling Capacity	Btu/hr		10,000	13,800	19,030	26,000
Input Power	W		850	1,150	1,860	2,450
Rated Current	A		3.70	5.00	8.10	10.61
EER	Btu/hr/W		11.76	12.00	10.23	10.61
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz				
Refrigerant Type/ Control		R410A / OUTDOOR CAP.TUBE				
Indoor Air Flow (H/L)	CFM		298/230	387/254	735/490	735/486
Noise Level (H/L)	dB(A)		41/34	42.5/34	40/34	44/36
Indoor Unit	Body Dimension(WxDxH)	mm	570x570x260	570x570x260	840x840x204	840x840x204
	Panel Dimension(WxDxH)	mm	700x700x60	700x700x60	950x950x60	950x950x60
	Net Weight Body	kg	23.30	26.30	25.00	28.50
	Net Weight Panel	kg	4.20	4.20	6.50	6.50
Outdoor Unit	Dimension (WxDxH)	mm	780x245x540	780x260x680	810x340x680	810x340x680
	Net Weight	kg	36.00	42.00	49.00	53.00
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4	6.35 / 1/4	9.52 / 3/8
	Gas	mm/in	12.70 / 1/2	12.70 / 1/2	15.88 / 5/8	15.88 / 5/8

Indoor Unit		Wireless	YCK3F30AAS-W	YCK3F35AAS-W	YCK3F40AAS-W	YCK3F50AAS-W
Outdoor Unit		Wired	YCK3F30AAS-SLM	YCK3F35AAS-SLM	YCK3F40AAS-SLM	YCK3F50AAS-SLM
			YSM3F30AAS	YSM3F35AAS	YSM3F40AAS	YSM3F50AAS
Cooling Capacity	Btu/hr		31,000	35,000	40,700	50,000
Input Power	W		2,850	3,150	3,590	4,500
Rated Current	A		12.39	13.70	6.10	7.60
EER	Btu/hr/W		10.88	11.11	11.34	11.11
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz			3Ph/380-415V/50Hz	
Refrigerant Type/ Control		R410A / INDOOR CAP.TUBE				
Indoor Air Flow (H/L)	CFM		962/500	1,068/589	1,068/589	1,118/618
Noise Level (H/L)	dB(A)		47/37	48/40	48/40	49/40
Indoor Unit	Body Dimension(WxDxH)	mm	840x840x246	840x840x246	840x840x246	840x840x288
	Panel Dimension(WxDxH)	mm	950x950x60	950x950x60	950x950x60	950x950x60
	Net Weight Body	kg	33.50	33.00	33.50	35.50
	Net Weight Panel	kg	6.50	6.50	6.50	6.50
Outdoor Unit	Dimension (WxDxH)	mm	862x375x730	840x415x960	1,008x410x830	1,008x410x830
	Net Weight	kg	59.00	72.50	84.00	93.50
Refrigerant Piping	Liquid	mm/in	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8
	Gas	mm/in	15.88 / 5/8	15.88 / 5/8	19.05 / 3/4	19.05 / 3/4

Note:

- All designs and specifications are subjected to change without prior notice for product improvement
- Nominal cooling capacity is based on the conditions below
Power supply, 1Ph/230V/50Hz or 3Ph/380V/50Hz
Cooling - Indoor: 27°C DB /19°C WB and Outdoor 35°C DB / 24°C WB
- Units are tested and comply with the latest ISO5151



(Applicable to 2.8 HP and below)

Head Office:

YORK (MALAYSIA) SALES & SERVICE SDN BHD (168496-T)

Bangunan THK, Suite 2.1, 2nd Floor,
No.2A, Jalan 243, Section 51A,
46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia
Tel. 03-7628 4100 Fax: 03-7628 4101

Branches:

Penang Branch
Tel. 04-397 0213 Fax: 04-397 2045

Kuching
Tel. 082-553 100 Fax: 082-553 200

Johor Bahru Branch
Tel. 07-354 9878 Fax: 07-354 9871

Kota Kinabalu Branch
Tel. 088-448 350 Fax: 088-448 352



Authorized Dealer

Customer Care Centre: 1800 - 88 - YORK (9675)

Website: www.york.com/my