Safety Padlocks

BradyID.com/s35



Brady Safety Padlocks

- Comply with all OSHA requirements and are a safer alternative to metal locks for lockout applications
- Non-conductive body with unique key cylinder prevents electricity from traveling from the shackle to the key, protecting workers when key is inserted
- Superior temperature, chemical and corrosion resistance
- "Danger" and "Property of" labels provided in English, Spanish and French and printed on 100% recycled paper
- Reserved paracentric keyway provides optimal security (prevents someone from getting a copy made at a local key shop)
- Key-retaining feature prevents key from being removed until shackle is securely closed
- Locks come keyed differently or in keyed-alike sets. Custom keying and charting available
- Lock bodies can be custom laser engraved upon request
- One key is supplied with each padlock for safer key management



Compact Safety Padlocks

- Extremely compact and lightweight the smallest safety lock on the market
- Easily fits in small spaces ideal for electrical contractors/ maintenance/electricians
- 5-pin cylinder can support same keying system as our current Safety Padlock
- Fiberglass reinforced nylon body for extra impact resistance
- Service temperature: 0°-250° F (-20°-120° C)
- Lock body dimensions: 1-2/5"H x 1-1/5"W x 5/8"D Shackle clearance: 1"; shackle diameter 1/5"
- Each padlock includes 1 key and 1 each English, Spanish and French labels

Compact Safety Padlocks - 1" Steel Shackle

•	-			
Color	Keyed Different 1/Pack	Keyed Different 6/Pack	Keyed Alike 3/Pack	Keyed Alike 6/Pack
Red	143150	118926	118953	118954
Green	143152	118927	118955	118956
Orange	143154	118928	118957	118958
Blue	143156	118929	118959	118960
Yellow	143158	118930	118961	118962
Brown	143160	118931	118963	118964
White	143162	118932	118965	118966
Purple	143164	118933	118967	118968
Black	143166	118934	118969	118970



Safety Padlocks

- Lightweight, non-conductive and non-sparking body
- Special 6-pin cylinder resists tampering
- Fiberglass reinforced nylon body and triple-coated hardened steel shackle
- Service temperature: 0°-250° F (-20°-120° C)
 Lock body dimensions: 1-3/4"H x 1-1/2"W x 4/5"D
- Shackle clearance: 1-1/2"; shackle diameter: 1/4"
- Each padlock includes 1 key and 1 each English, Spanish and French labels

Safety Padlocks - 1-1/2" Steel Shackle

Color	Keyed Different 1/Pack	Keyed Different 6/Pack	Keyed Alike 3/Pack	Keyed Alike 6/Pack
Red	99552	51339	105886	105890
Green	99564	51345	105889	105893
Orange	99576	51347	123268	123270
Blue	99556	51344	105887	105891
Yellow	99570	51346	105888	105892
Brown	103033	101956	118947	118948
White	143123	118925	118949	118950
Purple	104919	104916	118951	118952
Black	99580	51353	123269	123271

When keyed alike, all locks in a set can be opened with the same key. This option is beneficial when multiple locks are assigned to a single employee.



BradyID.com/s35

Safety Padlocks



Compact Safety Padlock Kits

Ideal for any worker needing just "one lock and one tag"

- 1 Compact Safety Padlock
- 1 Reuseable Heavy-duty Laminated Polyester (B-837) Lockout Tag
 1 Nylon Cable Tie

Compact Safety Padlock Kits

Catalog #	Lock Color	Qty
123143	Red	1
123144	Green	1
123145	Orange	1
123146	Blue	1
123147	Yellow	1
123148	Brown	1
123149	White	1
123150	Purple	1
123151	Black	1



Compact Cable Padlocks

- Compact 1.31"x1.25" nylon body with an elongated, flexible cable as the shackle
- Flexible cable means you can angle and twist padlock or lockout multiple energy isolation points with one lock

Compact Cable Padlocks

Color	Cable Length	1 Pack Keyed Different	6 Pack Keyed Alike
Red	Short 7.87" (20 cm)	146120	146128
Red	Long 15.75" (40 cm)	146124	146132
Yellow	Short 7.87" (20 cm)	146121	146129
Yellow	Long 15.75" (40 cm)	146125	146133
Blue	Short 7.87" (20 cm)	146122	146130
Blue	Long 15.75" (40 cm)	146126	146134
Green	Short 7.87" (20 cm)	146123	146131
Green	Long 15.75" (40 cm)	146127	146135



Safety Padlocks with Non-Conductive Nylon Shackle

- Lightweight, non-conductive and non-sparking body
- Special 6-pin cylinder resists tampering
- Fiberglass reinforced nylon body with non-conductive nylon shackle
- Lock body dimensions: 1-3/4"H x 1-1/2"W x 4/5"D
- Shackle clearance: 1-1/2"; shackle diameter: 1/4"
- Each padlock includes 1 key and 1 each English, Spanish and French labels





Long Body Safety Padlocks

- 3" long body has ample space for your most important identification information
- Lightweight, non-conductive and non-sparking body
- Special 6-pin cylinder resists tampering
- Fiberglass reinforced nylon body and triple-coated hardened steel shackle
- Service temperature: 0°-250° F (-20°-120°C)
- Lock body dimensions: 3"H x 1-1/2"W x 4/5"D
- Shackle clearance: 1-1/2"; shackle diameter: 1/4"
- Each padlock includes 1 key and 1 each English/Spanish and English/French labels

Safety Padlocks - 1-1/2" Nylon Shackle

Color	Keyed Different 1/Pack	Keyed Different 6/Pack	Keyed Alike 3/Pack	Keyed Alike 6/Pack
Red	123324	123351	123333	123342
Green	123326	123353	123335	123344
Orange	123328	123355	123337	123346
Blue	123325	123352	123334	123343
Yellow	123327	123354	123336	123345
Brown	123330	123357	123339	123348
White	123332	123359	123341	123350
Purple	123331	123358	123340	123349
Black	123329	123356	123338	123347

Long Body Safety Padlocks - 1-1/2" Shackle

Red 123405 123396 123414 123423 Green 123407 123398 123416 123425 Orange 123409 123400 123418 123427 Blue 123406 123397 123415 123424 Yellow 123408 123399 123417 123426 Brown 123411 123402 123420 123429 White 123413 123404 123422 123421)
Orange 123409 123400 123418 123427 Blue 123406 123397 123415 123424 Yellow 123408 123399 123417 123426 Brown 123411 123402 123420 123429	
Blue 123406 123397 123415 123424 Yellow 123408 123399 123417 123426 Brown 123411 123402 123420 123429	
Yellow 123408 123399 123417 123426 Brown 123411 123402 123420 123429	
Brown 123411 123402 123420 123429	
White 123413 123404 123422 123431	
Purple 123412 123403 123421 123430	
Black 123410 123401 123419 123428	

When keyed alike, all locks in a set can be opened with the same key. This option is beneficial when multiple locks are assigned to a single employee.