


HEAVY DUTY SLIDING GATE OPERATOR



attuatore per cancelli scorrevoli



actuator for sliding gates



actionneur pour portails coulissants



torantriebe für Schiebetore

Manufactured with highly resistant material to atmospheric corrosion, VALET SLIDING OPERATORS silently manoeuvre all kinds of sliding gates used in industrial, commercial and residential environment.

The operators are engineered to fit in gear wheel for pulling toothed gear rack and featured with powerful starting strength.

In case of power failure, an emergency release key allows the gate to operate manually. Lubricated gears and reliable rotating output shaft are a signature of efficient engineering and ensure accurate opening and closing mechanism.

Under OEM arrangement for VALET®, these sliding operators are designed to be both attractive and durable.



*MADE IN ITALY



Synthetic Oil
FOR LIFE

VT Series of operating actuators created for automatic movement of sliding gate weight up to 6,000kg



Technical Data

*Motor & gearbox are made in Italy

VT 1500S

Voltage : 230V ± 10%, 50-60Hz
Power : 370W (0.5HP)
Current : 3.2 Amps
Gate Weight : Max 1500 Kg
Gear Module : 4
Motor Protection : Thermal bimetallic device

VT 2000T

Voltage : 415V ± 10%, 50-60Hz
Power : 370W (0.5HP)
Current : 1.3 Amps
Gate Weight : Max 2000 Kg
Gear Module : 4
Motor Protection : Thermal bimetallic device

VT 2500S

Voltage : 230V ± 10%, 50-60Hz
Power : 750W (1.0HP)
Current : 5.6 Amps
Gate Weight : Max 2500 Kg
Gear Module : 4
Motor Protection : Thermal bimetallic device

VT 3000T

Voltage : 415V ± 10%, 50-60Hz
Power : 750W (1.0HP)
Current : 2.1 Amps
Gate Weight : Max 3000 Kg
Gear Module : 4
Motor Protection : Thermal bimetallic device

VT 4000T

Voltage : 415V ± 10%, 50-60Hz
Power : 1.5 Kw (2.0HP)
Current : 3.8 Amps
Gate Weight : Max 4000 Kg
Gear Module : 6

VT 5000T

Voltage : 415V ± 10%, 50-60Hz
Power : 2.2 Kw (3.0HP)
Current : 5.4 Amps
Gate Weight : Max 5000 Kg
Gear Module : 6

VT 6000T

Voltage : 415V ± 10%, 50-60Hz
Power : 3.0 Kw (4.0HP)
Current : 7.0 Amps
Gate Weight : Max 6000 Kg
Gear Module : 6

Single Phase

Three Phase

Opening Speed : 10m per minute

Synthetic Oil : For Life

Protection Rating : IP 55

Duty Service : S1 Continuous Service

Ventilation : Bidirectional Fan



Recommended to use external safety devices

Specification is subject to change without prior notice