



### Luminaire Specifications

Power	50W, 100W, 150W, 200W
Input Voltage	AC220 – 240V 50/60Hz
Fitting Color	Black
Material	Die Cast Aluminum, Glass
Ingress Protection	IP 65
Operating Temperature	20 - 50°C

### Product Features

- Ultra-slim & thin sleek design, stylish, classic, elegant and light weight
- Long lifetime, Energy-efficient lighting
- High-performance led chip Lumileds
- Energy saving, high light efficiency.
- Suitable for Indoor and outdoor use

### Application

- Exhibition Halls
- Car Park
- Building Facade
- Public Corridor
- Stair Corridor



Code	Watt	Lumen	Size	Degree
JDC-FLM50-DZ-V	50W	5000 Lm	230*185*40 mm	120°
JDC-FLM100-DZ-V	100W	10000 Lm	295*220*45 mm	120°
JDC-FLM150-DZ-V	150W	15000 Lm	370*280*50 mm	120°
JDC-FLM200-DZ-V	200W	20000 Lm	370*280*50 mm	120°

## Technical Data

Light LED Source	SMD 3030
Color Temperature	3000K Warm White 4000K Nature White 5700K Cool White
Rendering Index	>RA 70
LED life cycle	LM80 52,000hours @ 35°C
Power Factor	>0.9
Life Cycle	> 10,000 hours

