

Solenoid Coil Series



SV1000

SV3000

SV5000

SV6000

SV231
~232

COIL
CONNECTOR

SMV100

SMV200

SMVS200

SMVF231
~232

SMVF250

SMVF350

SFVM

SHV

CAUTION

How to order

SL3 - A2

① Coil type

- SG1 - 15mm - Grommet / Flying Leads
- SC1 - 15mm - 3 Pin Connector Coil
- SG3 - 22mm - Grommet / Flying Leads
- SL3 - 22mm - Grommet / Flying Leads with LED
- SC3 - 22mm - 3 Pin Connector Coil

② Voltage

- A1 - AC 220V
- A2 - AC 110V
- A4 - AC 24V
- D4 - DC 24V

Specification

Model	SG1, SC1	SG3, SL3, SC3		
Voltage Tolerances	±10% of Rated Voltage			
Coil Insulation Class	F-Class or Equivalent			
Ambient and Media temp.	5~60°C			
Holding Power	AC	60Hz	3.6VA	4.9VA
		50Hz	4.6VA	6.0VA
	DC	2.5W	2.5W	

Material

- Molding : Glass Pressure Nylon
- Lead Wire : AWG-no.22, no.24
- Lead Wire Packing : Viton
- Yoke : Carbon Iron
- Indicator Cap : Polycarbonate