

P2 SMD1515 INDOOR LED DISPLAY

Product Code/Model: HIP2SC2320X160MM

- Excellent color performance
- 16:9 gold ratio
- Light and thin box design
- 100% easy-maintenance


















Fully die-cast aluminium box Better cooling effect




Dual backup of power and signal

The box section has 2 power jacks and 4 signal jacks



Easy to install

The four chuckboards behind the box can be remove for front maintenance



Low gray highlighting technology **Enchance dark details**











Reliable products

High quality Nationstar LED chip and Mean Well power supply. Our products are compliance with CE & RoHs Certification.









2 YEARS WARRANTY













BREAKDOWN FAST RESPONSE (WITHIN 4 HOURS)

TECHNICAL PARAMETERS

ESCRIPTION	SPECIFICATION
Pixel Pitch	2mm
Pixel Density	250,000 pixel/m ²
LED Type	SMD1515 1R1G1B
LED Cabinet Size	640mm (W) x 480mm(H)
Module Size	320mm(H) x 160mm(H)
Module Resolution	160px (W) x 80px (H)
Driving Method	1/42
Weight	8.5 kg/pc
Maintenance Method	Front
Туре	Magnetic Type
Best view distance	≥2m
Brightness	800 cd/m ²
Color Temperature	6500K-9500K adjustable
Horizontal Viewing Angle	140°
Vertical viewing angle	140°
Maximum Contrast	3000:1
Control system	Asynchronous & Synchronous Control System
Power Consumption	Max: 540 w/m², Ave: 180 w/m²
Working Voltage	AC100~240V(50-63Hz)
Refresh Rate (Hz/Second)	60
Refresh Rate (Hz)	2880~3840
Gray Level	65536 grades for each color
Brightness Level	256 levels
Brightness Adjustment Method	Manual/Automatic/Program Control
Control Distance	CAT5 cable <100m; Single-mode fiber <10Km
Operation Temperature	-30°C - +65°C
Operation Humidity	10% - 90%RH
Chassis Design	IP31
MTBF	>10000h
Lifespan	>100000h
Certification	EMC / CE / ROHS / CCC / FCC / ISO







Contact us: +6012-723 2935 (Jack) +6017-702 6269