

CS210 / 510 / 610 are general purpose speakers suitable for paging and BGM applications which do not only deliver the required audio quality but fits into every installation with its contemporary outlooks. It is designed with slim edges for cosy appearance and the clamping mechanism provides ease of installation works.

Three variants are available with re-engineered sound output to serve the needs for both BGM and EVAC. CS210 is a miniature version most suitable for small enclosed area such as hotel room foyer and narrow corridors, while CS510 and 610 fits most other installations according to the needs of different coverage areas.



Features

- ▶ Slim edge design with low side profile
- ▶ High quality ABS enclosure with optional FR grade
- ▶ Spring clip installation
- ▶ Option for installation without enclosure

Packing information

CS210	: 570(L) x 230(W) x 290(H) mm : 11.30 kg : 20 uts per carton
CS510	: 690(L) x 350(W) x 400(H) mm : 19.60 kg : 24 uts per carton
CS610	: 660(L) x 440(W) x 430(H) mm : 19.50 kg : 18 uts per carton

Technical Specifications

	CS210	CS510	CS610	CS610B
SPEAKER				
Power rating	6W 100V line			10W 100V line
Diameter	2" (51 mm)	5" (125 mm)	6" (150 mm)	
Cone type	Single cone	Dual cone		
Impedance (Ohm)	8			
Freq response @ 1KHz +/-3 dB	160 - 15 KHz	150 - 19 KHz	120 - 19 KHz	
SPL @ 1W / m (+/- 3dB) 1 KHz)	90 dB	92 dB		
TRANSFORMER				
Tapping (100V line)	1.5 / 3 / 6W			1 / 3 / 6 / 10W
Primary impedance (Ohm)	6.7K / 3.3K / 1.67K			10K / 3.3K / 1.67K / 1K
Secondary impedance (Ohm)	8			
PHYSICAL				
Grille / enclosure	Metal / ABS enclosure			
Cutting hole dim	85 mm	145 mm	185 mm	
Overall size (dia x height)	110 x 110 mm	165 x 110 mm	205 x 110 mm	
Weight	500 g	780 g	840 g	850 g
Colour	White			