

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



Part #: 14240256

Model Number: C1651

Category: Basic

Sub Category: Standard

Power Configuration: 16A, 230V, 3.6kW

Physical Configuration: 1683mm x 51mm x 51mm, Vertical

Product Summary:

C1651 - Basic Standard, 16A, 230V, 3.6kW, Vertical, (20) IEC C13 and (4) IEC C19, 3m power cord Hardwired, Black Powder Coat

Plug Form:



Hardwired

Receptacle:



IEC C13
(Quantity: 20)



IEC C19
(Quantity: 4)

Chassis Color Options:



Part #: 14240256

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW (230V)
Frequency	50/60Hz
Over Current Protection	None
Switch	None
Power Cable Length	3m
Plug Type	3 x 2.5mm ² hardwire
Receptacle/Socket Type #1	IEC C13
- Quantity	20
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC C19
- Quantity	4
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45°C/113F
Heavy Steel - Powder Coat Finish	Black
Configuration	0U, Vertical
Toolless mounting HW – Center to Center	1560mm and 1645mm (Vertical mounting bracket included)
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	CE, EN55032 & EN55024, IEC62368-1, RoHS
Chassis Dimensions (HxWxD)	1683mm x 51mm x 51mm