

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



Part #: 14240246

Model Number: C1650L

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 1683mm x 51mm x 51mm, Vertical

Product Summary:

C1650L - Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) Locking IEC C13, (4) Locking IEC C19, Breakered, 3m power cord 2P+E (IP44), Black Powder Coat

Plug Form:



2P + E
(IP44)

Receptacle:



Locking IEC C13
(Quantity: 20)



Locking IEC C19
(Quantity: 4)

Chassis Color Options:



Part #: 14240246

Product Specification and Options

System Features

| | |
|--|---|
| Quantity Of Inputs | 1 |
| Voltage | 220-240V |
| Current | 32A |
| VA per Input (Load Capacity) | 7.3kW (230V) |
| Frequency | 50/60Hz |
| Over Current Protection | (2) 16A Single Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 4mm ² |
| Power Cable Length | 3m |
| Plug Type | IEC60309 2P + E, 32A, 250V, Splash proof IP44 |
| Receptacle/Socket Type #1 | U-Lock IEC C13 |
| - Quantity | 20 |
| - Quantity per Breaker | 10 |
| - U-Lock Color | 2 circuit (Orange, Green) |
| - Maximum Output per Receptacle/Socket | 10A |
| - Voltage per Receptacle/Socket | 230V |
| Receptacle/Socket Type #2 | U-Lock IEC C19 |
| - Quantity | 4 |
| - Quantity per Breaker | 2 |
| - U-Lock Color | 2 circuit (Orange, Green) |
| - Maximum Output per Receptacle/Socket | 16A |
| - Voltage per Receptacle/Socket | 230V |
| Maximum Operating Temperature | 45°C/113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 0U, Vertical |
| Toolless mounting HW – Center to Center | 1560mm and 1645mm (vertical mounting bracket included) |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | CE, EN55032 & EN55024, IEC62368-1, RoHS |
| Chassis Dimensions (HxWxD) | 1683mm x 51mm x 51mm |
| Shipped Weight | 8.16kg |