

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.



**Part #: 14240257**

**Model Number:** C1652

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 1683mm x 51mm x 51mm, Vertical

### Product Summary:

C1652 - Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) IEC C13, (4) IEC C19, Breakered, 3m power cord Hardwired, Black Powder Coat

### Plug Form:



Hardwired

### Receptacle:



IEC C13  
(Quantity: 20)



IEC C19  
(Quantity: 4)

### Chassis Color Options:



## Part #: 14240257

### Product Specification and Options

#### System Features

<b>Quantity Of Inputs</b>	1
<b>Voltage</b>	230V
<b>Current</b>	32A
<b>VA per Input (Load Capacity)</b>	7.3kW (230V)
<b>Frequency</b>	50/60Hz
<b>Over Current Protection</b>	(2) 16A Single Pole Magnetic Breakers
<b>Switch</b>	Breaker/Switch Combination
<b>Power Cable Length</b>	3m
<b>Plug Type</b>	3 x 4mm <sup>2</sup> hardwire
<b>Receptacle/Socket Type #1</b>	IEC C13
- Quantity	20
- Quantity per Breaker	10
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
<b>Receptacle/Socket Type #2</b>	IEC C19
- Quantity	4
- Quantity per Breaker	2
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
<b>Maximum Operating Temperature</b>	45°C/113F
<b>Heavy Steel - Powder Coat Finish</b>	Black
<b>Configuration</b>	0U, Vertical
<b>Toolless mounting HW – Center to Center</b>	1560mm and 1645mm (Vertical mounting bracket included)
<b>Product Warranty</b>	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
<b>Certification/Agency Approvals</b>	CE, EN55032 & EN55024, IEC62368-1, RoHS
<b>Chassis Dimensions (HxWxD)</b>	1683mm x 51mm x 51mm