


Spirolab III®

**Fast, simple, durable
Diagnostic spirometer
with oximetry option**



3rd Generation Laboratory



**Highly portable
desktop spirometer
with large test memory
capacity and built in
printer**



Suitable for children
**Exclusive pediatric
incentive MIR
exclusive patent**




Oximetry Option
**Different types of
oximetry tests including
sleep and exercise tests**



Ideal for Screening
**Easy remote
diagnosis and
tele-consulting**

Spirolab III®



Oximetry option for a variety of tests



Spot oximetry.
Bed side sleep oximetry
with desaturation events recording.
Oximetry during exercise test.



Highly portable Desktop spirometer

FVC, VC with breathing pattern plus MVV tests with real time curves.
High resolution color display (also available Black and White option).
Simple icon based menu on the keyboard.
PRE test and related POST test are shown superimposed.
6000 test memory and upto 8 tests on screen.
Selectable language and predicted values.
Customisable printout format.
Connectivity: USB and RS232.

Ideal for Screening

Spirolab III® is a multitasking and versatile spirometer ideal for accurate and early diagnosis of respiratory diseases (like COPD and Asthma). Spirolab III® is easy to use for family doctors screening or pharmacy quick tests.

Teleconsulting and Clinical Trials


It is also indicated for Clinical Trials.

These studies often enroll large numbers of people and are conducted at many doctors' offices, clinics, and centers globally.

Data recorded by Spirolab III® can be easily transmitted via FTP connection.

Exclusive pediatric incentive system

Amusing on screen paediatric incentive program which can be useful to help a child (or an older person) make a correct spirometry test.



New WinspiroPRO®

High performance PC software for spirometry and oximetry

WinspiroPRO® is a unique featured PC software, which comes standard with all MIR spirometers and oximeters.

All tests memorized in Spirolab III® can be downloaded into WinspiroPRO® and a patient data card is created automatically, with a preview of the spirometry curve.


The spirometry incentive routine (MIR patent), allows the user to select the patient's favourite image in order to get his maximum compliance.

This software also gives trend of any parameter so is ideal for clinical trials and telemedicine.

HL7 Interface for a remote connection with the Hospital Management System.

WinspiroPRO® can easily be connected to a database or to an EMR, Hospital or Occupational Health System.

Network Version available.



Summary of all tests carried out



Printout: Exercise Test Oximetry



Printout: Sleep Oximetry with desaturation analysis

Spirolab III®

Spirolab III® along with all standard accessories (winspiroPRO CD, user manual CD, oximetry sensor, if available) comes in a robust and lightweight carrying case.



MIR Turbine Flowmeters (comply with ATS/ERS standards)



FlowMIR: disposable turbine

Spirometry testing requires maximum accuracy and hygiene.

FlowMir is the answer to both requirements. Each turbine is calibrated with a computerized system and it is packaged individually. After patient testing both turbine and mouthpiece are thrown away.

Only in this way 100% hygiene can be guaranteed.

Option available: reusable turbine

The accuracy and the precision of the reusable turbine remains unchanged even over time.



Spirolab III® Spirometer

Technical specifications

Power supply: Rechargeable battery and mains power

Temperature sensor: semiconductor (0-45°C)

Flow sensor: bi-directional digital turbine

Flow range: ±16L/s - Volume accuracy: ±3% or 50mL

Flow accuracy: ±5% or 200mL/s

Dynamic resistance: <0.5 cmH₂O/L/s

Connectivity: USB and RS232

Display: FSTN graphic, 320 × 240 pixel

Printer/paper: Thermal, 4.4 inch (112 mm) width

Mouthpieces: Ø 1.18 inch (30 mm)

Dimensions: 12.2×8.1×2.6 inch (310×205×65 mm)

Weight: 4.2 lbs. (1.9 Kg)

Measured parameters

FVC, FEV1, FEV1/FVC%, FEV3, FEV3/FVC%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FET, Vext, Lung Age, FIVC, FIV1, FIV1/FIVC%, PIF, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MVV

Spirolab III® Spirometer with SpO2 Opt

Technical specifications

SpO2 range: 0-99%

SpO2 accuracy: ± 2% between 70-99% SpO2

Pulse Rate range: 30-254 BPM

Pulse Rate accuracy: ± 2BPM or 2%

Sleep test: Rapid Desaturation Analysis > 2,5 min. (ODI)

Prolonged Desaturation Analysis < 5 min. (NOD)

% Bradycardia Duration (<40 BPM)

% Tachycardia Duration (>120 BPM)

% of Time with SpO2 ≤ 90% (T90%, T89%, T88%, T87%)

Exercise test: Baseline, exercise, recovery with dyspnea and fatigue data entry.

MIR Medical International Research

Via del Maggiolino, 125

00155 Roma (Italy)

Tel. +39 06.22754777 - Fax. +39 06.22754785

mir@spirometry.com

MIR - Medical International Research USA, Inc.

1900 Pewaukee Road, Suite O

Waukesha, WI 53188

Phone: (262) 565-6797 - Fax: (262) 364-2030

mirusa@spirometry.com