

AMEDTEC *ECG pro*[®]



Holter-RR

Precise in function diagnosis - Easy to use

Made in Germany - Made for Europe

Technical Data

Pressure measurement range	Systolic 60 to 290 mmHg Diastolic 30 to 180 mmHg
Accuracy	+/-3 mmHg in the range indicated
Static pressure range	0 to 300 mmHg
Pulse range	30 to 240 beats per minute
Method	Oscillometric
Measurement intervals	0, 1, 2, 4, 5, 6, 12 or 30 measurements per hour
Monitoring protocols	2 programmable and 7 fixed protocols
Storage capacity	300 measurements
Operating temperatures	+10°C bis +40°C
Operating humidity	15% to 90%
Dimensions	128 mm x 75 mm x 30 mm
Weight	Approx. 240 g incl. rechargeable batteries
Power supply	2 Mignon AA alkaline or rechargeable batteries
Interfaces	Cable: serial interface RS232, converter for USB Infrared Bluetooth class 1
Standards	DIN EN 60601-1, DIN EN 60601-2, EN 1060-1, EN 1060-3, R&TTE directive 1999/5/EG

The Holter-RR blood pressure monitor fulfils the requirements of

- Association for the Advancement of Medical Instrumentation (AAMI)
- British Hypertension Society (BHS) and
- European Society of Hypertension (ESH).

AMEDTEC Medizintechnik Aue GmbH

Schneeberger Straße 5
08280 Aue
Germany

Telefon: +49 3771 59827-0
Telefax: +49 3771 59827-90

info@amedtec.de
www.amedtec.de

Produced for AMEDTEC by:

I.E.M. GmbH
Cockerillstr. 69
D-52222 Stolberg