

BB Angle adjustable and easy install stopper nozzle with pipe clamp




Features

- Female nut for fixing nozzle is easy to loosen for adjusting nozzle angle.
- Amazingly easy to drill a hole instead of threading onto a pipe and fix it on with our exclusive pipe clamp without any tool.
- For stopping spaying, if one or a few of the holes on pipe need to be stopped.
- The size for drilling the installation hole:
 - Ø 15 (14.3~15mm) - Ø 17 (16.4~17mm)
 - Ø 20 (19.0~20mm) 8.35~9m/m
- Size of clamp:
 - 1" (OD34 +/-0.3mm) - 1-1/4" (OD42+/-0.3mm)
 - 1-1/2" (OD48 +/-0.4mm)

Applications

- Coating
- Cleaning



Material	Serie	Unit (mm)			Pipe Size	Weight (g)
		A	B	C		
Plastic	BB	52	64	72	-	63.2

Appearance dimensions may vary depending on model, material. Please ask for details.

Material

- Nozzle part: PP
- Nut: fiberglass, Strengthening PP
- Pipe clamp: Stainless 316
- Sealing ring: NBR

TB Angle adjustable and easy install nozzle thread adapter with pipe clamp




Features

- Female nut for fixing nozzle is easy to loosen for adjusting nozzle angle.
- A mazingly easy to drill a hole instead of threading onto a pipe and fix it on with our exclusive pipe clamp without any tool.
- This accessory is available with a 1/4" or 3/8" PT female thread for flexible use with other kind of nozzles.
- The size for drilling the installation hole:
 - Ø 15 (14.3~15mm) - Ø 17 (16.4~17mm)
 - Ø 20 (19.0~20mm)
- Size of clamp:
 - 1" (OD34 +/-0.3mm) - 1-1/4" (OD42+/-0.3mm)
 - 1-1/2" (OD48 +/-0.4mm)

Applications

- Coating
- Cleaning



Material	Serie	Unit (mm)			Pipe Size	Weight (g)
		A	B	C		
Plastic	TB	52	48	56	-	64

Appearance dimensions may vary depending on model, material. Please ask for details.

Material

- Nozzle part: fiberglass, Strengthening PP
- Nut: fiberglass, Strengthening PP
- Pipe clamp: Stainless 316
- Sealing ring: NBR