

3" Label Printer



- 3 inch print width
- 6 inch/sec ultra high print speed
- Support 2D barcode printing
- Thermal continuous and sticker paper supported
- Label paper auto positioned
- Module design for different application
- Support print media in 16mm to 82mm range, easy operation design
- Paper auto checkout and temperature auto controlled function
- Simplified Chinese, Traditional Chinese and Korean character supported
- Label paper peel-off and tear-off modes optional
- Compatible with various label software
- BMP, PCX, BAS files download and storage supported



LP-3150TN

Model		LP-3150TN
Print	Print method	Direct thermal line
	Print width	3inch
	Resolution	203dpi
	Print speed	3~6inch/s
	Interface	Serial+USB+Ethernet, Parallel+USB
	Media	Diameter:25~85mm; Width:16~82mm
	Print head	Temperature sensor: thermal sensitive resistance; Position sensor: microswitch
	Paper presence	Photoelectricity sensor
Character & Barcode	Enlargement	1to10 times enlargement in both directions. 0°、90°、270°、360°rotation
	Barcode type	CODE128/EAN128/ITF/CODE39/CODE93/EAN13/EAN13+2/EAN13+5/EAN8/EAN8+2 EAN8+5/CODABAR/POSTNET/UPC-A/UPCA+2/UPCA+5/UPC-E/UPCE+2/UPC-E+5 CPOST/MSI/MSIC/PLESSEY/ITF14/EAN14/QRCODE(GP-3150TI)
	Character Size	FONT 0 to FONT 8 Simplified/Traditional Chinese /Korean
	Fonts	GB2312
Buffer	Data	2M bytes
	NV Flash	2M bytes
Power	Cashdrawer out	DC 24V/1A
	Power supply	DC 24V/2A
	Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2A
Physical Properties	Weight	1.65kg
	Dimension	230 x 158 x 147mm(L x W x H)
Environment	Work environment	Temperature: 0 ~ 45℃, Humidity: 10 ~ 80%
	Storage environment	Temperature: -10 ~ 60℃, Humidity: 10 ~ 90%
Reliability	Mechanism	150km

Serial Port Specification

Item	Specification
Baud rate	2400, 4800, 9600, 19200, 38400, 57600, 115200bps
Data bit	8
Equal bit	—
Ending bit	1
Control method	H/W BUSY,Xon/Xoff

USB Port Specification

Compliant to USB version 1.1

