

Diesel Fuel Treatment

Stock #:
C24

12 pack

32 fl oz./ 946 mL

Unit UPC: 0 89269 00024 2

Carton UPC: 1 00 89269 00024 9

Shelf Life (From Date Of Manufacture): 5+ years

Anti-Gel Formula

Super Concentrated Anti-Gel, De-Icer, Stabilizer

Prevents cold weather fuel gelling and improves fuel flow for quicker cold starts.



- Cold flow improver, wax crystal inhibitor de-icer formula lowers the pour point of the fuel as much as 50° F (10° C)
- Prevents filter plugging from wax or ice
- Keeps injectors clean
- Disperses water
- Lubricant for low sulfur fuel
- One bottle treats 250 gallons (946 L)

Directions: For best results, add Cyclo Anti-Gel Diesel Fuel Treatment to fuel tank prior to fill-up. One quart treats 500 gallons (1,893 L). Below 20°F (-6.7°C), add one quart to 250 gallons (946 L). Below 0°F (-18°C), add one quart to 150 gallons (568 L).



Cyclo Industries, Inc. | 902 South US Highway 1 | Jupiter, FL | 33477 | USA | Customer Service 800.843.7813



A division of Pidilite USA, Inc.
Source Code: W-CY1211-111

www.cyclo.com