

SAFETY DATA SHEET



Jotafloor Solvent Free Primer - Comp. A

1. Identification of the substance/preparation and company/undertaking

Product name and/or code : Jotafloor Solvent Free Primer - Comp. A

Supplier/Manufacturer : Jotun Paints (Europe) Ltd.
Stather Road
Flixborough, Scunthorpe
North Lincolnshire
DN15 8RR
England

Tel: +44 17 24 40 00 00
Fax: +44 17 24 40 01 00

Emergency telephone number : Contact National Poison Centre via Hospital or Registered Medical Practitioner

2. Composition/information on ingredients

Chemical name*	CAS no.	EC number	%	Classification
epoxy resin (MW < 700)	25068-38-6	500-033-5	50 - 100	Xi; R36/38 R43
oxirane, mono[(c12-14-alkyloxy)methyl]derivs	68609-97-2	271-846-8	10 - 25	N; R51/53 Xi; R38 R43
benzyl alcohol	100-51-6	202-859-9	2.5 - 10	Xn; R20/22
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4		1 - 2.5	Xi; R36/38 R43 N; R51/53
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.



Irritant



Dangerous for the environment.

The preparation may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect.

4. First-aid measures

First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from: oxidising agents, strong alkalis, strong acids.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use respiratory mask with charcoal and dust filter when spraying this product.(as filter combination A2-P2).In confined spaces, use compressed-air or fresh-air respiratory equipment.When use of roller or brush, consider use of charcoalfilter (A2).
- Skin and body** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

- Hands** : For prolonged or repeated handling, use gloves: nitrile.
- Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

9. Physical and chemical properties

- Physical state** : Liquid.
- Odour** : Characteristic.
- Colour** : Various colours.
- Flash point** : Closed cup: 100°C (212°F).
- Density** : 1.1 g/cm³
- Lower explosion limit** : The greatest known range is Lower: 1.3% Upper: 13% (benzyl alcohol)
- Solubility** : Insoluble in cold water, hot water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

Contains (reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700), Oxirane, mono[(C12-14-alkyloxy)methyl]derivs, phenol, polymer with formaldehyde, glycidyl ether). May produce an allergic reaction.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
epoxy resin (MW < 700)	Trout (LC50)	96 hour/hours	1.5 mg/l
	Daphnia (EC50)	48 hour/hours	3.6 mg/l
oxirane, mono[(c12-14-alkyloxy)methyl]derivs	Daphnia (EC50)	48 hour/hours	<10 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	10 mg/l
	Pimephales promelas (LC50)	96 hour/hours	460 mg/l
benzyl alcohol	Trout (LC50)	96 hour/hours	7.5 mg/l
	Daphnia (EC50)	48 hour/hours	3.3 mg/l

13. Disposal considerations

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

European waste catalogue (EWC) : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

14. Transport information

International transport regulations

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW < 700))

UN Number : 3082

Class : 9

Sub-risk : -

Packing group : III

Label :



Additional information

ADR / RID : Hazard identification number: 90

IMDG : Emergency schedules (EmS): F-A, S-F
Marine pollutant: No.

IATA : -

Transport in accordance with ADR/RID, IMDG/IMO and ICAO/IATA and national regulation.

15. Regulatory information

EU regulations : The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

Hazard symbol/symbols :



Irritant



Dangerous for the environment.

Contains : epoxy resin (MW < 700)
oxirane, mono[(c12-14-alkyloxy)methyl]derivs
phenol, polymer with formaldehyde, glycidyl ether

Risk phrases : R36/38- Irritating to eyes and skin.
R43- May cause sensitisation by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S23- Do not breathe vapour / spray.
S24- Avoid contact with skin.
S37- Wear suitable gloves.
S51- Use only in well-ventilated areas.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer. This information is provided by the present Safety Data Sheet.

16. Other information

CEPE Classification : 1

Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK) : R20/22- Harmful by inhalation and if swallowed.
R36/38- Irritating to eyes and skin.
R38- Irritating to skin.
R43- May cause sensitisation by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Notice to reader

History

Date of printing : 29.12.2005.

Date of issue : 29.12.2005.

Date of previous issue : No previous validation.

Version : 3

Date of issue : 29.12.2005.

Prepared by : Jotun Group Product Safety Department

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

 Indicates information that has changed from previously issued version.

Version 3