

Technical Data

JOTUN ANTI-SKID



Product description

Jotun Anti-Skid is aluminium oxide grains, intended to be spread into the last coat in a non-skid system. Available in coarse, medium and fine particle sizes.

Recommended use

For use on decks, floors, gangways and other areas where additional friction properties are required. The spreading is to take place in the wet film during application.

Recommended quantity

Fine particle size (180 - 250 µm) for coatings applied in 50 to 150 µm DFT, such as topcoats. The recommended usage is 1,5 - 2,0 kg per 10 litres of paint

Medium particle size (400 - 600 µm) for coatings applied in 150 to 400 µm DFT, such as Jotamastic products and thick film topcoats.

The recommended usage is 2,5 - 3,3 kg per 10 litres of paint

Coarse particle size (700 - 1000 µm) for coatings applied in 400 to 1500 µm DFT, such as Baltoflake products.

The recommended usage is 3,0 - 4,0 kg per 10 litres of paint

If a more rough surface is required, the quantity may be increased.

Physical properties

Colour	Dark
Solids (vol %)*	100 ±

Flash point	N.A.
-------------	------

*Measured according to ISO 3233:1998 (E)

Surface preparation

Coated surfaces

According to specifications for the chosen topcoat.

Other surfaces

The coating may be used on other substrates. Please contact your local Jotun office for more information.

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care.

Packing size

3 kg. in a 3 litre container.

Packing may vary from country to country according to local requirements.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Footer - English

Head Office & Nordic	Europe	Middle East	South East Asia
Jotun A/S	Jotun Paints (Europe) Ltd.	Jotun U.A.E Ltd. LLC.	Jotun (Singapore) Pte. Ltd.
P.O. Box 2021	Stather Road, Flixborough		No 11-15, Sixth Lok Yang
N-3248 Sandefjord	North Lincolnshire DN15	Al Quoz Industrial Area	Road
Norway	8RR	P.O Box 3671	Jurong
Phone +47 33 45 70 00	United Kingdom	Dubai U.A.E	Singapore 628 111
Fax +47 33 46 46 13	Phone +44 172 44 00 000	Phone +971 4 3 39 50 00	Phone +65 6265 4711
	Fax +44 172 44 00 100	Fax +971 4 3 38 06 66	Fax +65 6265 7484

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 4 NOVEMBER 2005 BY JOTUN
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED