



JOTUN

Penguard Express

Fast Drying High Solids Epoxy Coatings

SPEEDING UP THE PRODUCTION PROCESS

Penguard Express

Fast Drying High Solids Epoxy Coatings



Fast to dry

Dry to recoat after only 2 hours at 23°C

- Speeds up the process and improves efficiency of applicators, contractors and steel fabricators
- Reduces the need for space for drying of painted structures
- Reduces risk of damage during transport and handling



Low & high temperature application

Application range from -5°C to above 40°C

- Low temperature curing enables the application process to continue – even at temperatures below freezing
- Pot life of 45 minutes at 40°C enables users in hot climates to reap the benefits of Penguard Express
- Same curing agent at low and high temperatures reduces risk of errors and simplifies application



High volume solids

74% volume solids, 230g/l VOCs

- Ensures compliance with existing and future legislation
- Reduced wastage and volume of paint required
- Reduced solvent emission mean less environmental impact and safer to use



Optimum topcoat hiding power

Colour Management Concept

- Colours designed to ensure optimum hiding power by any selected topcoat colour
- Reduction in topcoat thickness requirement



Broad dry film thickness range

Application range from 75µm to 250µm DFT

- Easy application with good flow and film formation at 75µm combined with no sagging at 250µm in one coat ensures a wide flexibility in application
- Primer and intermediate coat can be applied as a single coat
- Improved efficiency – saves application time – saves money

3 choices for Tailored Protection

Penguard Express

Penguard Express is a fast drying, high solids 2-pack epoxy coating which may be applied in high film thickness and at lower temperatures. It is for use as an anti-corrosive primer or intermediate coat for the protection of steel and other substrates in atmospheric exposure. The fast dry-to-recoat and dry-to-handle times allow for increased throughput and efficiency during the paint application process.

Penguard Express ZP

Penguard Express ZP offers all the benefits of Penguard Express. It is pigmented with zinc phosphate for increased corrosion protection and is the natural choice as a first coat for protection of metal structures exposed in highly corrosive environments.

Penguard Express MIO

Penguard Express MIO is reinforced with micaceous iron oxide pigments for increased barrier effect. This barrier effect is provided by overlapping layers of the MIO pigments which prevent moisture penetrating through the paint film. It further provides increased hardness and improved adhesion of subsequent coats.

Product Data

Dry film thickness μm (min/max)	75 – 250			
Solids (vol%)	74 \pm 2			
Colours:				
Penguard Express	Grey, Red, Buff, Light Red, Turquoise			
Penguard Express ZP	Grey, Red			
Penguard Express MIO	Grey, Red			
Mixing ratio	4 parts Comp. A (base) 1 part Comp. B (curing agent)			
Pot life (23°C)	2 hours (reduced at higher temperature)			
Drying times:	40°C	23°C	10°C	-5°C
Surface dry	0.5 hr	1 hr	2 hrs	16 hrs
Dry to recoat (minimum)	1 hr	2 hrs	4 hrs	24 hrs

Reducing recoating times or shortening dry-to-handle periods can offer real benefits – especially in production processes

These are exactly the features provided by Penguard Express

The Penguard Express range is designed to speed up the production process. Each of the three products – Penguard Express, Penguard Express ZP and Penguard Express MIO – provides fast dry-to-recoat and fast dry-to-handle times. These are the essential elements that increase the speed and efficiency for paint contractors and fabrication lines.

Penguard Express is designed for protection of structural steel, external tanks, pipes, cranes and numerous steel structures and objects. Coating systems for such structures must be specified according to the particular corrosive environment and expected lifetime. The common factor with Penguard Express products is that they are fast drying and high build epoxies, allowing the coating system to be completed within one day in most cases, even at low temperatures.

Exposed Steel Structures

Steel structures which are exposed to heavy atmospheric environments, such as onshore and offshore oil & gas installations, cranes, bridges, power plants and exteriors of tanks, need a coating system that provides long term, durable protection.

In such cases the coating system will often be based on a zinc rich primer, followed by 1 or 2 coats of high build epoxy with a polyurethane topcoat. Penguard Express is designed to provide excellent protection and strong adhesion to both the zinc primer and the topcoat in such coating systems.

Using Penguard Express it is possible to apply even a 4 coat system in one day. At 10°C this can be completed within 10 hours. In hot climates where the steel substrate may reach 40°C, it can even be completed in less than 3 hours.

EXPOSED STEEL STRUCTURES			Dry to recoat (minimum)		
Coat no.	Product	DFT μm	10°C	23°C	40°C
1	Barrier	50	2 hrs	1.5 hrs	40 min
2	Penguard Express	125	4 hrs	2 hrs	1 hr
3	Penguard Express	125	4 hrs	2 hrs	1 hr
4	Hardtop AS/Hardtop XP	50	-	-	-



Structural Steel

Structural steel for office blocks, sport stadia, exhibition halls and infrastructure projects are usually protected with one or two coats of an epoxy – with or without zinc phosphate and MIO-pigmentation. Where a good cosmetic appearance is desired, a polyurethane topcoat is often part of the coating system.

Application of a 3 coat system, including Penguard Express, can be completed within 8 hours at 10°C or within just 2 hours should the temperature reach 40°C.

STRUCTURAL STEEL		Dry to recoat (minimum)			
Coat no.	Product	DFT μm	10°C	23°C	40°C
1	Penguard Express ZP	75	4 hrs	2 hrs	1 hr
2	Penguard Express MIO	125	4 hrs	2 hrs	1 hr
3	Hardtop AS/Hardtop XP	50	-	-	-



Penguard Express

Appreciated by customers across the world

Jotun is proud to record that, since its launch, an area equivalent to more than twice the area of Denmark* has been painted with Penguard Express – surely proof of the high quality of the product and appreciation of its features.

Penguard Express has been applied on a wide range of areas in exposures that range from mild to the harshest environments.





* Denmark: 43,069 sq km x 2
(16,629 sq miles x 2)



Jotun challenged the performance of Penguard Express with testing, undertaken at independent laboratories, of systems according to the requirements of 'System 1' ISO 20340/NORSOK M501 rev.5.

The results were as follows:

System	DFT μm	Approved
Resist 86	75	
Penguard Express	175	
Hardtop AS	40	
Total	290	
Barrier	75	
Penguard Express	150	
Hardtop XP	60	
Total	285	

Jotun worldwide

Jotun Coatings and Jotun Paints Divisions of Jotun A/S Legal Jotun entities world wide are listed.

For details of Branch offices and Jotun representation in countries not listed, please visit jotun.com

AUSTRALIA

Jotun Australia Pty. Ltd.,
P.O. Box 105, Altona North,
9 Cawley Road,
BROOKLYN, VIC 3025
Tel: +61 3 9314 0722
Fax: +61 3 9314 0423

BRAZIL

Jotun Brasil Ltda.
Av Santa Luzia, 2084 - Santa Luzia
24.722-315 São Gonçalo
RIO DE JANEIRO
Tel: +55 21 2776 1313
Fax: +55 21 2776 2263

P.R. of CHINA

Jotun Coatings (Zhangjiagang) Co. Ltd.
Jotun COSCO Marine Coatings
(Qingdao) Co. Ltd.
Floor 20, Jiu Shi Mansions,
No. 28 Zhong Shan Road (South)
SHANGHAI 200010
Tel: +86 21 6333 080 0
Fax: +86 21 6326 968 6

Jotun Coatings (Zhangjiagang) Co. Ltd.
Jotun COSCO Marine Coatings
(Qingdao) Co. Ltd.
Room 709-12, Goldlion Digital Network
Centre, 138 Tiyu Road East,
GUANGZHOU, 510620
Tel: +86 20 38 78 07 49
Fax: +86 20 38 78 19 66

HONG KONG

Jotun COSCO Marine Coatings (H.K.) Ltd
Room 1208, 12/F, Stanhope House
734 King's Road, Quarry Bay
HONG KONG
Tel: +852 2527 6466
Fax: +852 2861 1307

DENMARK

Jotun Danmark A/S Jotun Coatings
Columbusvej 5, 2860 Søborg,
COPENHAGEN
Tel: +45 4492 9400
Fax: +45 4492 9401

EGYPT

El Mohandes Jotun S.A.E.
El Sheikh Aly Gad El Haq Street
Florida Mall,
Masaken Sheraton – 4th Floor
CAIRO
Tel: +20 2265 1800
Fax: +20 2265 1801

FINLAND

Nor-Maali OY
Vanhatie 20, 15240 LAHTI
Tel: +358 3 874 650
Fax: +358 3 874 6550

FRANCE

Jotun France S.A.
22/24 Rue du President Wilson, Bat.A
92300 LEVALLOIS PERRET
Tel: +33 1 4519 3882
Fax: +33 1 4519 3894

GERMANY

Jotun (Deutschland) GmbH
Haferweg 38
22769 HAMBURG
Tel: +49 40 851 960
Fax: +49 40 856 234

GREAT BRITAIN

Jotun Paints (Europe) Ltd.
Stather Road, Flixborough,
SCUNTHORPE DN15 8RR
Tel: +44 1724 400 000
Fax: +44 1724 400 100

GREECE

Jotun Hellas Ltd.
18, Vouliagmenis Avenue,
Glyfada
ATHENS 16675
Tel: +30 210 42 85 980-82
+30 210 42 86 035-37
Fax: +30 210 42 85 983/
+30 210 42 87 237

INDIA

Jotun India Pvt Ltd.
204 & 205 Ascot Centre,
Sahar Road, Andheri (East)
MUMBAI 400 099
Tel: +91 22 2822 4600
+91 22 2820 5900 (+fax)
Fax: +91 22 2820 5900

INDONESIA

P.T. Jotun Indonesia Paints and Chemicals
Kawasan Industri MM2100
Blok KK-1, Cikarang Barat
Bekasi 17520
Tel: +62 21 8998 2657
Fax: +62 21 8998 2658

IRELAND

Jotun (Ireland) Ltd.,
Unit K7, Marina Commercial Park,
Centre Park Road, CORK
Tel: +353 214 965955
Fax: +353 214 965992

ITALY

Jotun Italia S.P.A.
Via Petronio, 8, Zona Ind. Noghere
34147 - MUGGIA (TRIESTE)
Tel: +39 040 23 98204
Fax: +39 040 23 98222

KOREA (SOUTH)

Chokwang-Jotun Ltd.
30th Block Jisa Science Park,
1205 Jisa-dong, Gangseo-gu,
BUSAN 618-230
Tel: +82 517 976 000
Fax: +82 517 117 735

LIBYA

Jotun Libya J.S.Co
Al Mumtaz Imp. of Paints and Equipm. Co.
P.O. Box 6850
Hail Al Andalous district
TRIPOLI
Tel: +218 214777811
Fax: +218 214780718

MALAYSIA

Jotun (Malaysia) Sdn. Bhd.
Lot 7 Persiaran Perusahaan,
Section 23, P.O. Box 7050
40700 SHAH ALAM
Tel: +60 351 235 500
Fax: +60 351 235 632

THE NETHERLANDS

Jotun B.V.
Postbus 208
3200 AE SPIJKENISSE
Visiting address:
Curieweg 11b, 3208 KJ Spijkennisse
ROTTERDAM
Tel: +31 181 678 300
Fax: +31 181 617 899

NORWAY

Jotun A/S
P.O. Box 2021,
3202 SANDEFJORD
Visiting address:
Hystadveien 167, 3209 Sandefjord
Tel: +47 33 45 70 00
Fax: +47 33 45 79 00

OMAN

Jotun Paints Co. LLC
Rusayl Ind. Estate, Road No.10
P.O. Box 672 Code 111, MUSCAT
Tel: +968 2444 6100
Fax: +968 2444 6105

PAKISTAN

Jotun Pakistan (Pvt.) Limited
Plot no. 2-H, Sector 5
Korangi Industrial Area, KARACHI
Tel: +92 213 5121 491-2
Fax: +92 213 5121 493

POLAND

Jotun Polska Sp.zo.o.
Ul. 10 Lutego 16, 81-364 GDYNIA
Tel: +48 58 555 1515
Fax: +48 58 781 9692

RUSSIA

Jotun Paints O.O.O.
Varshavskaya Str., 23/2, Office 53
196128 ST. PETERSBURG
Tel: +7 81 2332 0080 / 2785 0034
Fax: +7 81 2783 0525

SAUDI ARABIA

Jotun Saudia Co. Ltd.
Jeddah Industrial City, Phase 3,
P.O. Box 34698, JEDDAH 21478
Tel: +966 2635 0535 / 2636 1271
Fax: +966 2636 2483

SINGAPORE

Jotun (Singapore) Pte. Ltd.
11&15 Sixth Lok Yang Road,
Jurong, SINGAPORE 628111
Tel: +65 650 882 88
Fax: +65 6265 7484

SOUTH AFRICA

Jotun Paints South Africa (PTY) Ltd.
Wimbledon Road, P.O.Box 187
BLACKHEATH 7581
Tel: +27 21 905 1070
Fax: +27 21 905 1652

SPAIN

Jotun Iberica S.A.
Poligon Santa Rita,
Calle Estatica no. 3,
08755 Castellbisbal,
BARCELONA
Tel: +34 937 711 800
Fax: +34 937 711 801

SWEDEN

Jotun Sverige AB
Amata Nakom Ind. Estate (BIPII)
700/353 Moo 6 Tumbol
Donhualoh, Amphur Muang
CHONBURI 2000
Tel: +66 38 214 824-6/214 347-51
Fax: +66 38 214 373/375

THAILAND

Jotun Thailand Ltd
Amata Nakom Ind. Estate (BIPII)
700/353 Moo 6 Tumbol
Donhualoh, Amphur Muang
CHONBURI 2000
Tel: +66 38 214 824-6/214 347-51
Fax: +66 38 214 373/375

TURKEY

Jotun Boya San. ve Ticaret. A.S.
Yeni Camlik Caddesi, Ayaz Sok. No. 2/4,
4. Levent,
ISTANBUL 34418
Tel: +90 21 2279 7878
Fax: +90 21 2279 2549

U. A. E.

Abu Dhabi
Jotun Abu Dhabi (LLC)
P.O. Box 3714, Mussafah
ABU DHABI
Tel: +971 2551 0300
Fax: +971 2551 0232

Dubai
Jotun U.A.E. Ltd. (LLC)
P.O. Box 3671,
Al Quoz Industrial Area
DUBAI
Tel: +971 4339 5000
Fax: +971 4338 0666

USA

Jotun Paints, Inc.
9203 Highway 23, P.O. Box 159,
Belle Chasse, LA 70037
Tel: +1 800 229 3538 /
+1 504 394 3538
Fax: +1 504 394 3726

VIETNAM

Jotun Paints (Vietnam) Co. Ltd.
Song Than Industrial. Zone,
No.1 Street 10,
Di An District, Binh Duong Province
Tel: +84 65 074 2206-9
Fax: +84 65 074 2205

YEMEN

Jotun Yemen Paints Co. Ltd
P.O. Box 70183, Al Alam
ADEN
Tel: +967 2820 546-9
Fax: +967 2249 362

Jotun A/S

P.O. Box 2021,
N-3202 Sandefjord, Norway
Tel: +47 33 45 70 00
jotun.com



Jotun Protects Property