

## TP-3250N SERIES



- 250mm/sec ultra high print speed
- Paper near end sensor supported (TP-3250IIN, TP3250IIIN)
- Printer status monitoring
- Receipt printout alerting and error alarm function
- GB18030 large fonts and various international code pages supported
- Built in Webconfig to provide easy and convenient Ethernet setting
- Support various printer ports and support WAN connection print
- High speed driver printing mode, serial port speed is 66% faster
- Auto print recovering when network disconnected
- Virtual serial port for USB connection, USB port supports OPOS application
- 100MB network interface card makes the connection and print much faster, stop receipts misprinting



**TP-3250IIN**

Model	TP-3250IIN	TP-3250IIIN	TP-3250IVN	TP-3250VN	
Print	Print method	Direct thermal line			
	Print width	64/72mm			
	Dot density	512dot/line or 576dot/line			
	Print speed	250mm/s			
	Interface	Serial+USB+Ethernet、Paralle+USB			
	Paper diameter	83mm			
	Line space	3.75mm(can be adjusted by sending commands)			
Character & Barcode	Columns	Font A - 42columns or 48columns / Font B - 56columns or 64columns / Simplified/Traditional Chinese - 21columns or 24columns			
	Character Size	ANK Font Font A: 12x24dots Font B: 9x17dots Simplified/Traditional Chinese: 24x24dots			
	Code page	PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/Iran/I/Latvian/Arabic/PT151,1251/PC737/WPC1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)			
	Barcode type	UPC-A/UPC-E/IAN13(EAN13)/IAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128			
	Fonts	GB18030			
Buffer	Data	128K bytes			
	NV Flash	256K bytes			
Power	Cashdrawer out	DC 24V/1A			
	Power supply	DC 24V/2A			
	Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2A			
Physical Properties	Weight	1.50KG	1.70KG	1.40KG	1.65KG
	Dimension	195 x 142 x 142mm	202 x 140 x 149mm	210 x 145 x 140mm	186 x 145 x 140mm
Environment	Work environment	Temperature: 0 ~ 45°C, Humidity: 10 ~ 80%			
	Storage environment	Temperature: -10 ~ 60°C, Humidity: 10 ~ 90%			
Reliability	Mechanism	150km			



**TP-3250IN**



**TP-3250IIIN**



**TP-3250IVN**



**TP-3250VN**