

CHARGER RANGE AND CAPACITIES

Model Number	Input Voltage Range	No of cells	STANDARD CHARGE Max Battery Capacity* (AH)	OPPORTUNITY CHARGE Max Charger Capacity (AH)
HF-1-24-300-1	1	12	300	231
HF-1-24-600-1	1		600	462
HF-1-24-875-1	2		875	673
HF-3-24-1050-1	3		1050	877
HF-1-36-300-1	1	18	300	231
HF-1-36-600-1	1		600	462
HF-1-36-750-1	2		750	577
HF-3-36-875-1	2		875	673
HF-1-48-240-1	1	24	240	184
HF-1-48-475-1	1		475	365
HF-3-48-750-1	3		750	577

* Battery capacity for 8hr charge.

CHARGER INPUT/OUTPUT AMPS & WEIGHT

No of cells	Model Number	AH*	DC AMPS	AC Amps @ AC Volts			Weight (Kg)
				208	240	415	
12	HF-1-24-300-1	300	37	8.9	7.71	4.5	18
	HF-1-24-600-1	600	74	7.23	6.27	3.6	24
	HF-1-24-875-1	875	137				30
	HF-3-24-1050-1	1050	163	26.7	23.1	13	30
18	HF-1-36-300-1	300	37	11.1	9.64	5.6	18
	HF-1-36-600-1	600	74	22.2	19.3	11	24
	HF-1-36-750-1	750	93	27.7	24.1	13.8	30
	HF-3-36-875-1	875	137	33.4	28.9	17	30
24	HF-1-48-240-1	260	32	12.8	11.1	6.4	18
	HF-1-48-475-1	475	59	25.6	22.2	13	24
	HF-3-48-750-1	750	93	38.4	33.3	19	30

* for Standard Charge RTC 8Hrs