

Floor Stand Series

QP1580FS - 15U




Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Top Cover
Vented Design



Equipment
Tray



19" 5 Gang
Power Distribution



Earthing
cable



Side Panel
Latch



19" Panel
Mounting

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
QP1580FS	15	812	600	800	835 x 612 x 812	63

☒ Black
 ☐ Grey
 ☐ Beige

* Customized sizes available upon request
 * Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD
 NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
 Taman Indah Subang Uep, 47150 Subang Jaya,
 Selangor Darul Ehsan.
 +603 - 8081 2216 sales@gvisb.com.my

Penang Branch
 737-6-9, Sri Nibong Complex,
 Jalan Sultan Azlan Shah,
 11900 Penang
 +604 - 642 8753

Johor Branch
 No.49 & 49A, Jalan Pulau 23,
 Taman Pulau Utama, 81300
 Skudai, Johor, Malaysia
 +607 - 520 5236