

# Trunking Rack Series


**QP42100TR - 42U**


## Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Wheel  
Stopper



Equipment  
Tray



19" 5 Gang Power  
Distribution



Ventilation  
Fan



Earthing  
cable



Side Panel  
Latch

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
QP42100TR	42	2012	800	1000	2035 x 812 x 1012	113

☐ Black
 ☐ Grey
 ☐ Beige

\* Customized sizes available upon request

\* P = perforated door

### GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,  
 Taman Indah Subang Uep, 47150 Subang Jaya,  
 Selangor Darul Ehsan. E-mail: [sales@gvisb.com.my](mailto:sales@gvisb.com.my)  
 +603 - 8081 2216 Website: [www.gvisb.com.my](http://www.gvisb.com.my)

### Penang Branch

737-6-9, Sri Nibong Complex,  
 Jalan Sultan Azlan Shah,  
 11900 Penang  
 +604 - 642 8753

### Johor Branch

No.49 & 49A, Jalan Pulau 23,  
 Taman Pulau Utama, 81300  
 Skudai, Johor, Malaysia  
 +607 - 520 5236