







oor Stand






Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
 Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg













Top Cover Vented Design

Equipment Trav

19" 5 Gang Power Distribution

Earthing cable

Side Panel Latch

19" Panel Mounting

Model	Capasity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)	PDU (nos)
X1580FS	15	850	600	800	862 x 610 x 810	93	5
X1880FS	18	980	600	800	992 x 610 x 810	97.5	5
X2480FS	24	1250	600	800	1262 x 610 x 810	105.5	5
X2880FS	28	1420	600	800	1432 x 610 x 810	111.5	5
X3380FS	33	1650	600	800	1662x 610 x 810	120	12
X3780FS	37	1830	600	800	1842 x 610 x 810	125	12
X4280FS	42	2050	600	800	2062 x 610 x 810	133.5	12
X42100FS	42	2050	600	1000	2062 x 610 x 1010	143	12

Black



Beige

^{*} Customized sizes available upon request



GV INDUSTRIES SDN. BHD NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang, Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

Penang Branch 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

Johor Branch No.49 & 49A, Jalan Pulai 23, Taman Pulai Utama, <u>81300</u>