

## oor Stand













## Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
  Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg



Top Cover


Vented Design













**Earthing** cable



Side Panel Latch



19" Panel Mounting

Model	Capasity	Height	Width	Depth	Packing Dimension	Weight	PDU
	(U)	(mm)	(mm)	(mm)	(H*W*D)	(kg)	(nos)
XP1880FS	18	980	600	800	992 x 612 x 812	97.5	5



Grey

Beige

\* Product shown is for illustration purpose only



**GV INDUSTRIES SDN. BHD** *NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,* Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvisb.com.mv **Penang Branch** 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang +604 - 642 8753

Johor Branch

<sup>\*</sup> Customized sizes available upon request